

10855

C36322

**SAFETY DATA SHEET**

**PURITY™ FG WO WHITE MINERAL OIL 15**

000003000154



Version 4.0

Revision Date 2017/02/01

Print Date 2017/02/01

**SECTION 1. IDENTIFICATION**

Product name : PURITY™ FG WO WHITE MINERAL OIL 15

Product code : PFWO15P20, PFWO15IBC, PFWO15DRX, PFWO15, PFWO15BLK

**Manufacturer or supplier's details**

Petro-Canada America Lubricants Inc.  
 115N Oak Park Avenue #1C  
 Oak Park IL 60301-1366  
 United States

**Emergency telephone number**

Petro-Canada Lubricants Inc.: +1 905-403-5770;  
 CHEMTREC Transport Emergency: 1-800-424-9300;  
 Poison Control Centre: Consult local telephone directory for emergency number(s).

**Recommended use of the chemical and restrictions on use**

Recommended use : Purity FG WO White Mineral Oil 15 is a highly refined white mineral oil intended for the food processing industry.

NSF 3H and H1 Registered.

This product complies with FDA 21 CFR 172.878 "White Mineral Oil" and 21 CFR 178.3620(a) regulations for direct food contact.

Prepared by : Product Safety: +1 905-804-4752

**SECTION 2. HAZARDS IDENTIFICATION**

**Emergency Overview**

Appearance	viscous liquid
Colour	Clear and bright
Odour	Mild petroleum oil like.

**GHS Classification**

Aspiration hazard : Category 1

**GHS label elements**

**SAFETY DATA SHEET**

**PURITY™ FG WO WHITE MINERAL OIL 15**

000003000154



Version 4.0

Revision Date 2017/02/01

Print Date 2017/02/01

Hazard pictograms



Signal word

: Danger

Hazard statements

: May be fatal if swallowed and enters airways.

Precautionary statements

: **Response:**  
IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
Do NOT induce vomiting.  
**Storage:**  
Store locked up.  
**Disposal:**  
Dispose of contents/ container to an approved waste disposal plant.

**Potential Health Effects**

Primary Routes of Entry

: Eye contact  
Ingestion  
Inhalation  
Skin contact

Aggravated Medical Condition

: None known.

**Other hazards**

None known.

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture

: Substance

**Hazardous components**

Chemical name	CAS-No.	Concentration
White mineral oil (petroleum)	8042-47-5	100 %

Internet: [lubricants.petro-canada.com/sds](http://lubricants.petro-canada.com/sds)

™ Owned or used under license by Petro-Canada Lubricants Inc.

Page: 2 / 10

**SAFETY DATA SHEET**

**PURITY™ FG WO WHITE MINERAL OIL 15**

000003000154



Version 4.0

Revision Date 2017/02/01

Print Date 2017/02/01

Material can create slippery conditions.

**Environmental precautions** : Do not allow uncontrolled discharge of product into the environment.

**Methods and materials for containment and cleaning up** : Prevent further leakage or spillage if safe to do so.  
Remove all sources of ignition.  
Soak up with inert absorbent material.  
Non-sparking tools should be used.  
Ensure adequate ventilation.  
Contact the proper local authorities.

**SECTION 7. HANDLING AND STORAGE**

**Advice on safe handling** : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Use only with adequate ventilation.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin, eyes and clothing.  
Do not ingest.  
Keep away from heat and sources of ignition.  
Keep container closed when not in use.

**Conditions for safe storage** : Store in original container.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Keep in a dry, cool and well-ventilated place.  
Keep in properly labelled containers.  
To maintain product quality, do not store in heat or direct sunlight.  
Keep locked up or in an area accessible only to qualified or authorised persons.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
White mineral oil (petroleum)	8042-47-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

**Engineering measures** : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

# SAFETY DATA SHEET

## PURITY™ FG WO WHITE MINERAL OIL 15



000003000154

Version 4.0

Revision Date 2017/02/01

Print Date 2017/02/01

### SECTION 4. FIRST AID MEASURES

- |   |   |   |
|---|---|---|
| If inhaled  | : | Move to fresh air.<br>Artificial respiration and/or oxygen may be necessary.<br>Seek medical advice.  |
| In case of skin contact                                     | : | In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.<br>Wash skin thoroughly with soap and water or use recognized skin cleanser.<br>Wash clothing before reuse.<br>Seek medical advice. |
| In case of eye contact                                      | : | Remove contact lenses.<br>Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.<br>Obtain medical attention.   |
| If swallowed  | : | Rinse mouth with water.<br>DO NOT induce vomiting unless directed to do so by a physician or poison control center.<br>Never give anything by mouth to an unconscious person.<br>Seek medical advice.   |
| Most important symptoms and effects, both acute and delayed | : | First aider needs to protect himself.   |

### SECTION 5. FIREFIGHTING MEASURES

- |                                       |   |  |
|---------------------------------------|---|--|
| Suitable extinguishing media          | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  |
| Unsuitable extinguishing media        | : | No information available.  |
| Specific hazards during fire-fighting | : | Cool closed containers exposed to fire with water spray.   |
| Hazardous combustion products         | : | Carbon oxides (CO, CO <sub>2</sub> ), smoke and irritating vapours as products of incomplete combustion. |
| Further information                   | : | Prevent fire extinguishing water from contaminating surface water or the ground water system.            |

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- |   |   |   |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.<br>Ensure adequate ventilation.<br>Evacuate personnel to safe areas. |
|---|---|---|

Internet: [lubricants.petro-canada.com/sds](http://lubricants.petro-canada.com/sds)  
™ Owned or used under license by Petro-Canada Lubricants Inc.

Page: 3 / 10

# SAFETY DATA SHEET

## PURITY™ FG WO WHITE MINERAL OIL 15



000003000154

Version 4.0

Revision Date 2017/02/01

Print Date 2017/02/01

Evaporation rate	: No data available
Flammability	: Low fire hazard. This material must be heated before ignition will occur.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Density	: 0.85 kg/l (15 °C / 59 °F)
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Viscosity	
Viscosity, kinematic	: 15.00 cSt (40 °C / 104 °F) 3.43 cSt (100 °C / 212 °F)
Explosive properties	: Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

### SECTION 10. STABILITY AND REACTIVITY

Possibility of hazardous reactions	: Hazardous polymerisation does not occur. Stable under normal conditions.
Conditions to avoid	: No data available
Incompatible materials	: Reactive with oxidising agents.
Hazardous decomposition products	: May release COx, smoke and irritating vapours when heated to decomposition.

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Eye contact  
Ingestion  
Inhalation  
Skin contact

#### Acute toxicity

#### Product:

Internet: [lubricants.petro-canada.com/sds](http://lubricants.petro-canada.com/sds)  
™ Owned or used under license by Petro-Canada Lubricants Inc.

Page: 6 / 10

# SAFETY DATA SHEET

## PURITY™ FG WO WHITE MINERAL OIL 15



000003000154

Version 4.0

Revision Date 2017/02/01

Print Date 2017/02/01

### Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Filter type : organic vapour filter
- Hand protection Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).
- Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Protective measures : Wash contaminated clothing before re-use.
- Hygiene measures : Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : viscous liquid
- Colour : Clear and bright
- Odour : Mild petroleum oil like.
- Odour Threshold : No data available
- pH : No data available
- Pour point : -18 °C (-0.40 °F)
- Boiling point/boiling range : No data available
- Flash point : 175 °C (347 °F)  
Method: Cleveland open cup
- Fire Point : No data available
- Auto-Ignition Temperature : No data available

**SAFETY DATA SHEET**

**PURITY™ FG WO WHITE MINERAL OIL 15**

000003000154



Version 4.0

Revision Date 2017/02/01

Print Date 2017/02/01

Acute oral toxicity : Remarks: No data available  
Acute inhalation toxicity : Remarks: No data available  
Acute dermal toxicity : Remarks: No data available

**Components:**

**White mineral oil (petroleum):**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,  
Acute inhalation toxicity : LC50 (Rat): > 5.2 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

**Skin corrosion/irritation**

**Product:**

Remarks: No data available

**Serious eye damage/eye irritation**

**Product:**

Remarks: No data available

**Respiratory or skin sensitisation**

No data available

**Germ cell mutagenicity**

No data available

**Carcinogenicity**

No data available

**Reproductive toxicity**

No data available

**STOT - single exposure**

No data available

**STOT - repeated exposure**

No data available

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

Internet: [lubricants.petro-canada.com/sds](http://lubricants.petro-canada.com/sds)  
™ Owned or used under license by Petro-Canada Lubricants Inc.

# SAFETY DATA SHEET

## PURITY™ FG WO WHITE MINERAL OIL 15

000003000154



Version 4.0

Revision Date 2017/02/01

Print Date 2017/02/01

Toxicity to fish :  
Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates :  
Remarks: No data available

Toxicity to algae :  
Remarks: No data available

Toxicity to bacteria :  
Remarks: No data available

### Persistence and degradability

#### Product:

Biodegradability :  
Remarks: No data available

#### Bioaccumulative potential

No data available

#### Mobility in soil

No data available

#### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Offer surplus and non-recyclable solutions to a licensed disposal company.  
Waste must be classified and labelled prior to recycling or disposal.  
Send to a licensed waste management company.  
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

Internet: [lubricants.petro-canada.com/sds](http://lubricants.petro-canada.com/sds)

™ Owned or used under license by Petro-Canada Lubricants Inc.

Page: 8 / 10

**SAFETY DATA SHEET**

**PURITY™ FG WO WHITE MINERAL OIL 15**

000003000154



Version 4.0

Revision Date 2017/02/01

Print Date 2017/02/01

**49 CFR**  
Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION**


The components of this product are reported in the following inventories:

<b>DSL</b>	On the inventory, or in compliance with the inventory
<b>TSCA</b>	All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
<b>IECSC</b>	On the inventory, or in compliance with the inventory
<b>EINECS</b>	On the inventory, or in compliance with the inventory
<b>AICS</b>	On the inventory, or in compliance with the inventory
<b>KECI</b>	On the inventory, or in compliance with the inventory
<b>PICCS</b>	On the inventory, or in compliance with the inventory

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA:**



**HMIS III:**

<b>HEALTH</b>	<b>3</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>PERSONAL PROTECTION</b>	<b>B</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

For Copy of SDS

: Internet: [lubricants.petro-canada.com/sds](http://lubricants.petro-canada.com/sds)  
United States, telephone: 1-800-268-5850; fax: 1-800-201-6285  
For Product Safety Information: 1 905-804-4752

Prepared by

: Product Safety: +1 905-804-4752

Revision Date

: 2017/02/01

# SAFETY DATA SHEET

## PURITY™ FG WO WHITE MINERAL OIL 15

000003000154



Version 4.0

Revision Date 2017/02/01

Print Date 2017/02/01

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.