MATERIAL SAFETY DATA SHEET

ROCK PAINT DISTRIBUTING CORPORATION 1632

NASCO WASHABLE COUNTRY SCHOOL

TRADE NAME ON LABEL

12-15129 97-15178

MSDS NUMBER

MANUFACTURER

365 SUNNYSIDE DR. P.O. BOX 482

ADDRESS

CAS NUMBER

MILTON, WI 53563

MARCH 10, 1994

DATE PREPARED

(608) 868-6873

(414) 583 8545

PHONE NUMBER (FOR INFORMATION)

PREPARED BY

SECTION 1 - MATERIAL

AND INFORMATION

COMPONENTS CHEMICAL NAME & COMMON NAMES

IDENTIFICATION

% OSHA PEL ACGIH TLY OTHER LIMITS RECORDEDED

WATER

DYE: ASSORTED NON-TOXIC COLORS

KAOLIN CLAY

CALCIUM CARBONATE

PROPYLENE GLYCOL

AS PER ASTM D-4236 AND AS PER THE ART AND CRAFT MATERIALS INSTITUTE (ACMI), INC. THIS PAINT HAS BEEN CERTIFIED NON-TOXIC.

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT ABOUT 212 F

SPECIFIC GRAVITY (H20 = 1) ABOUT 9 LBS/GAL

VAPOR PRESSURE(mm Hg & TEMPERATURE) 17 mmHG

MELTING POINT 32 F

VAPOR DENSITY (AIR=1) LIGHTER

EVAPORATION RATE (WATER=1) SLOWER

SOLUBULITY IN WATER DILUTABLE

WATER REACTIVE N/A

APPEARANCE & ODOR SLIGHT AMMONIA ODOR, OR NO ODOR PRESENT

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

PLASH POINT & METHOD USED N/A

AUTO - IGNITION TEMPERATURE N/A

FLAMMABILITY LIMITS IN AIR % BY VOLUME LEL NI/A

VEL

EXTINGUISHER MEDIA FOAM, DRY CHEMICAL, CO2, WATER SPRAY OR FOG

SPECIAL FIRE FIGHTING PROCEDURES

N/A

UNUSUAL FIRE AND EXPLOSION HAZARDS

SECTION	4 - REAC	TIVITY HAZARD DATA				
TABILITY STABLE OUNSTABLE	CONDITIONS	TO AVOID				
COMPATABILITY	MATERIALS TO	AVOID) NONE KOWN-HOWEVER P	RODUCT PROPERTIES MAY!	BE ALTERED BY MIXING WIT	TU OOLE MATERIAL	
AZARDOUS DE	COMPOSITION PR	RODUCTS THERMAL DECOMPOSITION IN T	HE PRESENCE OF AIR MAY YIE	ELD CARBON MONDATOE AND/C	R CARBON DIOXEDS	
NZARDOUS PA		CONDITIONS TO AV				
ECTION 5	- HEALTH	HAZARD DATA	A.			
UMARY ROUTES		NHALATION INGESTION SEIN ARSORTION IN NOT HAZARDA	CARCINOGEN LISTED IN	D IARCMONOGRAPH	□ OSRA	
ALTH HAZAROS	W	ACUTE	<u> </u>	P. WILL WORKENIN	O NOT LISTE	
		CHRONIC				
INS AND SYMPTO	ONS					
DICAL CONDITIO	NS GENERALLY AG	GRAVATED BY EXPOSURE				
			<u>-</u> <u>-</u>			
ERODICY FIRST		8 - SEEK MEDICAL ABRISTANCE FOR PURT				
E CONTACT D	IRECT CONTACT	T WITH EMULSION MAY RESULT IN EAST 15 MINUTES AND CONSULT A	NIPPITATION CLIMATER			
N CONTACT PE	PROLONGED OR REPEATED CONTACT WITH EMULSION MAY CAUSE SOME SKIN IRRITATION. WASH SKIN THOROUGHLY WITH SOAP AND WATER; IF DRENCHED REMOVE AND WASH CLOTHING BEFORE REUSE.					
ALATION	//A					
	IF VICTIM IS CONSCIOUS, GIVE TWO GLASSES OF WATER TO DRINK AND CALL A PHYSICIAN.					
CTION 6	- CONTROL	AND PROTECTIVE MEAS	URES			
PIRATORY PROT	TECTION (SPECIFY					
		OVES RECOMMENDED	EYE PROTECTION CHE	MICAL GOGGLES WITH E	YE GUARD	
TLATION TO BE	USED	LOCAL EXHALIST	MECHANICAL (GENERAL)	SPECIAL		
	_	OTHER (SPECIFY)			· · · · · · · · · · · · · · · · · · ·	
ERPROTECTIVE	CLOTHING AND EQ	RUPMENT N/A				
ENIC WORK PRA	CTICES					
ECTION /	- PRECAU	Tions for safe handli	ING AND USE/LEA	R PROCEDURES		
S TO BE TAKEN!	F MATERIAL IS SPA RYING MATERI	led or released IAL OR FLUSH SPILLED MATERIAL I G SEWERS, STORM DRAINS, DRAIN			t. Prevent	
S CHOP COME ME	INODS					
OSE OF PROD	DUCT IN ACCO	RDANCE WITH APPLICABLE LOCAL	,county, state and f	EDERAL REGULATIONS.		
AUTIONS TO BE	TAKEN IN HANDLIN	G AND STORAGE				
		EMPERATURE TO PROLONG SHELF	LIFE KEEP FROM FREE	ZING AND AWAY FROM	PYCHRRIVR HRAT	
	S AND/OR SPECIAL I				ONCOLOUS IN THE PARTY	