

Nasco

Fort Atkinson, WI



WORLDWIDE SERVICE TO EDUCATION • HEALTH • AGRICULTURE • INDUSTRY

901 JANESVILLE AVENUE FORT ATKINSON, WISCONSIN 53538-0901

PHONE 920-563-2446 FAX 920-563-8296

www.eNASCO.com E-MAIL info@eNASCO.com

2002

MSDS for Whirl-Pak® Bags

Whirl-Pak® bags are made of low density polyethylene (LDPE) and linear low density polyethylene (LLDPE)-separate sheets for both are attached.

A handwritten signature in cursive script, reading "Tom Valitchka".

Tom Valitchka

Director, Whirl-Pak® Sales

9-3-03

MATERIAL SAFETY DATA SHEET
ExxonMobil Chemical Company
A Division of Exxon Mobil Corporation

PAGE: 1
DATE PREPARED: SEP 6, 2000
MSDS NO.: 89001000

EXXONMOBIL LLDPE(ALL GRADES)

SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ExxonMobil LLDPE(ALL GRADES)
CHEMICAL NAME:
Polyethylene or Ethylene-Olefin Copolymer
CHEMICAL FAMILY:
Ethylene-Based Polymer
PRODUCT DESCRIPTION:
Odorless opaque white pellets or granules.

1500679	BC1063	BC1196	BC1339
1300736	BC1064	BC1239	BC1511
1300790	BC1065	BC1245	BC1348
1300792	BC1067	BC1253	BC1450
1300794	BC1182	BC1254	BC1363
BC1009	BC1183	BC1255	BC1404
BC1018	BC1185	BC1292	BC1365
BC1020	BC1186	BC1297	BC1380
BC1027	BC1187	BC1299	BC1391
BC1040	BC1193	BC1318	BC1392
BC1062	BC1195	BC1323	BC1373
			BC1401
			BC1402
			BC1463
			BC1470
			BC1270

CONTACT ADDRESS:
ExxonMobil Chemical Company,
P.O. Box 3272, Houston, Texas 77253-3272

** EMERGENCY TELEPHONE NUMBERS: (24 Hours) **
** CHEMTREC (800) 424-9300 **
** ExxonMobil Chemical Company (800) 726-2015 **

NON EMERGENCY TELEPHONE NUMBERS : (8am-5pm M-F)
FOR GENERAL PRODUCT INFORMATION CALL : (281) 870-6000
FOR HEALTH AND MEDICAL INFORMATION CALL : (281) 870-6884

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

This product is not hazardous as defined in 29 CFR1910.1200

SECTION 3 HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYE CONTACT:

Particulates may scratch eye surfaces/cause mechanical irritation.

SKIN CONTACT:

Negligible hazard at ambient temperatures (-18 to +38 degrees C; 0 to 100 degrees F).

Exposure to hot material may cause thermal burns.

INHALATION:

Negligible hazard at ambient temperature (-18 to 38 Deg C; 0 to 100 Deg F)

Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract.

INGESTION:

Minimal toxicity.

Continues on page 2

10 000 372 3702 FROM ACH SECURE JVL 04APR01 1331231 0070003N PAGE 3 OF 8

MATERIAL SAFETY DATA SHEET
ExxonMobil Chemical Company
A Division of Exxon Mobil Corporation

PAGE: 2
DATE PREPARED: SEP 5, 2000
MSDS NO.: 89001000

EXXONMOBIL LLDPE(ALL GRADES)

SECTION 4 FIRST AID MEASURES

EYE CONTACT:

This product is an inert solid. If in eye, remove as one would any foreign object.

SKIN CONTACT:

For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and get prompt medical attention. No attempt should be made to remove material from skin or to remove contaminated clothing, as the damaged flesh can be easily torn.

INHALATION:

In case of adverse exposure to vapors and/or aerosols formed at elevated temperatures, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

INGESTION:

First aid is normally not required.

SECTION 5 FIRE-FIGHTING MEASURES

FLASH POINT: 549 Deg F. METHOD: ASTM E136 NOTE: Estimated Minimum

FLAMMABLE LIMITS: NOTE: Not applicable

AUTOIGNITION TEMP.: 549 Deg F. NOTE: Estimated Minimum

GENERAL HAZARD

Solid material, may burn at or above the flashpoint, and airborne dust may explode if ignited .

If thermally decomposed, flammable/toxic gases may be released.

Toxic gases will form upon combustion.

Static Discharge, material can accumulate static charges which can cause an incendiary electrical discharge .

FIRE FIGHTING

Respiratory and eye protection required for fire fighting personnel.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS

Under Oxygen lean conditions, Carbon Monoxide (CO) and irritating smoke may be produced.

SECTION 6 ACCIDENTAL RELEASE MEASURES

LAND SPILL

Recover spilled material and place in suitable containers for recycle or disposal. Consult an expert on disposal of recovered material and ensure

Continues on page 3

MATERIAL SAFETY DATA SHEET
ExxonMobil Chemical Company
A Division of Exxon Mobil Corporation

PAGE: 3
DATE PREPARED: SEP 5, 2000
MSDS NO.: 89001000

EXXONMOBIL LLDPE(ALL GRADES)

conformity to local disposal regulations.

WATER SPILL

Plastic pellets are defined by the US EPA under the Clean Water Act (40CFR122.25) as a "significant material" which requires any industrial plant that may expose pellets to storm water to secure a storm water permit. Violations of the rule carry the same penalties as other Clean Water Act violations. Pellets found in storm water runoff are subject to EPA regulations with the potential for substantial fines and penalties.

Skim from surface.

Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

Recover the spilled material and place in suitable containers for recycle or disposal.

SECTION 7 STORAGE AND HANDLING

ELECTROSTATIC ACCUMULATION HAZARD:

Yes, use proper bonding and/or grounding procedure.

STORAGE TEMPERATURE, Deg F:

Ambient

LOADING/UNLOADING TEMPERATURE, Deg F:

Ambient

STORAGE/TRANSPORT PRESSURE, mmHg:

Atmospheric

LOADING/UNLOADING VISCOSITY, cSt:

Solid

STORAGE AND HANDLING:

Keep container closed. Handle and open containers with care. Store in a cool, well ventilated place away from incompatible materials.

Do NOT handle or store near an open flame, heat or other sources of ignition. Protect material from direct sunlight.

Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or grounding procedures.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE CONTROLS

Local exhaust ventilation of process equipment may be needed to control particulate exposures to below the recommended exposure limit. See personal protection recommendations.

PERSONAL PROTECTION

For open systems at ambient temperature (-18 to 38 degrees C) where contact is likely, wear safety glasses with side shields.

Where contact may occur with hot material, wear thermal resistant gloves, arm protection, and a face shield.

Continues on page 4

MATERIAL SAFETY DATA SHEET
ExxonMobil Chemical Company
A Division of Exxon Mobil Corporation

PAGE: 4
DATE PREPARED: SEP 5, 2000
MSDS NO.: 89001000

EXXONMOBIL LLDPE(ALL GRADES)

WORKPLACE EXPOSURE GUIDELINES

OSHA REGULATION 29CFR1910.1000 REQUIRES THE FOLLOWING PERMISSIBLE

EXPOSURE LIMITS:

5 mg/m3 (respirable dust), and 15 mg/m3 (total dust) based on the OSHA PEL for nuisance dust.

The recommended permissible exposure levels indicated above reflect the levels revised by OSHA in 1989 or in subsequent regulatory activity. Although the 1989 levels have since been vacated by the 11th Circuit Court of Appeals, ExxonMobil Chemical Company recommends that the lower exposure levels be observed as reasonable worker protection.

THE ACGIH RECOMMENDS THE FOLLOWING THRESHOLD LIMIT VALUES:

A TWA of 10 mg/m3 for inhalable particulate (total dust) and a TWA of 3 mg/m3 for respirable particulate (total dust) for Particulates Not Otherwise Classified (PNOC).

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

SPECIFIC GRAVITY at Deg F:	0.92 - 0.970
VAPOR PRESSURE, mmHg at Deg F:	Not Applicable
SOLUBILITY IN WATER, wt. % at Deg F:	Insoluble
VISCOSITY OF LIQUID, cSt at Deg F:	Not applicable
SP. GRAV. OF VAPOR, at 1 atm (Air=1):	Not applicable
FREEZING/MELTING POINT, Deg F:	See Notes in Section 15
EVAPORATION RATE, n-Bu Acetate=1:	Not applicable
BOILING POINT, Deg F:	Not applicable

SECTION 10 STABILITY AND REACTIVITY

STABILITY:

Stable

CONDITIONS TO AVOID INSTABILITY:

Temperatures over 550 F (343 C) will lead to resin degradation and decomposition

HAZARDOUS POLYMERIZATION:

Will not occur

CONDITIONS TO AVOID HAZARDOUS POLYMERIZATION:

Not Applicable

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY:

Fluorine

Strong Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS:

Flammable Hydrocarbons

Continues on page 5

MATERIAL SAFETY DATA SHEET
ExxonMobil Chemical Company
A Division of Exxon Mobil Corporation

PAGE: 5
DATE PREPARED: SEP 6, 2000
MSDS NO.: 89001000

EXXONMOBIL LLDPE(ALL GRADES)

SECTION 11 TOXICOLOGICAL INFORMATION

Please refer to Section 3 for available information on potential health effects.

SECTION 12 ECOLOGICAL INFORMATION

No specific ecological data are available for this product. Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

SECTION 13 DISPOSAL CONSIDERATIONS

Please refer to Sections 5, 6 and 15 for disposal and regulatory information.

SECTION 14 TRANSPORT INFORMATION

DEPARTMENT OF TRANSPORTATION (DOT):

This product is not DOT regulated.

SECTION 15 REGULATORY INFORMATION

TSCA:

This product is listed on the TSCA Inventory.

CERCLA:

If this product is accidentally spilled, it is not subject to any special reporting under the requirements of the Comprehensive Environmental Response, Compensation and Liability Act. We recommend you contact local authorities to determine if there may be other local reporting requirements.

SARA TITLE III:

Under the provisions of Title III, Sections 311/312 of the Superfund Amendments and Reauthorization Act, this product is classified into the following hazard categories:

Not Hazardous.

This product does not contain Section 313 Reportable Ingredients.

SECTION 16 OTHER INFORMATION

NOTES:

Polymer CAS Numbers:

For polyethylene homopolymer grades: 9002-88-4

For ethylene/butene copolymer grades: 25087-34-7

For ethylene/hexene copolymer grades: 25213-47-3

Melting Point Ranges:

HDPE: 255 to 280 Deg F. (129 to 137.5 Deg C)

LLDPE: 240 to 265 Deg F. (115 to 129 Deg C)

Continues on page 6

10 000 072 0702 1 000 00000 000 0440001 1001001 00700000N PAGE 7 OF 8

MATERIAL SAFETY DATA SHEET
ExxonMobil Chemical Company
A Division of Exxon Mobil Corporation

PAGE: 6
DATE PREPARED: SEP 5, 2000
MSDS NO.: 89001000

EXXONMOBIL LLDPE(ALL GRADES)

=====

National Fire Protection Association standards NFPA 654 and 68 indicate possible explosion hazard of dust particles. Conform accordingly. Avoid accumulation of dust or dust clouds; operate handling and storage systems leak free, practice good housekeeping. Keep from sources of ignition. Do not store near heat, flame, or strong oxidants. Assure proper electrical grounding of all handling equipment.

For more information see "Guide for Handling and Storage of ESCORENE Polyethylene Resins."

Product may also contain varying levels of additives, such as slip and antiblocking agents (talc or silica), antioxidants, stabilizers, and corrosion inhibitors. Certain grades may contain cristobalite, a form of crystalline silica, as an additive that is encapsulated in the polymer. Inhaled crystalline silica in an occupational environment has been classified as a Group 1 human carcinogen by the International Agency for Research on Cancer. However, ExxonMobil Chemical Company has assessed the potential for release of silica to the air when this polymer is handled and has determined that silica encapsulated in this polymer is not expected to pose a health hazard when processed under normal conditions of use.

SPECIAL PRECAUTIONS:

Should significant vapors/fumes be generated during thermal processing of this product, it is recommended that work stations be monitored for the presence of thermal degradation by-products which may evolve at elevated temperatures (for example, formaldehyde and acrolein). Processors of this product should assure that adequate ventilation or other controls are used to control exposure.

It is recommended that the current ACGIH-TLVs for thermal degradation by-products be observed. Contact your ExxonMobil Representative for further information.

Representative Paxon HDPE grades may include:

EA55-003	EA50-007	EE50-007	FD50-018
FE50-018	4251A Q450	4700	AA45-004
AA55-003	AA50-003	AB40-003	AB50-003
AB55-003	AC40-003	AD60-007	AF50-003
AF50-007	AG45-004	AK53-004	AL55-003
AM55-003	AS55-003	AT55-003	AU55-003
BA45-055	BA50-100	BA50-120	BA53-035
BA53-058	BC50-100		
AX40-003	AX50-003	AX50-200	AX55-003
AX50-007	BX50-100	BX53-035	BX53-058

=====

Continues on page 7

MATERIAL SAFETY DATA SHEET
ExxonMobil Chemical Company
A Division of Exxon Mobil Corporation

PAGE: 7
DATE PREPARED: SEP 5, 2000
MSDS NO.: 89001000

EXXONMOBIL LLDPE(ALL GRADES)

HAZARD RATING SYSTEMS:

This information is for people trained in:
National Paint & Coatings Association's (NPCA)
Hazardous Materials Identification System (HMIS)
National Fire Protection Association (NFPA 704)
Identification of the Fire Hazards of Materials

	NPCA-HMIS	NFPA 704
HEALTH	1	1
FLAMMABILITY	1	1
REACTIVITY	0	0

KEY
4 = Severe
3 = Serious
2 = Moderate
1 = Slight
0 = Minimal

REFERENCE NUMBER:
HDHA-K-20313

SUPERSEDES ISSUE DATE:

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the users responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.

LAST PAGE

; US 0000178 0405010127 FLRPRKVM HLMeyer

MATERIAL SAFETY DATA SHEET

ExxonMobil Chemical Company

A Division of Exxon Mobil Corporation

ESCORENE LDPE All PE Homopolymer Grades

PAGE: 1
DATE PREPARED: MAY 4, 2000
MSDS NO.: 87000000

SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ESCORENE LDPE -All PE Homopolymer Grades**CHEMICAL NAME:**

Polyethylene

CHEMICAL FAMILY:

Ethylene-Based Polymer

PRODUCT DESCRIPTION:

Odorless opaque white pellets or granules.

CONTACT ADDRESS:ExxonMobil Chemical Company,
P.O. Box 3272, Houston, Texas 77253-3272

**	EMERGENCY TELEPHONE NUMBERS: (24 Hours)	**
**	CHEMTREC (800) 424-9300	**
**	ExxonMobil Chemical Company (800) 726-2015	**

NON EMERGENCY TELEPHONE NUMBERS : (8am-5pm M-F)

FOR HEALTH AND SAFETY INFORMATION CALL : (281) 870-6884

FOR GENERAL PRODUCT INFORMATION CALL : (281) 870-6000

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

This product is not hazardous as defined in 29 CFR1910.1200

SECTION 3 HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS**EYE CONTACT:**

Particulates may scratch eye surfaces/cause mechanical irritation.

SKIN CONTACT:

Negligible hazard at ambient temperatures (-18 to +38 degrees C; 0 to 100 degrees F).

Exposure to hot material may cause thermal burns.

INHALATION:

Negligible hazard at ambient temperature (-18 to 38 Deg C; 0 to 100 Deg F)

Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract.

INGESTION:

Minimal toxicity.

SECTION 4 FIRST AID MEASURES

EYE CONTACT:

This product is an inert solid. If in eye, remove as one would any foreign object.

Continues on page 2

MATERIAL SAFETY DATA SHEET

ExxonMobil Chemical Company

A Division of Exxon Mobil Corporation

ESCORENE LDPE -All PE Homopolymer Grades

PAGE: 2
DATE PREPARED: MAY 4, 2000
MSDS NO.: 87000000

SKIN CONTACT:

For hot product, immediately immerse in or flush the affected area with large amounts of cold water to dissipate heat. Cover with clean cotton sheeting or gauze and get prompt medical attention. No attempt should be made to remove material from skin or to remove contaminated clothing, as the damaged flesh can be easily torn.

INHALATION:

In case of adverse exposure to vapors and/or aerosols formed at elevated temperatures, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

INGESTION:

First aid is normally not required.

SECTION 5 FIRE-FIGHTING MEASURES

FLASH POINT: 649 Deg F. NOTE: Estimated Minimum
FLAMMABLE LIMITS: NOTE: Not applicable
AUTOIGNITION TEMPERATURE: 649 Deg F. NOTE: Estimated Minimum

GENERAL HAZARD

Solid material, may burn at or above the flashpoint, and airborne dust may explode if ignited.
If thermally decomposed, flammable/toxic gases may be released.
Toxic gases will form upon combustion.
Static Discharge, material can accumulate static charges which can cause an incendiary electrical discharge.

FIRE FIGHTING

Use water spray to cool fire exposed surfaces, protect personnel, and extinguish the fire.
Respiratory and eye protection required for fire fighting personnel.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS

Under Oxygen lean conditions, Carbon Monoxide (CO) and irritating smoke may be produced.

SECTION 6 ACCIDENTAL RELEASE MEASURES

LAND SPILL

Recover spilled material and place in suitable containers for recycle or disposal. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

WATER SPILL

Plastic pellets are defined by the US EPA under the Clean Water Act (40CFR122.26) as a "significant material" which requires any industrial plant that may expose pellets to storm water to secure a storm water permit. Violations of the rule carry the same penalties as other Clean Water Act violations. Pellets found in storm water runoff are subject to EPA regulations with the potential for substantial fines and penalties.
Skim from surface.

Continues on page 3

MATERIAL SAFETY DATA SHEET

ExxonMobil Chemical Company

A Division of Exxon Mobil Corporation

ESCORENE LDPE -All PE Homopolymer Grades

PAGE: 3
DATE PREPARED: MAY 4, 2000
MSDS NO.: 87000000

Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
Recover the spilled material and place in suitable containers for recycle or disposal.

SECTION 7 STORAGE AND HANDLING

ELECTROSTATIC ACCUMULATION HAZARD:

Yes, use proper bonding and/or grounding procedure.

STORAGE TEMPERATURE, °F:

Ambient

LOADING/UNLOADING TEMPERATURE, °F:

Ambient

STORAGE/TRANSPORT PRESSURE, mmHg:

Atmospheric

LOADING/UNLOADING VISCOSITY, cSt:

Solid

STORAGE AND HANDLING:

Keep container closed. Handle and open containers with care. Store in a cool, well ventilated place away from incompatible materials.
Do NOT handle or store near an open flame, heat or other sources of ignition. Protect material from direct sunlight.
Material will accumulate static charges which may cause an electrical spark (ignition source). Use proper bonding and/or grounding procedures.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE CONTROLS

Local exhaust ventilation of process equipment may be needed to control particulate exposures to below the recommended exposure limit. See personal protection recommendations.

PERSONAL PROTECTION

For open systems at ambient temperature (-18 to 38 degrees C) where contact is likely, wear safety glasses with side shields.
Where contact may occur with hot material, wear thermal resistant gloves, arm protection, and a face shield.

WORKPLACE EXPOSURE GUIDELINES

OSHA REGULATION 29CFR1910.1000 REQUIRES THE FOLLOWING PERMISSIBLE EXPOSURE LIMITS:

5 mg/m3 (respirable dust), and 15 mg/m3 (total dust) based on the OSHA PEL for nuisance dust.

The recommended permissible exposure levels indicated above reflect the levels revised by OSHA in 1989 or in subsequent regulatory activity. Although the 1989 levels have since been vacated by the 11th Circuit Court of Appeals, ExxonMobil Chemical Company recommends that the lower exposure levels be observed as reasonable worker protection.

THE ACGIH RECOMMENDS THE FOLLOWING THRESHOLD LIMIT VALUES:

A TWA of 10 mg/m3 for inhalable particulate (total dust) and a TWA of 3 mg/m3 for respirable particulate (total dust) for Particulates Not Otherwise Classified (PNOC).

Continues on page 4

MATERIAL SAFETY DATA SHEET

ExxonMobil Chemical Company
A Division of Exxon Mobil Corporation

ESCORENE LDPE -All PE Homopolymer Grades

PAGE: 4
DATE PREPARED: MAY 4, 2000
MSDS NO.: 87000000

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

SPECIFIC GRAVITY, at °F: 0.92 - 0.970	VAPOR PRESSURE, mmHg at °F: Not available
SOLUBILITY IN WATER, wt. % at °F: Insoluble	VISCOSITY OF LIQUID, cSt at °F: Not applicable
SP. GRAV. OF VAPOR, at 1 atm (Air=1): Not applicable	FREEZING/MELTING POINT, °F: 225 to 229 Deg F
EVAPORATION RATE, n-Bu Acetate=1: Not applicable	BOILING POINT, °F: Not applicable

SECTION 10 STABILITY AND REACTIVITY

STABILITY:
Stable

CONDITIONS TO AVOID INSTABILITY:
Temperatures over 650 F (343 C) may cause resin degradation.

HAZARDOUS POLYMERIZATION:
Will not occur

CONDITIONS TO AVOID HAZARDOUS POLYMERIZATION:
Not Applicable

MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY:
Fluorine
Strong Oxidizing agents

HAZARDOUS DECOMPOSITION PRODUCTS:
Flammable Hydrocarbons

SECTION 11 TOXICOLOGICAL INFORMATION

Please refer to Section 3 for available information on potential health effects.

SECTION 12 ECOLOGICAL INFORMATION

No specific ecological data are available for this product. Please refer to Section 6 for information regarding accidental releases and Section 15 for regulatory reporting information.

SECTION 13 DISPOSAL CONSIDERATIONS

Please refer to Sections 5, 6, and 15 for disposal and regulatory information.

SECTION 14 TRANSPORT INFORMATION

DEPARTMENT OF TRANSPORTATION (DOT):
This product is not DOT regulated.

Continues on page 5

MATERIAL SAFETY DATA SHEET

ExxonMobil Chemical Company

A Division of Exxon Mobil Corporation

ESCORENE LDPE -All PE Homopolymer Grades

PAGE: 5
DATE PREPARED: MAY 4, 2000
MSDS NO.: 87000000

SECTION 15 REGULATORY INFORMATION

TSCA:

This product is listed on the TSCA Inventory at CAS Registry Number 9002-88-4

CERCLA:

If this product is accidentally spilled, it is not subject to any special reporting under the requirements of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA). We recommend you contact local authorities to determine if there may be other local reporting requirements.

SARA TITLE III:

Under the provisions of Title III, Sections 311/312 of the Superfund Amendments and Reauthorization Act, this product is classified into the following hazard categories:
Not Hazardous.

This product does not contain Section 313 Reportable Ingredients.

SECTION 16 OTHER INFORMATION

NOTES:

National Fire Protection Association standards NFPA 654 and 68 indicate possible explosion hazard of dust particles. Conform accordingly.

Avoid accumulation of dust or dust clouds; operate handling and storage systems leak free, practice good housekeeping.

Keep from sources of ignition. Do not store near heat, flame, or strong oxidants.

Assure proper electrical grounding of all handling equipment.

For more information see "Guide for Handling and Storage of ESCORENE Polyethylene Resins."

Product may also contain varying levels of additives, such as slip and antiblocking agents (talc or silica), antioxidants, stabilizers, and corrosion inhibitors. Certain grades may contain cristobalite, a form of crystalline silica, as an additive that is encapsulated in the polymer. Inhaled crystalline silica in an occupational environment has been classified as a Group 1 human carcinogen by the International Agency for Research on Cancer. However, ExxonMobil Chemical Company has assessed the potential for release of silica to the air when this polymer is handled and has determined that silica encapsulated in this polymer is not expected to pose a health hazard when processed under normal conditions of use.

SPECIAL PRECAUTIONS:

Should significant vapors/fumes be generated during thermal processing of this product, it is recommended that work stations be monitored for the presence of thermal degradation by-products which may evolve at elevated temperatures. It is recommended that the current ACGIH-TLVs for these materials be observed. Contact your ExxonMobil representative for further information.

Continues on page 6

MATERIAL SAFETY DATA SHEET

ExxonMobil Chemical Company
A Division of Exxon Mobil Corporation

ESCORENE LDPE -All PE Homopolymer Grades

PAGE: 6
DATE PREPARED: MAY 4, 2000
MSDS NO.: 87000000

HAZARD RATING SYSTEMS:

This information is for people trained in:
National Paint & Coatings Association's (NPCA)
Hazardous Materials Identification System (HMIS)
National Fire Protection Association (NFPA 704)
Identification of the Fire Hazards of Materials

	NPCA-HMIS	NFPA 704
HEALTH	1	1
FLAMMABILITY	1	1
REACTIVITY	0	0

KEY
4 = Severe
3 = Serious
2 = Moderate
1 = Slight
0 = Minimal

REVISION SUMMARY:

Since April 29, 2000 this MSDS has been revised in Section(s):
6

REFERENCE NUMBER:
HDHA-K-10103

SUPERSEDES ISSUE DATE:
April 29, 2000

THIS INFORMATION RELATES TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABILITY AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE. WE DO NOT ACCEPT LIABILITY FOR ANY LOSS OR DAMAGE THAT MAY OCCUR FROM THE USE OF THIS INFORMATION NOR DO WE OFFER WARRANTY AGAINST PATENT INFRINGEMENT.

LAST PAGE

MATERIAL SAFETY DATA SHEET

ExxonMobil Chemical Company

A Division of Exxon Mobil Corporation

LOW DENSITY POLYETHYLENE

ESCORENE LDPE

PAGE: 1
DATE PREPARED: MAY 4, 2000
MSDS NO.: 87000000

SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ESCORENE LDPE -All PE Homopolymer Grades

CHEMICAL NAME:

Polyethylene

CHEMICAL FAMILY:

Ethylene-Based Polymer

PRODUCT DESCRIPTION:

Odorless opaque white pellets or granules.

CONTACT ADDRESS:

ExxonMobil Chemical Company,
P.O. Box 3272, Houston, Texas 77253-3272

**	EMERGENCY TELEPHONE NUMBERS: (24 Hours)	**
**	CHEMTREC (800) 424-9300	**
**	ExxonMobil Chemical Company (800) 726-2015	**

NON EMERGENCY TELEPHONE NUMBERS : (8am-5pm M-F)

FOR HEALTH AND SAFETY INFORMATION CALL : (281) 870-6884

FOR GENERAL PRODUCT INFORMATION CALL : (281) 870-6000

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

This product is not hazardous as defined in 29 CFR1910.1200

SECTION 3 HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYE CONTACT:

Particulates may scratch eye surfaces/cause mechanical irritation.

SKIN CONTACT:

Negligible hazard at ambient temperatures (-18 to +38 degrees C; 0 to 100 degrees F).

Exposure to hot material may cause thermal burns.

INHALATION:

Negligible hazard at ambient temperature (-18 to 38 Deg C; 0 to 100 Deg F)

Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract.

INGESTION:

Minimal toxicity.

SECTION 4 FIRST AID MEASURES

EYE CONTACT:

This product is an inert solid. If in eye, remove as one would any foreign object.

Continues on page 2

MATERIAL SAFETY DATA SHEET
ExxonMobil Chemical Company
A Division of Exxon Mobil Corporation

LINEAR LOW DENSITY

PAGE: 1
DATE PREPARED: SEP 6, 2000
MSDS NO.: 89001000

EXXONMOBIL LLDPE(ALL GRADES)

POLYETHYLENE

SECTION 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ExxonMobil LLDPE(ALL GRADES)

CHEMICAL NAME:

Polyethylene or Ethylene-Olefin Copolymer

CHEMICAL FAMILY:

Ethylene-Based Polymer

PRODUCT DESCRIPTION:

Odorless opaque white pellets or granules.

CONTACT ADDRESS:

ExxonMobil Chemical Company,
P.O. Box 3272, Houston, Texas 77253-3272

** EMERGENCY TELEPHONE NUMBERS: (24 Hours)	**
** CHEMTREC (800) 424-9300	**
** ExxonMobil Chemical Company (800) 726-2015	**

NON EMERGENCY TELEPHONE NUMBERS : (8am-5pm M-F)

FOR GENERAL PRODUCT INFORMATION CALL : (281) 870-6000

FOR HEALTH AND MEDICAL INFORMATION CALL : (281) 870-6884

SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

This product is not hazardous as defined in 29 CFR1910.1200

SECTION 3 HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYE CONTACT:

Particulates may scratch eye surfaces/cause mechanical irritation.

SKIN CONTACT:

Negligible hazard at ambient temperatures (-18 to +38 degrees C; 0 to 100 degrees F).

Exposure to hot material may cause thermal burns.

INHALATION:

Negligible hazard at ambient temperature (-18 to 38 Deg C; 0 to 100 Deg F)

Vapors and/or aerosols which may be formed at elevated temperatures may be irritating to eyes and respiratory tract.

INGESTION:

Minimal toxicity.

Continues on page 2