



0500479 0500480 0500481 0500482.

0500467

0500470

0500472

32350

Product Name: STYROFOAM(TM) White Floral & Craft Billet

Issue Date: 11/07/2011

9704420

9704421

9714794.

Print Date: 03 Jan 2014

0500504-V# 031577

The Dow Chemical Company encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

SB24 08 9714796

Product and Company Identification 1.

Product Name

10.875 Inch

STYROFOAM(TM) White Floral & Craft Billet 10.875 Inch

COMPANY IDENTIFICATION

The Dow Chemical Company 2030 Willard H. Dow Center Midland, MI 48674 **United States**

Customer Information Number:

800-258-2436

SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: **Local Emergency Contact:**

989-636-4400 989-636-4400

2. **Hazards Identification**

Emergency Overview

Color: White Physical State: Billet

Odor: None Hazards of product:

No significant immediate hazards for emergency response are known.

OSHA Hazard Communication Standard

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Potential Health Effects

Eye Contact: Solid or dust may cause irritation or corneal injury due to mechanical action. Furnes/vapor released during thermal operations such as hot-wire cutting may cause eye irritation. Skin Contact: Essentially nonirritating to skin. Mechanical injury only. Skin Absorption: Skin absorption is unlikely due to physical properties.

®(TM)*Trademerk

Page 1 of 8

Product Name: STYROFOAM(TM) White Floral & Craft Billet

10.875 Inch

Inhalation: Dust may cause irritation to upper respiratory tract (nose and throat). Fumes/vapors released during thermal operations such as hot wire cutting may cause respiratory irritation. Concentrations of the blowing agents anticipated incidental to proper handling are expected to be well below those which cause acute inhalation effects and below exposure guidelines.

Issue Date: 11/07/2011

Ingestion: Swallowing is unlikely because of the physical state. Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts. May cause choking or blockage of the

digestive tract if swallowed.

Aspiration hazard: Based on physical properties, not likely to be an aspiration hazard.

Effects of Repeated Exposure: For the minor component(s): Blowing agents. In animals, effects have been reported on the following organs: Kidney. Respiratory tract. Testing has indicated that normal handling and cutting are unlikely to result in exposure levels sufficient to cause the listed effects.

3. Composition Information

Component	CAS#	Amount	
2-Propenenitrile, polymer with ethenylbenzene	9003-54-7	> 60.0 - < 100.0 %	
1,1-Difluoroethane	75-37-6	> 1.0 - < 10.0 %	
Styrene, polymers	9003-53-6	> 1.0 - < 10.0 %	

4. First-aid measures

Description of first aid measures

General advice: If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin Contact: Wash skin with plenty of water.

Eye Contact: Flush eyes with plenty of water; remove contact lenses after the first 1-2 minutes then continue flushing for several minutes. Only mechanical effects expected. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: If swallowed, seek medical attention. May cause gastrointestinal blockage. Do not give

laxatives. Do not induce vomiting unless directed to do so by medical personnel.

Most important symptoms and effects, both acute and delayed

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), no additional symptoms and effects are anticipated.

Indication of immediate medical attention and special treatment needed

If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire Fighting Measures

Suitable extinguishing media

Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam.

Special hazards arising from the substance or mixture

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. In smoldering or flaming conditions, carbon monoxide, carbon dioxide and carbon are generated. Combustion products may include and are not limited to: Hydrogen halides. Based on combustion toxicity testing, the effects of combustion from this foam are not more acutely toxic than the effects of combustion from

Issue Date: 11/07/2011

common building materials such as wood.

Unusual Fire and Explosion Hazards: Container may vent and/or rupture due to fire. When product is stored in closed containers, a flammable atmosphere can develop. Mechanical cutting, grinding or sawing can cause formation of dusts. To reduce the potential for dust explosion, do not permit dust to accumulate. This product contains a flame retardant to inhibit accidental ignition from small fire sources. This plastic foam product is combustible and should be protected from flames and other high heat sources. For more information, contact Dow. Dense smoke is produced when product burns.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Soak thoroughly with water to cool and prevent re-ignition. If material is molten, do not apply direct water stream. Use fine water spray or foam. Cool surroundings with water to localize fire zone.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, ceat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

Accidental Release Measures

Personal precautions, protective equipment and emergency procedures: Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Collect in suitable and properly labeled centainers. See Section 13, Disposal Considerations, for additional information.

7. Handling and Storage

Handling

General Handling: See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Storage

Minimize sources of ignition, such as static build-up, heat, spark or flame. When large quantities of this product are stored or fabricated, blowing agents may be released. Released blowing agents may thermally decompose to form gases which may accelerate corrosion or rust formation of heaters, boilers, gas fired recirculating air furnaces or heaters, or gas water heaters. Flammable vapors may accumulate in some storage situations.

8. Exposure Controls / Personal Protection Exposure Limits				
1,1-Difluoroethane	AIHA WEEL	TWA	2,700 mg/m3 1,000 ppm	

10.875 Inch

Concentrations of the blowing agents anticipated incidental to proper handling are expected to be well below those which cause acute inhalation effects and below exposure guidelines.

Personal Protection

Eye/Face Protection: Eye protection should not be necessary. For fabrication operations safety glasses (with side shields) are recommended. If there is a potential for exposure to particles which could cause eye discomfort, wear chemical goggles.

Skin Protection: No precautions other than clean body-covering clothing should be needed. Hand protection: Use gloves to protect from mechanical injury. Selection of gloves will depend on the task.

Respiratory Protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. In dusty or misty atmospheres, use an approved particulate respirator. When respiratory protection is required for certain operations, including but not limited to saw, router or hot-wire cutting, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: When dust/mist are present use a/an Particulate filter. When combinations of vapors, acids, or dusts/mists are present use a/an Organic vapor cartridge with a particulate pre-filter. Ingestion: No precautions necessary due to the physical properties of the material.

Engineering Controls

Ventilation: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

9. Physical and Chemical Properties

Appearance

Physical State Billet
Color White
Odor None
Odor Threshold Odorless
pH Not applicab

pH Not applicable
Melting Point 90 - 130 °C (194 - 266 °F) Estimated.

Freezing Point Boiling Point (760 mmHg)
Flash Point - Closed Cup
Evaporation Rate (Butyl

Not applicable
Not applicable
Not applicable

Acetate = 1)

Flammability (solid, gas) No Flammable Limits In Air Lo

Flammable Limits In Air

Lower: Not applicable
Upper: Not applicable
Not applicable
Not applicable
Not applicable

Vapor Density (air = 1)
Specific Gravity (H2O = 1)
Solubility In water (by
weight)

Not applicable
not soluble

Autoignition Temperature 354 °C (669 °F) ASTM D1929
Decomposition No test data available

Decomposition No test data available Temperature

Kinematic Viscosity
Explosive properties
Oxidizing properties
Not applicable
no data available

10.875 Inch

Stability and Reactivity

Reactivity

No dangerous reaction known under conditions of normal use.

Chemical stability

Thermally stable at typical use temperatures.

Possibility of hazardous reactions

Polymerization will not occur.

Conditions to Avoid: Avoid temperatures above 300 °C (572 °F). Exposure to elevated temperatures can cause product to decompose. Avoid direct sunlight.

Incompatible Materials: Avoid contact with oxidizing materials. Avoid contact with: Aldehydes. Amines. Esters. Liquid fuels. Organic solvents.

Hazardous decomposition products

Does not normally decompose. Evolution of small amounts of hydrogen halides occur when heated over 250°C (482°F). Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aromatic compounds. Aldehydes. Hydrogen halides. Polymer fragments. Toxic flammable gases can be released during decomposition. Under high heat, non-flaming conditions, small amounts of aromatic hydrocarbons such as styrene and ethylbenzene are generated.

11. Toxicological Information

Acute Toxicity

Ingestion

As product: Single dose oral LD50 has not been determined.

Dermal

As product: The dermal LD50 has not been determined.

Inhalation

As product: The LC50 has not been determined.

Eye damage/eye irritation

Solid or dust may cause irritation or comeal injury due to mechanical action. Fumes/vapor released during thermal operations such as hot-wire cutting may cause eye irritation.

Skin corrosion/irritation

Essentially nonirritating to skin. Mechanical injury only.

Sensitization

Skin

Relevant data not available.

Respiratory

Relevant data not available.

Repeated Dose Toxicity

For the minor component(s): Blowing agents. In animals, effects have been reported on the following organs: Kidney. Respiratory tract. Testing has indicated that normal handling and cutting are unlikely to result in exposure levels sufficient to cause the listed effects.

Chronic Toxicity and Carcinogenicity

Contains component(s) which did not cause cancer in laboratory animals.

Developmental Toxicity

Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.

Reproductive Toxicity

Relevant data not available.

Genetic Toxicology

10.875 Inch

The data presented are for the following material: Blowing agents. In vitro genetic toxicity studies were negative in some cases and positive in other cases.

12. Ecological Information

Toxicity

Not expected to be acutely toxic to aquatic organisms.

Persistence and Degradability

Surface photodegradation is expected with exposure to sunlight. No appreciable biodegradation is expected. 1,1-difluoroethane (HFC 152a) has a stratospheric ozone depletion potential (ODP) of zero, relative to CFC 12 (ODP=1).

Bioaccumulative potential

Bioaccumulation: No bioconcentration is expected because of the relatively high molecular weight (MW greater than 1000). In the terrestrial environment, material is expected to remain in the soil.

Mobility in soil

Mobility in soil: In the aquatic environment, material is expected to float.

13. Disposal Considerations

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. Waste water treatment system. Landfill.

14. Transport Information

DOT Non-Bulk NOT REGULATED

DOT Bulk NOT REGULATED

IMDG NOT REGULATED

ICAO/IATA NOT REGULATED

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be

Issue Date: 11/07/2011

obtained through an authorized sales or customer service representative. It is the responsibility of the trensporting organization to follow all applicable laws, regulations and rules relating to the trensportation of the material.

15. Regulatory Information

OSHA Hazard Communication Standard

This product is not a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health Hazard No
Delayed (Chronic) Health Hazard No
Fire Hazard No
Reactive Hazard No
Sudden Release of Pressure Hazard No

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

Component	CAS#	Amount
Ethylbenzene	100-41-4	< 0.058 %
Acrylonitrile	107-13-1	< 0.005 %
Cumene	98-82-8	<= 0.0016 %

US. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

CEPA - Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

16. Other Information

Recommended Uses and Restrictions

Identified uses

Thermal insulation.

10.875 Inch

Revision

Identification Number: 1007860 / 1001 / Issue Date 11/07/2011 / Version: 6.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this

Legend

N/A	Not available
ww	Weight/Weight
OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
DOW IHG	Dow Industrial Hygiene Guideline
WEEL	Workplace Environmental Exposure Level
HAZ DES	Hazard Designation
Action Level	A value set by OSHA that is lower than the PEL which will trigger the need for activities such as exposure monitoring and medical surveillance if exceeded.

The Dow Chemical Company urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good feith and believed to be accurate as of the effective data shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cennot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.