



BLACK

Page:

PRODUCT NAME: BLACK PRODUCT CODE: LG-37687 MHIS CODES: H F R P

2 2 0 B

MANUFACTURER'S NAM

: 4035 W. Kinzie Street ADDRESS

CITY/ETATE CHICAGO, IL Ľ

ZIPCODE 1 60624

EMERGENCY PRONE 1 (800) 255-3924 DATE PRINTED 1 12/14/99

INFORMATION PHONE z (773) 826-0200 NAME OF PREPARER : Cudner & O'Connor

======= BECTION II HAZARDOUS INGREDIENTS/SARA III INFORMATION ======

REPORTABLE COMPONENTS	CAS HUMBER	VAPOR PRESSURE		WEIGHT	
		ATTA. HI	A TEMP	PERCENT	

MIMERAL SPIRITS	8052-41-3	2	6 8 F	40 - 45	
OSHA:PEL 100ppm, ACGIH: TLV 100ppm					
CARBON BLACK	1333-86-4	M/A	H/A	10.79	
NA					
ROSIN	MIXTURE	.061	68F	05 + 10	
OSHA: PEL H/E, ACUIH: THV N/E					
PETROLEUM NYDBOCARRON 100	64742-95-6	4	68F	05 + 10	
OSHA:PEL 50 ppm, Acciti: TLV 50 ppm				,	
* 1,2,4 TRINETNYLBENZENE	95-63-6	9	25C	05 - 10	
CSHA:PEL 25ppm, ACGIH: TLY 25ppm					
SYNTHETIC AMORPHOUS SILICA	RIXTURE	N/A	W/A	00 ~ 05	
OSHA:PEL 6mg/H3, ACGIN: TLY 10mg/H3 (As Dust)					
DICZ-ETHYLHEXYL) PHTHALATE	117:-81-7	N/A	M/A	0.81	
OSHA:PEL 5 mg/H3, ACGIH:TLY 5mg/H3					

^{*} indicates toxic chemical(a) subject to the reporting requirements of section 313 of Title 111 and of 40 CFR 372. MARKING: DETECTABLE AMOUNTS OF A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM RAY BE PRESENT IN THIS PRODUCT.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 278.6F - 724F SPECIFIC GRAVITY (H20=1): VOLATILE WEIGHT: 53.88%

VOLATILE VOLUME: 66.97%

VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER MATERIAL V.O.C.: 4.51 lb/ql SOLUBILITY IN WATER: Non Soluble

APPEARANCE AND ODOR: Characteristic Solvent Odor

SECTION IV -FIRE AND EXPLOSION HAZARD DATA

PLASH POINT: SOF METHOD USED: TCC FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: .3 UPPER: 13.3

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, MATER FOG, OTHER

SPECIAL FIREFIGHTING PROCEDURES:

Self-containing breathing apparatus (SCDA) should be worn to avoid inhalation of concentrated vapors. Water should not be used except as fog to keep nearby containers cool. Fumes released on burning may be toxic and dengerous.

UNUSUAL FIRE AND EXPLOSION HAZARDS:



KATERIAL SAFETY DATA SEET

BLACK

Page:

Handle as flammable liquid. Vapors form an explosive mixture in mir between the upper and lower explosive limits which can be idnited by many sources such as pilot lights, open flamms, electrical motors and switches.

STABILITY: STABLE

CONDITIONS TO AVOID:

Excessive heat, poor ventilation, corrosive atmospheres, excessive aging, ignition sources, sparks and open flame:

INCOMPATIBILITY (MATERIALS TO AVOID):

Alkaiine materials, strong acids and exidizing materials.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Carbon memoxide, carbon diskide, exides of mitrogen, and possibly acrolein.

HAZARDOUS POLYMENIZATION: Not enticipated during normal printing and storage conditions.

HERLTH HAZARD DATA HERLTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Inhelations Dizziness, breathing difficulty; headeches & loss of coordination.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Eye contact: Severe irritation, tearing, rechees and blurred vision.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE:

Skin contact: Can dry and defet skin causing cracks, irritation, and dermatitis.

INGESTION SEALTH RISKS AND SYMPTOMS OF EXPOSURES

ingestion: Can cause gestrointestinal irritation, vomiting, nauses, and distribes. Aspiration of material into lungs may cause chemical preumonitis which can be fatal.

HEALTH HAZARDS (ACUTE AND CHRONIC):

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system design.

If lead compounds and inorganic lead are present it is classified as a (CRCUP 28) cardinogen by IARC. Repeated and prolonged overexposure to lead by ingretion may cause nauses, dignetive disorders, abdomined cramps and incoming as well as blood, nervous, uninery and birth defects. Lead exposure is not expected when using this product as intended. Chromium and certain thromium compounds are included in the MTP and IARC List of cardinogens.

CARCINGGENICITY: NTP CARCINGGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED: No Information Available.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Pregnent women and persons with pre-existing health disorders should consult their physician before using this product. Repeated and prolonged overexposure and/or individual sensitivity may increase the potential for and degree of adverse health effects.

EMERGENCY AND FIRST AID PROCEDURES!

Inhelation overexposure: Nove person to frash air. If breathing stope, apply artificial respiration and seek immediate medical attention. Eye contact: Flush with large quantities of water for 15 minutes. Skin contact: Wash thoroughly with soap and water and see a physician, ingestion: Do not induce vomiting, can cause chemical pneumonitis and pulmonary adepts. Contact physician immediately.

FRECAUTIONS FOR SAFE HANDLING AND USE ============

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Remove all sources of ignition. Ventilate area and avoid breathing vapor. Contain release and remove with inert absorbent, Use non-

DATA MATERIAL BAYETY

BLACK

Pages

sparking tools to piece material in appropriate container for disposal.

WASTE DISPOSAL METHOD:

Dispose of in accordance with local, county, state, provincial and federal regulations. Emptied containers may retain hazardous properties. Empty containers should be disposed of in an environmentally safe wormer in eccordance with explicable regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Use non-sparking utchells when handling this motorial. Avoid hot metal surfaces. Use in cool, mult-ventilated areas. Keep containers closed when not in use. Keep away from exacesive heet and open flames.

OTHER PRECAUTIONS:

Smoking in area where this material is used should be strictly prohibited. Tools used with this material should be made from eliminum, brans or copper. Pinetic utensile should not be used. NOTE: This information is accurate to the best knowledge of Curier & O'Connor Co., but is furnished without any expressed or implied warranties.

RESPIRATORY PROTECTION:

When apraying this meterial use a NIOSK approved cartridge respirator or gazmask suitable to keep airborne mists and vebor concentrations below the timeweighted threshold limit values. When used in poorly ventileted and confined spaces, we an appropriate helf mask or full face MIOSH approved respirator.

VENTILATION:

General mechanical ventitation or local exhaust should be suitable to keep vapor concentrations below TLY. Ventilation equipment must be explosion proof.

PROTECTIVE GLOVES:

Use impermeable chemical handling gloves for skin protection.

EYE PROTECTION:

Use chemical majory glasses, goggles, and facoshields for eye protection.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

Use impermeable aprone and protective clothing whenever possible to prevent skin contect.

WORK/HYGIENIC PRACTICES:

Wash with soap and water before ceting, amoking or using tellet facilities. Separately wash or dispard stothing and footweer before reuse. Never try to remove ink from the skin by using solvent or thirner, Remove conteminated clothing to prevent prolunged contact.

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No Warranty, sugranty or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what mafety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any federal or state laws.

MAY-17-2006 15:53