48140			Ce	9739	C	3103	36	
MATERIAL	SAFET	TY DA	ATA	SH	EE	Т		
OSHA - Meets 29 CFR 1910.1200 Standards	HEALTH	F	IMIS HAZ	ARD RAT		· · · · ·	3 = HIGH	
AW DAVED	FLAMMABILITY REACTIVITY		1 0	1 = SLIGHT 2 = MODEF	RATE	4 = EXTREME		
LEATHER	HAZARD CLAS	TRANSPORTATION INFORMA PROPER SHIPPING NAME: Not Regulated HAZARD CLASS / PKG GRP: Not regulated REF: IDENTIFICATION NUMBER: None LABE				Not Applicable		
SECTION 1 - PRODUCT / COMPAN	NY IDENTIFI	CATION					,	
IDENTITY (AS USED ON LABEL AND LIST) PURPLE OIL						P	age 1 of 2	
MANUFACTURER'S NAME Weaver Leather LLC		EMERGEN 800-25		MBER				
ADDRESS (NUMBER, STREET, P.O. BOX) 7540 CR 201		TELEPHONE NUMBER FOR INFORMATION 330-674-7548						
(CITY, STATE AND ZIP CODE) Mt. Hope, OH 44660		DATE PREPARED: July 28, 2004 SUPERSEDES: November 25, 2002						
SECTION 2 - HAZARDOUS INGRE	EDIENTS / ID							
HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (OPTIONAL)	OSHA PPM	MG/M3	PPM	H TWA	SARA TITLE III	RQ LBS
Paraffinic petroleum oil		100						
Heavy paraffinic petroleum oil	64741-88-4			5 (mist)		5 (mist)		
SECTION 3 - HEALTH HAZARD D	DATA							
ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE		EMERGENCY	AND FIRST	AID PROCE	DURES			
INHALATION: High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.		Remove affected person to fresh air; provide oxygen if breathing is difficult; affected person is not breathing, administer CPR and seek emergency medical attention.						
SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate irritation or dermatitis.		Remove contaminated clothing; wash affected area with scap and water; launder contaminated clothing before reuse; if irritation persists, seek medica attention.						
EYES: High vapor concentration or contact may cause irritation and discomfort.		Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.						
INGESTION: May result in vomiting; aspiration of vomitus into the lungs must be avoided; DO NOT induce vomiting. Minute amounts aspirated into the lungs can produce severe lung injury, chemical pneumonitis, pulmonary edema or death.		DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.						
CARCINOGENICITY	NTP?		IARC MOR	OGRAPHS?	No	OSHA R	EGULATED?	No
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY prolonged exposure.	EXPOSURE: Preex	isting skin, eye,	or respirato	ry disorders	may bec	come aggrav	vated throug	gh

Form revised 09 / 01

MATERIAL SAFETY DATA SHEET									
IDENTITY (AS USED ON LABEL AND LIST) Page 2 of 2									
PURPLE OIL		Date: July 28, 2004							
SECTION 4 - FIRE FIGHTING MEASURES									
FLASH POINT (METHOD USED)	NFPA RATING	FLAMMABLE LIMITS							
> 265° F (> 129.4° C)	IIIB	LEL: Not applicable UEL: Not applicable							
EXTINGUISHING MEDIA									
Carbon dioxide, water fog, dry chemical, chemical foam									
SPECIAL FIRE FIGHTING PROCEDURES Firefighters must wear full facepiece self - contained breathing apparatus in positive pressure mode. Do not use solid stream of water since stream will									
scatter and spread fire. Fine water spray can be used to keep fire - exposed containers cool.									
UNUSUAL FIRE AND EXPLOSION HAZARDS									
Closed containers can explode due to buildup of pressure when exposed to extreme heat.									
SECTION 5 - ACCIDENTAL RELEASE MEASURES									
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WILL SUPPORT COMBUSTION. Do not wash to sanitary sewer. All spills - confine									
spill, soak up with approved absorbent, shovel product into approved container for disposal. Flush area with water, recover flush for proper disposal.									
SECTION & HANDLING AND STORAGE									
SECTION 6 - HANDLING AND STORAGE									
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures, open flames. This material will support combustion. Keep this and other chemicals out of reach of children.									
SECTION 7 - EXPOSURE CONTROL	SIPERSONAL PE	ROTECTION							
RESPIRATORY PROTECTION (SPECIFY TYPE): None required while threshold limits (Section 2) are kept below maximum allowable concentrations; if TWA									
exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.									
	equired SPECIAL	: To maintain minimum TWA and STEL levels.							
MECHANICAL (GENERAL): Ye		Engineering and work controls as required.							
PROTECTIVE GLOVES: Neoprene or rubber gloves with cuffs. EYE PROTECTION: Protective eyeglasses or chemical safety goggles.									
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyebath nearby WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.									
SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES									
BOILING POINT		GRAVITY (WATER = 1)							
532° F	0.920 - 0								
VAPOR PRESSURE (MM Hg)	pH								
0.1 mm Hg @ 20° C	Not appl								
VAPOR DENSITY (AIR = 1)		TION RATE (n-Butyl acetate = 1)							
> 1 SOLUBILITY IN WATER	< 0.1								
Negligible	% VOLATI None	ILE (BY WEIGHT)							
APPEARANCE AND ODOR	Hono								
Purple liquid, sweet pea odor									
SECTION 9 - STABILITY AND REACT	TIVITY								
STABILITY UNSTABLE:	CONDITION	NS TO AVOID: Extreme temperatures, open flames							
STABLE: XX									
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers,	strong acids								
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decompo	nition will not occur if handles	and stared preserve in seas of a fire avides of sorthan							
hydrocarbons, fumes, and smoke may be produced.	short will not occur it handled	and stored property. In case of a fire, oxides of carbon,							
HAZARDOUS POLYMERIZATION MAY OCCUR:	CONDITION	NS TO AVOID:							
WILL NOT OCCUR: XX									
SECTION 10 - DISPOSAL CONSIDER	ATIONS								
WASTE DISPOSAL METHOD: Dispose of in accordance with Lo	cal, State, and Federal Regul	ations. This product may produce hazardous vapors or fumes in							
a closed disposal container creating a dangerous environment. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal									
regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals. Do not flush to sanitary sewer or waterway.									
The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current,									
applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if									
reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as									

described in Section 1. MSDS PREPARED BY: CDB, Inc., P.O. Box 5604, Lakeland, FL 33807 (863) 644 - 3298 www.compdatabase.com