

6027.

## SAFETY DATA SHEET

9737298  
RA28335

## LIQUITEX PROFESSIONAL SPRAY GLOSS VARNISH

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product Identifier**

**Product name** LIQUITEX PROFESSIONAL SPRAY GLOSS VARNISH  
**Product number** 3013646645006

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses** Varnish for Acrylic Painting  
**Uses advised against** No specific uses advised against are identified.

**1.3. Details of the supplier of the safety data sheet**

**Supplier** ColArt International Holdings Ltd.  
The Studio Building  
21 Evesham Street  
London  
W11 4AJ  
United Kingdom  
+44 (0)208 424 3200  
R.Enquiries@colart.co.uk

**Contact person** Regulatory Manager

**Manufacturer** ColArt International SA  
5 Rue Rene Panhard  
Z.I .Nord  
72021 Le Mans Cedex 2  
+33 2 43 83 83 00

**1.4. Emergency telephone number**

**Emergency telephone** +44 (0)208 424 3200 This telephone number is available during office hours only 09:00 to 17:00 GMT Language English.

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification**

**Physical hazards** Aerosol 1 - H222, H229  
**Health hazards** Not Classified  
**Environmental hazards** Not Classified

**Classification (67/548/EEC or 1999/45/EC)** F+; R12

**2.2. Label elements****Pictogram**

**Signal word** Danger

## LIQUITEX PROFESSIONAL SPRAY GLOSS VARNISH

### Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurised container: may burst if heated

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing vapour/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER/doctor if you feel unwell.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 Dispose of contents/container in accordance with national regulations.  
P102 Keep out of reach of children.  
P103 Read label before use.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/Information on Ingredients

### 3.2. Mixtures

<b>DIMETHYL ETHER</b> <span>30-60%</span>		
CAS number: 115-10-6	EC number: 204-065-8	REACH registration number: 01-2119472128-37
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas	<b>Classification (67/548/EEC or 1999/45/EC)</b> F+;R12	

<b>ETHANOL</b> <span>10-30%</span>		
CAS number: 64-17-5	EC number: 200-578-6	REACH registration number: 01-2119457610-43-xxxx
<b>Classification</b> Flam. Liq. 2 - H225	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11	

<b>ACETONE</b> <span>1-5%</span>		
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-xxxx
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 Xi;R36 R66 R67	



**LIQUITEX PROFESSIONAL SPRAY GLOSS VARNISH**

<b>METHANOL</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 67-56-1	EC number: 200-659-6	REACH registration number: 01-2119433307-44-xxxx
<b>Classification</b> Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370		<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 T;R23/24/25,R39/23/24/25
<b>PROPAN-2-OL</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-xxxx
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336		<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 Xi;R36 R67
<b>TRIETHYLAMINE</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 121-44-8	EC number: 204-469-4	
<b>Classification</b> Flam. Liq. 2 - H225 Acute Tox. 4 - H302 Acute Tox. 3 - H311 Acute Tox. 3 - H331 Skin Corr. 1A - H314 Eye Dam. 1 - H318 STOT SE 3 - H335		<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 C;R35 Xn;R20/21/22
<b>2-BUTOXYETHANOL</b> <span style="float: right;"><b>&lt;1%</b></span>		
CAS number: 111-76-2	EC number: 203-905-0	REACH registration number: 01-2119475108-36-xxxx
<b>Classification</b> Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332		<b>Classification (67/548/EEC or 1999/45/EC)</b> Xn;R20/21/22 Xi;R36/38

## LIQUITEX PROFESSIONAL SPRAY GLOSS VARNISH

<b>METHYL ACETATE</b>		<b>&lt;1%</b>
CAS number: 79-20-9                      EC number: 201-185-2		
<b>Classification</b> Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	<b>Classification (67/548/EEC or 1999/45/EC)</b> F;R11 Xi;R36 R66 R67	

  

<b>2-DIMETHYLAMINOETHANOL</b>		<b>&lt;1%</b>
CAS number: 108-01-0                      EC number: 203-542-8		
<b>Classification</b> Flam. Liq. 3 - H226 Skin Corr. 1B - H314 Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 STOT SE 3 - H335 Eye Dam. 1 - H318	<b>Classification (67/548/EEC or 1999/45/EC)</b> R10 C;R34 Xn;R20/21/22	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	If in doubt, get medical attention promptly. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms are severe or persist.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Get medical advice/attention if you feel unwell. Do not induce vomiting unless under the direction of medical personnel.
<b>Skin contact</b>	Rinse with water.
<b>Eye contact</b>	Rinse with water. Get medical attention if any discomfort continues.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	Spray/mists may cause respiratory tract irritation.
<b>Ingestion</b>	Due to the physical nature of this product, it is unlikely that ingestion will occur.
<b>Skin contact</b>	Repeated exposure may cause skin dryness or cracking.
<b>Eye contact</b>	May be slightly irritating to eyes. May cause discomfort.

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

### SECTION 5: Firefighting measures



## LIQUITEX PROFESSIONAL SPRAY GLOSS VARNISH

### 5.1. Extinguishing media

**Suitable extinguishing media** The product is flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and propellant.

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Risk of explosion. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated.

### 6.2. Environmental precautions

**Environmental precautions** Avoid discharge into drains or watercourses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Do not allow material to enter confined spaces, due to the risk of explosion. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

## LIQUITEX PROFESSIONAL SPRAY GLOSS VARNISH

### Usage precautions

Keep out of the reach of children. Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Avoid exposing aerosol containers to high temperatures or direct sunlight. The product is flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Avoid contact with eyes. Avoid inhalation of vapours and spray/mists.

### Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage precautions

Store locked up. Keep away from oxidising materials, heat and flames. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Protect from sunlight. Do not store near heat sources or expose to high temperatures. Do not expose to temperatures exceeding 50°C/122°F.

#### Storage class

Chemical storage.

### 7.3. Specific end use(s)

#### Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### DIMETHYL ETHER

Long-term exposure limit (8-hour TWA): OES 400 ppm 766 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): OES 500 ppm 958 mg/m<sup>3</sup>

##### ETHANOL

Long-term exposure limit (8-hour TWA): OES 1000 ppm 1920 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): OES

##### ACETONE

Long-term exposure limit (8-hour TWA): OES 500 ppm 1210 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): OES 1500 ppm 3620 mg/m<sup>3</sup>

##### METHANOL

Long-term exposure limit (8-hour TWA): OES 200 ppm(Sk) 266 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): OES 250 ppm(Sk) 333 mg/m<sup>3</sup>(Sk)

##### PROPAN-2-OL

Long-term exposure limit (8-hour TWA): OES 400 ppm 999 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): OES 500 ppm 1250 mg/m<sup>3</sup>

##### TRIETHYLAMINE

Long-term exposure limit (8-hour TWA): OES 2 ppm(Sk) 8 mg/m<sup>3</sup>(Sk)

Short-term exposure limit (15-minute): OES 4 ppm(Sk) 17 mg/m<sup>3</sup>(Sk)

##### 2-BUTOXYETHANOL

Long-term exposure limit (8-hour TWA): OES 25 ppm(Sk)

Short-term exposure limit (15-minute): OES 50 ppm(Sk)

##### METHYL ACETATE



## LIQUITEX PROFESSIONAL SPRAY GLOSS VARNISH

Long-term exposure limit (8-hour TWA): OES 200 ppm 616 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): OES 250 ppm 770 mg/m<sup>3</sup>

### 2-DIMETHYLAMINOETHANOL

Long-term exposure limit (8-hour TWA): OES 2 ppm 7.4 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): OES 6 ppm 22 mg/m<sup>3</sup>

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation.

#### Eye/face protection

Avoid contact with eyes. Large Spillages: Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

#### Hand protection

No specific hand protection recommended.

#### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

#### Hygiene measures

Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

#### Respiratory protection

No specific recommendations. Provide adequate ventilation. Large Spillages: If ventilation is inadequate, suitable respiratory protection must be worn.

#### Environmental exposure controls

Keep container tightly sealed when not in use. Avoid release to the environment.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Colourless.
Odour	Organic solvents.
Flash point	<40°C
Upper/lower flammability or explosive limits	: 1.8
Auto-ignition temperature	> 400°C
Comments	Information given is applicable to the major ingredient.

### 9.2. Other Information

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

#### Reactivity

There are no known reactivity hazards associated with this product.

### 10.2. Chemical stability

#### Stability

Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

## LIQUITEX PROFESSIONAL SPRAY GLOSS VARNISH

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** The following materials may react strongly with the product: Oxidising agents.

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid exposing aerosol containers to high temperatures or direct sunlight. Pressurised container: may burst if heated

### 10.5. Incompatible materials

**Materials to avoid** No specific material or group of materials is likely to react with the product to produce a hazardous situation.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

## SECTION 11: Toxicological Information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE oral (mg/kg)** 19,762.85

#### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE dermal (mg/kg)** 36,460.87

#### Acute toxicity - Inhalation

**Notes (Inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE inhalation (gases ppm)** 220,959.6

**ATE inhalation (vapours mg/l)** 364.61

**ATE inhalation (dusts/mists mg/l)** 157.83

#### Skin corrosion/Irritation

**Animal data** Based on available data the classification criteria are not met.

#### Serious eye damage/Irritation

**Serious eye damage/Irritation** Based on available data the classification criteria are not met.

#### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

#### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

**Genotoxicity - In vitro** Based on available data the classification criteria are not met.

#### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

#### IARC carcinogenicity

Contains a substance/a group of substances which may cause cancer. IARC Group 1 Carcinogenic to humans.



## LIQUITEX PROFESSIONAL SPRAY GLOSS VARNISH

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** Not classified as a specific target organ toxicant after a single exposure.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

### Aspiration hazard

**Aspiration hazard** Based on available data the classification criteria are not met.

### General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

**Inhalation** Spray/mists may cause respiratory tract irritation.

**Ingestion** Due to the physical nature of this product, it is unlikely that ingestion will occur.

**Skin contact** Repeated exposure may cause skin dryness or cracking.

**Eye contact** May be slightly irritating to eyes. May cause discomfort.

**Acute and chronic health hazards** Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Nausea, vomiting. Headache. Gas or vapour in high concentrations may irritate the respiratory system.

**Route of entry** Ingestion Inhalation Skin and/or eye contact

**Target organs** No specific target organs known.

**Medical symptoms** Symptoms following overexposure may include the following: Headache. Dizziness. Arrhythmia, (deviation from normal heart beat).

## SECTION 12: Ecological Information

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

### 12.1. Toxicity

**Toxicity** Based on available data the classification criteria are not met.

### 12.2. Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

### 12.4. Mobility in soil

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

**LIQUITEX PROFESSIONAL SPRAY GLOSS VARNISH****Other adverse effects**          None known.**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

**General information**          The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

**Disposal methods**          Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Waste class**                  14 06 03\* - waste aerosol propellants, other solvents and solvent mixtures

**SECTION 14: Transport information****14.1. UN number**

**UN No. (ADR/RID)**          1950

**UN No. (IMDG)**              1950

**UN No. (ICAO)**              1950

**UN No. (ADN)**              1950

**14.2. UN proper shipping name**

**Proper shipping name (ADR/RID)**      AEROSOLS

**Proper shipping name (IMDG)**          AEROSOLS

**Proper shipping name (ICAO)**      AEROSOLS

**Proper shipping name (ADN)**      AEROSOLS

**14.3. Transport hazard class(es)**

**ADR/RID class**              2.1

**ADR/RID classification code**      5F

**ADR/RID label**              2.1

**IMDG class**                  2.1

**ICAO class/division**          2.1

**ADN class**                  2.1

**Transport labels****14.4. Packing group****14.5. Environmental hazards**



**LIQUITEX PROFESSIONAL SPRAY GLOSS VARNISH****Environmentally hazardous substance/marine pollutant**

No.

**14.6. Special precautions for user****EmS** F-D, S-U**ADR transport category** 2**Tunnel restriction code** (D)**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code****SECTION 15: Regulatory Information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations**

Health and Safety at Work etc. Act 1974 (as amended).  
The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).  
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].  
EH40/2005 Workplace exposure limits.  
The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

**EU legislation**

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Commission Regulation (EU) No 453/2010 of 20 May 2010.  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).  
Dangerous Preparations Directive 1999/45/EC.  
Dangerous Substances Directive 67/548/EEC.  
Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended).

**15.2. Chemical safety assessment**

No chemical safety assessment has been carried out.

**SECTION 16: Other Information**

**Classification procedures according to Regulation (EC) 1272/2008** Aerosol 1 - H222, H229: : Expert judgement.

**Training advice** Read and follow manufacturer's recommendations.

**Revision date** 17/08/2015

**Revision** 4

**Supersedes date** 17/08/2015

**LIQUITEX PROFESSIONAL SPRAY GLOSS VARNISH****Risk phrases in full**

R10 Flammable.  
R11 Highly flammable.  
R12 Extremely flammable.  
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.  
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.  
R34 Causes burns.  
R35 Causes severe burns.  
R36 Irritating to eyes.  
R36/38 Irritating to eyes and skin.  
R37 Irritating to respiratory system.  
R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.  
R11 Highly flammable

**Hazard statements in full**

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H226 Flammable liquid and vapour.  
H229 Pressurised container: may burst if heated  
H301 Toxic if swallowed.  
H302 Harmful if swallowed.  
H311 Toxic in contact with skin.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H331 Toxic if inhaled.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H370 Causes damage to organs .

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.