

206223 AtC

Revision: 06.04.2016

Version number 1

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- Trade name SC0639
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Product category PC1 Adhesives, sealants
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:
- H.B. Fuller, Isar-Rakoll, S.A.
- Estrada Nacional 13
- PT-4486-851 Mindelo Vila do Conde
- +351 229 288 200
- EU-MSDS@hbfuller.com
- · Informing department: Regulatory department
- · 1.4 Emergency telephone number: +44 (0) 1235 239 670 (24 hours)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008
- Flam. Liq. 2 H225 Highly flammable liquid and vapour.
- Skin Irrit. 2 H315 Causes skin irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- H361f Suspected of damaging fertility. Repr. 2 STOT SE 3 H336 May cause drowsiness or dizziness.
- STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
- Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.
- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms









GHS02 GHS07 GHS08 GHS09 · Signal word Danger

- · Hazard-determining components of labelling:
- n-hexane
- Rosin
- · Hazard statements

- H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction.
- H361f Suspected of damaging fertility.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)

Printing date 06.04.2016

Version number 1

Revision: 06.04.2016

Trade name SC0639

(Contd. of page 1)

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

water/shower.

P241

Use explosion-proof electrical/ventilating/lighting/equipment.

P260

Do not breathe dust/fume/gas/mist/vapours/spray.

P405

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

P501

Store locked up. Dispose of contents/container in accordance with local/regional/national/international

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Solvent based adhesive

Dangerous components:		
CAS: 110-54-3 EINECS: 203-777-6	n-hexane Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 8050-09-7 EINECS: 232-475-7 Reg.nr.: 01-2119480418-32-0000	Rosin Skin Sens. 1, H317	5-10%
CAS: 96-37-7 EINECS: 202-503-2	methylcyclopentane Flam. Liq. 2, H225	< 5%
CAS: 96-14-0 EINECS: 202-481-4	3-methylpentane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	< 5%
CAS: 107-83-5 EINECS: 203-523-4	2-methylpentane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	< 2.5%
CAS: 67-56-1 EINECS: 200-659-6	methanol Flam. Liq. 2, H225; Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT SE 1, H370	0.5-1%

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information

Instantly remove any clothing soiled by the product.

Take affected persons into the open air.

After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

Supply fresh air.

(Contd. on page 3)

Printing date 06.04.2016

Version number 1

Revision: 06.04.2016

(Contd. of page 2)

Trade name SC0639

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. If symptoms persist, consult doctor.

After swallowing Do not induce vomiting; instantly call for medical help.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents

Water haze

Foam

Fire-extinguishing powder

Carbon dioxide

- · For safety reasons unsuitable extinguishing agents Water with a full water jet.
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Use breathing protection against the effects of furnes/dust/aerosol.

Wear protective clothing.

6.2 Environmental precautions:

Prevent material from reaching sewage system, holes and cellars.

Inform respective authorities in case product reaches water or sewage system.

Do not allow to enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose of contaminated material as waste according to item 13.

Ensure adequate ventilation.

Send for recovery or disposal in suitable containers.

Use non sparking handtools.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders)

6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

CP

(Contd. on page 4)

Printing date 06.04.2016

Version number 1

Revision: 06.04.2016

Trade name SC0639

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Store in cool, dry place in tightly closed containers.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Ensure that suitable extractors are available on processing machines

Take note of emission threshold.

Use solvent-proof equipment.

Keep away from children

Avoid release to the environment.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

Highly volatile, flammable constituents are released during processing.

Fumes can combine with air to form an explosive mixture.

Flammable mixtures may be formed in empty containers.

- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- · Requirements to be met by storerooms and containers:

Store in cool location.

Keep dark, cool and dry.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed containers.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical systems:

Please take care on national and local requirements.

8.1 Control parameters

Components with critical values that require monitoring at the workplace:

110-54-3 n-hexane

WEL Long-term value: 72 mg/m3, 20 ppm

8050-09-7 Rosin

WEL Short-term value: 0.15 mg/m³

Long-term value: 0.05 mg/m³

Sen

67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm

- · Additional information: Based on information valid at the time of writing.
- · 8.2 Exposure controls
- Personal protective equipment
- General protective and hygienic measures

Keep away from food, drink and animal feedingstuffs.

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

(Contd. on page 5)

Printing date 06.04.2016

Version number 1

Revision: 06.04.2016

(Contd. of page 4)

(Contd. on page 6)

Trade name SC0639

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution (exceeding of TLV) use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

Not necessary if room is well-ventilated.

Ensure that suitable extractors are available on processing machines

· Protection of hands:

Solvent resistant gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves Butyl rubber, BR

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Tightly sealed safety glasses.

· Body protection: Protective work clothing.

9.1 Information on basic physical a	and chemical properties
General Information	the Branch of Asia Sarana
Appearance:	
Form:	Liquid
Colour:	Amber
Smell:	Solvent-like
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Not determined
Boiling point/Boiling range:	Not determined
Flash point:	-18 °C
Inflammability (solid, gaseous)	Not applicable.
Ignition temperature:	
Decomposition temperature:	Not determined.
Self-inflammability:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosiv vapour/air mixtures is possible.
Critical values for explosion:	
Lower:	1.2 Vol %
Upper:	7.4 Vol %
Vapour pressure at 20 °C:	160 hPa
Density at 20 °C	0.85 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Water:	Not miscible or difficult to mix

Printing date 06.04.2016

Version number 1

Revision: 06.04.2016

Trade name SC0639

		(Contd. of page 5)
· Partition coefficient (n-octano	Vwater): Not determined.	
Viscosity: dynamic at 20 °C: kinematic:	45000 mPas Not determined.	
Solvent content: Organic solvents:	39.4 %	
Solids content: 9.2 Other information	60.0 % No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions Develops readily flammable vapours / fumes
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Additional toxicological information: Possible risk of impaired male and female fertility.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity

Suspected of damaging fertility.

STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 7)

Printing date 06.04.2016

Version number 1

Revision: 06.04.2016

(Contd. of page 6)

Trade name SC0639

· 12.4 Mobility in soil No further relevant information available.

· Ecotoxical effects:

· Remark: Toxic for fish

· Additional ecological information:

· General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Danger to drinking water if even small quantities leak into soil.

· 12.5 Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to disposers of hazardous waste.

Incineration under approved, controlled conditions using incinerators suitable or designed for the disposal of hazardous chemical wastes, is the preferred method for disposal.

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	UN1133
14.2 UN proper shipping name	1133 ADHESIVES, ENVIRONMENTALLY
IMDG	HAZARDOUS ADHESIVES (HEXANES, HEXANES), MARINE POLLUTANT
IATA	Adhesives
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
· 14.4 Packing group	
ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: n-hexane
Marine pollutant:	Yes
	Symbol (fish and tree)

Printing date 06.04.2016

Version number 1

Revision: 06.04.2016

Trade name SC0639

	(Contd. of page
· Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user Kemler Number: EMS Number: Stowage Category	Warning: Flammable liquids. 33 F-E,S-D A
14.7 Transport in bulk according to Ann Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ) Transport category	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m 3
Tunnel restriction code Remarks:	D/E Viscous according to ADR § 2.2.3.1.4
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 m
Remarks:	Suitable UN approved container necessary. Viscous according to 2.3.2.3 of the IMDG code
· IATA · Remarks:	Suitable UN approved container necessary. Viscous according to IATA § 3.3.3.1
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, III, ENVIRONMENTALL HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations
- · Other regulations, limitations and prohibitive regulations
- · VOC (EU) in %: 39.41 % · VOC (EU) in g/l: 334.9 g/l
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The information provided about the product on this Safety Sheet has been compiled from knowledge of

the individual constituent.

(Contd. on page 9)

Printing date 06.04.2016

Version number 1

Revision: 06.04.2016

Trade name SC0639

(Contd. of page 8)

The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications - usage in such may cause risks not mentioned in this sheet. Do not use for other application(s) without seeking advice from manufacturer.

H225 Highly flammable liquid and vapour. H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation. H317 May cause an allergic skin reaction.

H331 Toxic if inhaled. H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing data sheet: Regulatory department

Contact: EU-MSDS@hbfuller.com

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 2: Flammable liquids, Hazard Category 2
Acute Tox. 3: Acute toxicity, Hazard Category 3
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Repr. 2: Reproductive toxicity, Hazard Category 2
STOT SE 1: Specific target organ toxicity - Single exposure, Hazard Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Acutatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

* Data compared to the previous version altered.