

# 3A Composites

9736600

## Material Safety Data Sheet

Sintra®

Initial Release Date: August 28, 2002

Revised May 6, 2011

6950.

### Section I Product Identification

Manufacturer: 3A Composites USA, Inc.  
208 W. 5<sup>th</sup> Street, P.O. Box 507  
Benton, KY 42025  
(270) 527-4200

Emergency Phone Number: 1-800-424-9300 Chemtrec  
To be used only in the event of chemical emergencies involving a spill, leak, fire, and exposure accidents involving chemicals.

Trade Name: Sintra® & e-pvc™

Synonym: Expanded PVC Sheet, Polyvinyl Chloride Sheet, Sintra® Standard Density, Sintra® Low Density

### Section II Material Identification and Information

Ingredients	Percent (%) (By wt.)	Occupational Exp. Limits	
		(TWA) ACGIH	(PEL) OSHA
Polyvinyl Chloride	70-85	10.0 mg/m <sup>3</sup>	15.0 mg/m <sup>3</sup> Total <sup>(1)</sup> 5.0 mg/m <sup>3</sup> Resp. <sup>(1)</sup>

This product is an "article" as defined in 29 CFR 1910.1200. It will not result in exposure to hazardous components under normal conditions of use.

### Section III Physical Properties

Appearance and odor: Odorless, plastic sheet

Melting point: >350 °F

Sp. Gravity: 0.5 – 0.9 g/cm<sup>3</sup> range

Solubility: Insoluble in water

### Section IV Fire and Explosion Data

Auto Ignition: N/A

Flash point: (ASTM D-1929) >700 °F

Extinguishing media: CO<sub>2</sub>, dry chemical, or water spray.

# 3A Composites

## Material Safety Data Sheet

Sintra<sup>®</sup>

Initial Release Date: August 28, 2002

Revised May 6, 2011

Special fire fighting procedure: self-contained breathing apparatus should be worn.

Unusual fire and explosion hazards: PVC will burn in the presence of supported combustion, and will emit hydrogen chloride gas, benzene, water, carbon monoxide, carbon dioxide, and smoke.

<b>Section V</b>	<b>Reactivity Data</b>
------------------	------------------------

Stability:	Stable
Incompatibility:	None known
Decomposition products:	Reference: "Unusual fire and explosion hazards", Section IV

<b>Section VI</b>	<b>Health Hazard Data</b>
-------------------	---------------------------

These products are not considered to be a health hazard in the form in which they are sold (sheet, panel). However, if these products are abraded, melted, welded, cut or processed in any manner that causes release of fumes or dusts, hazardous levels of fumes or dusts may be generated from this product.

Effects of overexposure:

Acute: Physical irritation of the eyes may result from overexposure to high concentrations of dust from certain fabricating operations.

Chronic: Studies have shown that workers exposed for long periods to high concentrations of respirable PVC dust may retain the dust in their lungs. There is no evidence of a toxic response associated with such PVC dust retention.

Special Instructions:

Avoid prolonged inhalation of high dust concentrations and ingestion of material.

Wash hands before eating, drinking or smoking.

Wear proper eye and respiratory protection when working in areas of high dust concentrations.

Care should be taken during thermoforming operations. When temperatures exceed 350 °F, decomposition of the material may occur.

Emergency and first aid procedures: If contact with eyes, wash immediately under water for at least 15 minutes. For inhalation exposure, remove to fresh air. Contact a physician.

# 3A Composites

## Material Safety Data Sheet

Sintra®

Initial Release Date: August 28, 2002

Revised May 6, 2011

### Section VII

#### Storage, Handling, and Disposal Data

- Waste disposal: Care must be taken when using or disposing of material debris to prevent environmental contamination. Dispose of the debris in accordance with the Clean Air Act, the Clean Water Act, the Resource Conservation and Recovery Act and all state or local laws / regulations regarding disposal.
- Storage and handling precautions: Store in a flat dry area  
Exercise caution in all thermal forming procedures.

### Section VIII

#### Personal Protection Data

- Primary routes of entry are: Inhalation and ingestion
- Respiratory protection: An approved NIOSH/MSHA respirator must be used when engineering controls cannot be implemented to control dust concentrations. Reference OSHA 1910.134 for specific requirements.
- Ventilation: Local exhaust. Reference OSHA 1910.94 for specific requirements.
- Eye: Eye protection must be worn when working in dust concentrations and during sawing or other operations which might cause flying debris. Reference OSHA 1910.133 for specific requirements.
- Protective glove: Gloves should be used to prevent cuts or abrasions.

### Section IX

#### Regulatory

REACH: Pursuant to Title II article 7 of the regulation this product is exempt from registration and notification and is therefore compliant with the REACH regulation.

RoHS: Sintra® products are compliant with the RoHS standard.

**IMPORTANT:** The information and data contained herein are believed to be accurate and have been compiled from sources believed to be accurate. All information contained herein is offered for your consideration, information, investigation, and verification. 3A COMPOSITES MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HEREIN. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY EXCLUDED. 3A Composites will not be responsible for claims relating to any parties' use of or reliance on information and data contained herein regardless of whether it is claimed that the information are inaccurate, incomplete, or otherwise misleading