
Page 1/10



Safety Data Sheet according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and

Printing date: September 2, 2014

Revision: September 2, 2014

4: SECTION : Toknitteation of the substance/mixible and octine company.

- · 1.1 Product identifier
- · Trade name: Lightning® Bi-Chromatic™ Fingerprint Powder
- · Article number: 1003835, 1003836, 1003844, 1003994, 1-0005, 1-0006, 1-0015, 1-0305
- 1.2 Relevant identified uses of the substance or mixture and uses advised against.
 No further relevant information available.
- · 1.3 Details of the supplier of the Safety Data Sheet
- Manufacturer/Supplier:
 Safariland, LLC
 13386 International Parkway
 Jacksonville, FL 32218
 Customer Care (800) 347-1200
- 1.4 Emergency telephone number: ChemTel Inc. (800)255-3924, +1 (813)248-0585

SECTION 2. Hazards manufications with the second section of the second section of the second second

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008
- The following classifications are applicable only to OSHA (USA) regulations and not the specific CLP regulation: Carc. 2,
- Carc. 2 H351: Suspected of causing cancer.
- The product is not classified as hazardous according to the CLP regulation.
- · Classification according to Directive 67/548/EEC or Directive 1999/45/EC Not applicable.
- Information concerning particular hazards for human and environment:
- The product does not have to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
- Classification system:
- The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
- The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.
- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
- This product does not have a classification according to the CLP regulation.
- The following Hazard Statements are applicate only according to OSHA regulations within the United States. These Statements are not applicable for the CLP regulation (1272/2008/EC) in the EU: H351.
- Hazard pictograms



health hazard (US GHS only)

(Contd. on page 2)



418 N. Buchanan Circle, STE 17
Pacheco, CA 94553
www.osiforensic.com
800 227-6020

Printing date: September 2, 2014

Revision: September 2, 2014

Trade name: Lightning® BI-Chromatic™ Fingerprint Powder

(Contd. of page 1)

Signal word

Applicable only within the United States (USA) WARNING

· Hazard-determining components of labelling:

aluminium powder (stabilised)

Carbon black

Hazard statements

Not applicable within the EU; applicable only for North America.

H351; Suspected of causing cancer.

Precautionary statements

Applicable only within the United States (USA)
P281 Use personal protection Use personal protective equipment as required.

P202 Do not handle until all safety precautions have been read and understood. P308+P313 IF exposed or concerned: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

· Hazard description:

WHMIS-symbols:

D2A - Very toxic material causing other toxic effects



NFPA ratings (scale 0 - 4)



Health = 0 O Fire = 0
Reactivity = 0

· HMIS-ratings (scale 0 - 4)



REACTIVITY [Reactivity = 0

HMIS Long Term Health Hazard Substances

None of the ingredients is listed.

2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION Execution stable/information on bigreelents (4), 110000 bigreelents

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date: September 2, 2014

Revision: September 2, 2014

Trade name: Lightning® Bi-Chromatic™ Fingerprint Powder

· Dangerous compos None in reportable q	nents:	ld. of page 2
CAS: 1333-86-4 EINECS: 215-609-9	Carbon black substance with a Community workplace exposure limit	10-25%
CAS: 7429-90-5	Aluminum metal R R15 Water-react. 1, H260	2,5-10%

SECTION AL FIRST AGENCES TO THE STATE OF THE

- · 4.1 Description of first aid measures
- General Information: No special measures required.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Clean with water and soap.
- · After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Slight irritant effect on eyes.
Gastric or intestinal disorders when ingested.

Coughing

· Hazards May be harmful if inhaled.

4.3 Indication of any immediate medical attention and special treatment needed

If necessary oxygen respiration treatment.

See Section to a requirimental parameters of the section of the se

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- For safety reasons unsuitable extinguishing agents: None.
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information No further relevant information available.

TISEOREN 61 Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures
 Ensure adequate ventilation

(Contd. on page 4)

Printing date: September 2, 2014

Revision: September 2, 2014

Trade name: Lightning® Bi-Chromatic™ Fingerprint Powder

(Contd. of page 3)

Wear protective equipment. Keep unprotected persons away. For large splils, use respiratory protective device against the effects of fumes/dust/aerosol.

6.2 Environmental precautions: No special measures required.

6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Fandling and storage

- 7.1 Precautions for safe handling Use only in well ventilated areas.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any Incompatibilities
- Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Protect from humidity and water.

Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with acids.

Store away from oxidizing agents.

- Further Information about storage conditions: Store in cool, dry conditions in well sealed receptacles.
- · 7.3 Specific end use(s) No further relevant information available.

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

 Ingredients wi 	th limit values	that require	monitoring	at the workplace:

1333-86-4 Carbon black

PEL (USA) Long-term value: 3,5 mg/m8

REL (USA) Long-term value: 3,5* mg/m²

*0,1 in presence of PAHs; See Pocket Guide Apps.A+C

Long-term value: 3* mg/m³ TLV (USA)

inhalable fraction

EL (Canada) Long-term value: 3 mg/m³ IARC 2B

EV (Canada) Long-term value: 3,5 mg/m3

(Contd. on page 5)

Printing date: September 2, 2014

Revision: September 2, 2014

Trade name: Lightning® Bi-Chromatic™ Fingerprint Powder

		(Contd. of page 4
7429-90-5 Ali	uminum metal	
PEL (USA)	Long-term value: 15*; 15** mg/m² *Total dust; ** Respirable fraction	
REL (USA)	Long-term value: 10* 5** mg/m² *Total dust **Respirable fraction	
TLV (USA)	Long-term value: 1* mg/m² as Al; *as respirable fraction	
EL (Canada)	Long-term value: 1,0 mg/m³ metal and insoluble compdounds, respirable	
EV (Canada)	Long-term value: 5 mg/m² aluminium-containing (as aluminium)	

- DNELs No further relevant information available.
- · PNECs No further relevant information available.
- · Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Do not inhale dust / smoke / mist.

Avoid contact with the eyes.

Avoid close or long term contact with the skin.

Respiratory protection:

Not required under normal conditions of use.

Use suitable respiratory protective device when high concentrations are present.

For spills, respiratory protection may be advisable.

Protection of hands: Not required under normal conditions of use.

· Eye protection:



Safety glasses

Body protection:

Not required under normal conditions of use.

Protection may be required for spills.

Limitation and supervision of exposure into the environment No special requirements.

Risk management measures No special requirements.

The Seculon Particle and Carolingal Properties and the Control of the Control of

- 9.1 Information on basic physical and chemical properties
- · General Information

Appearance:

Form: Colour: Powder

Black

(Contd. on page 6)

Printing date: September 2, 2014

Revision: September 2, 2014

(Contd. of page 5)

Trade name: Lightning® Bi-Chromatic™ Fingerprint Powder

· Odour:

Odour threshold:

Odourless

Not determined.

· pH-value:

Not applicable.

· Change in condition

Melting point/Melting range: Boiling point/Bolling range: Not Determined. Undetermined.

· Flash point:

Not applicable.

Flammability (solid, gaseous):

Not determined.

Not determined.

Auto/Self-ignition temperature:
 Decomposition temperature:

Not determined.

Self-igniting:

Product is not self-igniting.

· Danger of explosion:

Product does not present an explosion hazard.

Explosion limits:

Lower: Upper: Not determined. Not determined.

· Vapour pressure:

Not applicable.

Density at 20 °C:

2,6 g/cm³

Relative density
Vapour density
Evaporation rate

Not determined. Not applicable. Not applicable.

· Solubility in / Miscibility with

water:

Insoluble.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:

Not applicable. Not applicable.

Kinematic: 9.2 Other information

No further relevant information available.

HASTON FOR SUBSTITUTE TO A CASE OF THE PROPERTY OF THE PROPERT

· 10.1 Reactivity

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

10.3 Possibility of hazardous reactions

As the product is supplied it is not capable of dust explosion; however enrichment with fine dust causes risk of dust explosion.

Reacts with oxidizing agents.

Reacts with strong acids.

Reacts with strong alkali.

(Contd. on page 7)

Revision: September 2, 2014

Trade name: Lightning® Bi-Chromatic™ Fingerprint Powder

(Contd. of page 6)

Toxic fumes may be released if heated above the decomposition point.

10.4 Conditions to avoid Store away from oxidizing agents.

10.5 Incompatible materials: No further relevant information available.

10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

Toxic metal oxide smoke

- · 11.1 Information on toxicological effects
- Acute toxicity:

Printing date: September 2, 2014

- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Slight irritant effect on eyes.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information: May be harmful if inhaled.
- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction): Based on IARC classifications and not the CLP classification.

Carc. 2B

SECTION ES Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- General notes: Not known to be hazardous to water.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13 Disposal considerations

- 13.1 Waste treatment methods
- Recommendation

Smaller quantities can be disposed of with household waste.

Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.

The user of this material has the responsibility to dispose of unused material, residues and containers in

compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

(Contd. on page 8)

Printing date: September 2, 2014

Revision: September 2, 2014

Trade name: Lightning® Bi-Chromatic™ Fingerprint Powder

(Contd. of page 7)

· Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.
 Recommended cleansing agents: Water, if necessary together with cleansing agents.

##SECTION 14 Transport information · 14.1 UN-Number · DOT, ADR, ADN, IMDG, IATA Not Regulated 14.2 UN proper shipping name DOT, ADR, ADN, IMDG, IATA Not Regulated · 14.3 Transport hazard class(es) DOT, ADR, ADN, IMDG, IATA · Class Not Regulated 14.4 Packing group DOT, ADR, IMDG, IATA Not Regulated 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Not applicable. · 14.7 Transport in bulk according to Annex II of

THE REPORT OF THE PROPERTY OF	Company of the second product of the second
[4] [4] [4] [4] [4] [4] [4] [4] [4] [4]	
開始に対象さればは 関する と下に、 原理は、 (こ)の)が、 とう)とりに 1 (2) とりに 1 (2) (2) (2) (2) (2) (2) (2) (2) (2) (2)	
。 【1975年1月17日 - 1975年1月17日 - 1975年1	Particular 1515年以后,1950年的1950年的1950年的1950年的1950年的1950年的1950年的1950年的1950年的1950年的1950年的1950年的1950年的1950年的1950年的1

· 15.1 8afety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable.

- · United States (USA)
- SARA
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

MARPOL73/78 and the IBC Code

UN "Model Regulation";

Section 313 (Specific toxic chemical listings):

7429-90-5 Aluminum metal

TSCA (Toxic Substances Control Act):

All ingredients are listed.

- Proposition 65 (California):
- · Chemicals known to cause cancer:

1333-86-4 Carbon black

Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 9)

Printing date: September 2, 2014 Revision: September 2, 2014

	(Contd. of par
Chemicals known to cause developmental toxicity:	, , , , , , , , , , , , , , , , , , , ,
None of the ingredients is listed.	
Carcinogenic Categories	
EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
· IARC (International Agency for Research on Cancer)	
1333-86-4 Carbon black	
TLV (Threshold Limit Value established by ACGiH)	
1333-86-4 Carbon black	
7429-90-5 Aluminum metal	
NIOSH-Ca (National Institute for Occupational Safety and H	lealth)
1333-86-4 Carbon black	
Canada	
Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients is listed.	
Canadian Ingredient Disclosure list (limit 1%)	
1333-86-4 Carbon black	
7429-90-5 Aluminum metal	AA
Other regulations, limitations and prohibitive regulations This product has been classified in accordance with hazard crit and the SDS contains all the information required by the Control	eria of the Controlled Products Regulational
Substances of very high concern (SVHC) according to REA	
None of the ingredients is listed.	

MESECALONIC OFFICE CONTROL OF THE PROPERTY OF This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H260 In contact with water releases flammable gases which may ignite spontaneously.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

R15 Contact with water liberates extremely flammable gases.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Alr Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

(Contd. on page 10)

(Contd. on page 10)

Printing date: September 2, 2014

Revision: September 2, 2014

Trade name: Lightning® Bi-Chromatic™ Fingerprint Powder

(Contd. of page 9)

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
WHMIS: Workplace Hazardous Materials information System (Canada)
DNEL; Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
Water-react. 1; Substances and Mixtures which, in contact with water, emit flammable gases, Hazard Category 1

Sources

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com