

769.

MATERIAL SAFETY DATA SHEET

C11385

1. Product and Company Identification

Product number 1000002942
 Material name **13 OZ CLEAR GROOMING ADHESIVE**
 Revision date 11-11-2013
 Company information Stone Manufacturing & Supply Company, Inc.
 1212 Kansas Ave
 Kansas City, MO 64127 United States
 Company phone 1-816-231-4020
 Emergency telephone US 1-866-836-8855
 Emergency telephone outside US 1-952-852-4646
 Version # 02
 Supersedes date 11-06-2013

2. Hazards Identification

Emergency overview **DANGER**
 Flammable. CONTENTS UNDER PRESSURE.
 Pressurized container may explode when exposed to heat or flame. May cause flash fire or explosion.
 Will be easily ignited by heat, spark or flames. Cancer hazard. Prolonged exposure may cause chronic effects.

OSHA regulatory status This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

Potential health effects
 Routes of exposure Inhalation. Ingestion. Skin contact. Eye contact.
 Eyes Contact with eyes may cause irritation. Health injuries are not known or expected under normal use.
 Skin Health injuries are not known or expected under normal use.
 Inhalation May cause cancer by inhalation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.
 Ingestion Harmful if swallowed. Exposure by ingestion of an aerosol is unlikely. Components of the product may be absorbed into the body by ingestion.

Target organs Cardiac. Central nervous system. Kidneys. Liver. Lungs. Respiratory system.

Chronic effects Shortness of breath. Edema. Jaundice. Liver injury may occur. Kidney injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage. May cause delayed lung injury.

Signs and symptoms Discomfort in the chest. Shortness of breath. Narcosis. Decrease in motor functions. Behavioral changes. Coughing. Edema. Liver enlargement. Jaundice. Proteinuria.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Methylene Chloride	75-09-2	40 - 60
Butane	106-97-8	10 - 20
n-Hexane	110-54-3	10 - 20
Propane	74-98-6	10 - 20
Toluene	108-88-3	2.5 - 10
Propylene Oxide	75-56-9	0.1 - 1
Other components below reportable levels		2.5 - 10

4. First Aid Measures

First aid procedures

Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Remove and isolate contaminated clothing and shoes. Immediately flush skin with plenty of water. Get medical attention if irritation develops and persists. For minor skin contact, avoid spreading material on unaffected skin. Wash clothing separately before reuse.
Inhalation	If inhalation of gas/fume/vapor/dust/mist from the material is excessive (air concentration is greater than the TLV or health effects are noticed), immediately remove the affected person(s) to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.
Ingestion	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Rinse mouth thoroughly. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Notes to physician	In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General advice	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation.

5. Fire Fighting Measures

Flammable properties	Flammable by OSHA criteria. Heat may cause the containers to explode. Vapors may travel considerable distance to a source of ignition and flash back. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media	
Suitable extinguishing media	Powder. Water. Foam. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Protection of firefighters	
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.
Protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

6. Accidental Release Measures

Personal precautions	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the MSDS.
Environmental precautions	Prevent further leakage or spillage if safe to do so. Do not contaminate water.
Methods for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Prevent entry into waterways, sewer, basements or confined areas.
Methods for cleaning up	Should not be released into the environment. Stop the flow of material, if this is without risk. Isolate area until gas has dispersed. Following product recovery, flush area with water. For waste disposal, see section 13 of the MSDS.

7. Handling and Storage

Handling

Vapors may form explosive mixtures with air. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Use only in area provided with appropriate exhaust ventilation. Wash thoroughly after handling.

Storage

Store locked up. Contents under pressure. The pressure in sealed containers can increase under the influence of heat. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the MSDS). Level 2 Aerosol.

8. Exposure Controls / Personal Protection

Occupational exposure limits

ACGIH Biological Exposure Indices Components

Components	Type	Value
Methylene Chloride (CAS 75-09-2)	BEI	0.3 mg/l
n-Hexane (CAS 110-54-3)	BEI	0.4 mg/l
Toluene (CAS 108-88-3)	BEI	0.3 mg/g 0.03 mg/l 0.02 mg/l

US. ACGIH Threshold Limit Values Components

Components	Type	Value
Methylene Chloride (CAS 75-09-2)	TWA	50 ppm
n-Hexane (CAS 110-54-3)	TWA	50 ppm
Propylene Oxide (CAS 75-56-9)	TWA	2 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
Methylene Chloride (CAS 75-09-2)	STEL	125 ppm
	TWA	25 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
n-Hexane (CAS 110-54-3)	PEL	1800 mg/m ³ 500 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m ³ 1000 ppm
Propylene Oxide (CAS 75-56-9)	PEL	240 mg/m ³ 100 ppm

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye / face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Wear chemical protective equipment that is specifically recommended by the manufacturer.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

General hygiene considerations When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical & Chemical Properties

Appearance Not available.

Auto-ignition temperature 814.75 °F (434.86 °C) estimated

Boiling point 96.99 °F (36.1 °C) estimated

Color Not available.

Flammability limits in air, upper, % by volume 33.1 % estimated

Flammability limits in air, lower, % by volume 7.6 % estimated

Flash point -156.00 °F (-104.44 °C) Propellant estimated

Form Aerosol.

Odor Not available.

Odor threshold Not available.

pH Not available.

Physical state Gas.

Solubility (water) Not available.

Specific gravity 0.881 estimated

Vapor pressure 54 psig @68F estimated

Other data

Heat of combustion 20.37 kJ/g estimated

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition.

Conditions to avoid Heat, flames and sparks. Avoid temperatures exceeding the flash point.

Hazardous decomposition products No hazardous decomposition products are known.

Possibility of hazardous reactions Hazardous polymerization does not occur.

11. Toxicological Information

Toxicological data

Product	Species	Test Results
13 OZ CLEAR GROOMING ADHESIVE (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	188 ml/kg, estimated
	Rat	18540 mg/kg, estimated
<i>Inhalation</i>		
LC50	Guinea pig	93.9582 mg/l, 6 Hours, estimated
	Mouse	70933.3359 mg/l, 8 Hours, estimated
		5333.3335 mg/l, 24 Hours, estimated
		131.4246 mg/l, 7 Hours, estimated
		120.3693 mg/l, 2 Hours, estimated
		114.7598 mg/l, 6 Hours, estimated
	Rat	4674.5356 mg/l, 15 Minutes, estimated

Product	Species	Test Results
		205.6796 mg/l, 900 Days, estimated
		184.6442 mg/l, 2 Hours, estimated
		150.3935 mg/l/4h, estimated
		121.5379 mg/l, 6 Hours, estimated
LD50	Mouse	37396.2852 mg/l, 7 Hours, estimated
<i>Oral</i>		
LD50	Rat	177.7778 mg/kg, estimated
	Wistar rat	362.963 mg/kg, estimated
<i>Other</i>		
LD50	Mouse	441.9823 mg/kg, estimated
	Rabbit	697.6744 ml/kg, estimated
	Rat	14156.3574 mg/kg, estimated
Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
Methylene Chloride (CAS 75-09-2)		
Acute		
<i>Inhalation</i>		
LC50	Guinea pig	40.2 mg/l, 6 Hours
	Mouse	56.23 mg/l, 7 Hours
		51.5 mg/l, 2 Hours
		49.1 mg/l, 6 Hours
	Rat	2000 mg/l, 15 Minutes
		88 mg/l, 900 Days
		79 mg/l, 2 Hours
		52 mg/l, 6 Hours
LD50	Mouse	16000 mg/l, 7 Hours
<i>Oral</i>		
LD50	Rat	1600 mg/kg
<i>Other</i>		
LD50	Mouse	437 mg/kg
n-Hexane (CAS 110-54-3)		
Acute		
<i>Inhalation</i>		
LC50	Mouse	48000 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	24 mg/kg
	Wistar rat	49 mg/kg
Propane (CAS 74-98-6)		
Acute		
<i>Inhalation</i>		
LC50	Rat	> 1442.847 mg/l, 15 Minutes
		658 mg/l/4h

Components	Species	Test Results
Propylene Oxide (CAS 75-56-9)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	1245 mg/kg
<i>Inhalation</i>		
LC50	Mouse	1740 mg/l, 4 Hours
	Rat	4000 mg/l, 4 Hours
<i>Oral</i>		
LD50	Guinea pig	660 mg/kg
	Rat	380 mg/kg
<i>Other</i>		
LD50	Mouse	175 mg/kg
	Rabbit	1.5 ml/kg
	Rat	150 mg/kg
Toluene (CAS 108-88-3)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	12124 mg/kg
		14.1 ml/kg
<i>Inhalation</i>		
LC50	Mouse	5320 mg/l, 8 Hours
		400 mg/l, 24 Hours
	Rat	26700 mg/l, If <1L: Consumer Commodity Hours
		12200 mg/l, 2 Hours
		8000 mg/l, 4 Hours
<i>Oral</i>		
LD50	Rat	2.6 g/kg
<i>Other</i>		
LD50	Mouse	59 mg/kg
	Rat	1332 mg/kg

* Estimates for product may be based on additional component data not shown.

Local effects	Toxic if swallowed. Liver toxicity.
Chronic effects	Hazardous by OSHA criteria. Prolonged or repeated exposure may cause lung injury. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects.
Subchronic effects	Kidney injury may occur.
Carcinogenicity	Hazardous by OSHA criteria. Risk of cancer cannot be excluded with prolonged exposure.

ACGIH Carcinogens

Methylene Chloride (CAS 75-09-2)	A3 Confirmed animal carcinogen with unknown relevance to humans.
Propylene Oxide (CAS 75-56-9)	A3 Confirmed animal carcinogen with unknown relevance to humans.
Toluene (CAS 108-88-3)	A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Methylene Chloride (CAS 75-09-2)	2B Possibly carcinogenic to humans.
Propylene Oxide (CAS 75-56-9)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.

US NTP Report on Carcinogens: Anticipated carcinogen

Methylene Chloride (CAS 75-09-2)

Reasonably Anticipated to be a Human Carcinogen.

Propylene Oxide (CAS 75-56-9)

Reasonably Anticipated to be a Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Methylene Chloride (CAS 75-09-2)

Potential cancer hazard.

Neurological effects Hazardous by OSHA criteria.**Further information** Symptoms may be delayed.**12. Ecological Information****Ecotoxicological data**

Product	Species	Test Results
13 OZ CLEAR GROOMING ADHESIVE (CAS Mixture)		
Algae	IC50	Algae 972.686 mg/L, 72 Hours, estimated
Crustacea	EC50	Daphnia 99.308 mg/L, 48 Hours, estimated
Fish	LC50	Fish 26.4294 mg/L, 96 Hours, estimated
Components		
Methylene Chloride (CAS 75-09-2)		
Algae	IC50	Algae 500.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia 1689.5 mg/L, 48 Hours
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 1250 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) 140.8 - 277.8 mg/l, 96 hours
n-Hexane (CAS 110-54-3)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 2.101 - 2.981 mg/l, 96 hours
Propylene Oxide (CAS 75-56-9)		
Crustacea	EC50	Daphnia 350 mg/L, 48 Hours
Toluene (CAS 108-88-3)		
Algae	IC50	Algae 433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia 7.645 mg/L, 48 Hours
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon, silver salmon (Oncorhynchus kisutch) 8.11 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Ecotoxicity Components of this product are hazardous to aquatic life.**Environmental effects** Harmful to aquatic organisms. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.**Persistence and degradability** Not available.**Bioaccumulation / Accumulation****Bioaccumulative potential****Octanol/water partition coefficient log Kow**

Butane	2.89
Methylene Chloride	1.25
n-Hexane	3.9
Propane	2.36
Propylene Oxide	0.03
Toluene	2.73

Partition coefficient

Butane	2.89
Methylene Chloride	1.25
n-Hexane	3.9

Propylene Oxide	0.03
Toluene	2.73

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

US RCRA Hazardous Waste U List: Reference

Methylene Chloride (CAS 75-09-2)	U080
Toluene (CAS 108-88-3)	U220

Disposal instructions Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information

DOT

Basic shipping requirements:

UN number	UN1950
Proper shipping name	Aerosols, flammable
Hazard class	2.1
Additional information:	
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2013, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/13 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, containing substances in Division 6.1, Packing Group III
Transport hazard class(es)	2.1
Subsidiary class(es)	6.1(PGIII)
ERG code	10P
Packaging Exceptions	LTD QTY

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, MARINE POLLUTANT
Transport hazard class(es)	2.1
Subsidiary class(es)	6.1(PGIII)
Environmental hazards	
Marine pollutant	Yes
EmS	F-D, S-U
Packaging Exceptions	NOT a LTD QTY

DOT



IATA; IMDG



Marine pollutant



15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3)	159 kg by weight 50 gallons by volume 6594
------------------------	--

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3)	35 % weight/volumn
------------------------	--------------------

DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3)	594
------------------------	-----

US EPCRA (SARA Title III) Section 302 - Extremely Hazardous Spill: Reportable quantity

Propylene Oxide (CAS 75-56-9)	100 lbs
-------------------------------	---------

US EPCRA (SARA Title III) Section 302 - Extremely Hazardous Substance: Threshold Planning Quantity

Propylene Oxide (CAS 75-56-9)	10000 lbs
-------------------------------	-----------

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Methylene Chloride (CAS 75-09-2)	0.1 %
n-Hexane (CAS 110-54-3)	1.0 %
Propylene Oxide (CAS 75-56-9)	0.1 %
Toluene (CAS 108-88-3)	1.0 %

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Methylene Chloride (CAS 75-09-2)	Listed.
n-Hexane (CAS 110-54-3)	Listed.
Propylene Oxide (CAS 75-56-9)	Listed.
Toluene (CAS 108-88-3)	Listed.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA (Superfund) reportable quantity

Methylene Chloride: 1000
 n-Hexane: 5000
 Toluene: 1000
 Propylene Oxide: 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
 Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - Yes
 Pressure Hazard - Yes
 Reactivity Hazard - No

Section 302 extremely hazardous substance No

SARA 311/312 Hazardous chemical No

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

State regulations

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - New Jersey RTK - Substances: Listed substance

Butane (CAS 106-97-8)	Listed.
Methylene Chloride (CAS 75-09-2)	Listed.
n-Hexane (CAS 110-54-3)	Listed.
Propane (CAS 74-98-6)	Listed.
Propylene Oxide (CAS 75-56-9)	Listed.
Toluene (CAS 108-88-3)	Listed.

US - Pennsylvania RTK - Hazardous Substances: Special hazard

Methylene Chloride (CAS 75-09-2)	Special hazard.
Propylene Oxide (CAS 75-56-9)	Special hazard.

US. Pennsylvania RTK - Hazardous Substances

Butane (CAS 106-97-8)	Listed.
Methylene Chloride (CAS 75-09-2)	Listed.
n-Hexane (CAS 110-54-3)	Listed.
Propane (CAS 74-98-6)	Listed.
Propylene Oxide (CAS 75-56-9)	Listed.
Toluene (CAS 108-88-3)	Listed.

16. Other Information

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This data sheet contains changes from the previous version in section(s):

Product and Company Identification: Product Review
Regulatory Information: Canada