

**1. Product and Company Identification**

sds Inv.# 1014

**Product number** 58106  
**Material name** 11 OZ FINAL MIST  
**Revision date** 11-19-2013  
**Company information** Stone Manufacturing & Supply Company, Inc.  
 1212 Kansas Ave  
 Kansas City, MO 64127 United States  
 Ph. 1-816-231-4020 (for information only)  
 (SMFG)  
**Emergency telephone US** 1-800-424-9300  
**Emergency telephone outside US** 1-703-527-3887  
**Version #** 02  
**Supersedes date** 12-11-2009  
**Mfg id code** 1000002941

**2. Hazards Identification**

**Emergency overview** DANGER  
 Flammable. CONTENTS UNDER PRESSURE.  
 Aerosol. Pressurized container may explode when exposed to heat or flame. May cause flash fire or explosion.  
  
 Will be easily ignited by heat, spark or flames. Prolonged exposure may cause chronic effects.

**OSHA regulatory status** This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

**Potential health effects**

**Routes of exposure** Inhalation.

**Eyes** Contact with eyes may cause irritation. Health injuries are not known or expected under normal use.

**Skin** Health injuries are not known or expected under normal use.

**Inhalation** Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

**Ingestion** Exposure by ingestion of an aerosol is unlikely.

**Target organs** Central nervous system.

**Chronic effects** May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion and blurred vision) and/or damage.

**Signs and symptoms** Narcosis. Decrease in motor functions. Behavioral changes.

**3. Composition / Information on Ingredients**

Components	CAS #	Percent
Butane	106-97-8	10 - 20
Propane	74-98-6	10 - 20
Other components below reportable levels		60 - 80

**4. First Aid Measures**

**First aid procedures**

**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.

**Skin contact** Rinse skin with water/shower. Get medical attention if irritation develops and persists.

**Inhalation** If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.

**Ingestion** In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

**Notes to physician** Symptoms may be delayed.

Product name: 11 OZ FINAL MIST  
 Product #: 58106 Version #: 02 Revision date: 11-19-2013 Issue date: 11-19-2013

SDS US  
 1 / 7



<b>General advice</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible).
<b>5. Fire Fighting Measures</b>	
<b>Flammable properties</b>	Flammable by OSHA criteria. Heat may cause the containers to explode. Vapors may travel considerable distance to a source of ignition and flash back. Runoff to sewer may cause fire or explosion hazard.
<b>Extinguishing media</b>	
<b>Suitable extinguishing media</b>	Powder. Foam. Dry chemicals. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Protection of firefighters</b>	
<b>Protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. In the event of fire and/or explosion do not breathe fumes. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6. Accidental Release Measures

<b>Personal precautions</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the MSDS.
<b>Environmental precautions</b>	Do not contaminate water.
<b>Methods for containment</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Prevent entry into waterways, sewer, basements or confined areas.
<b>Methods for cleaning up</b>	Should not be released into the environment. Stop the flow of material, if this is without risk. Isolate area until gas has dispersed. Following product recovery, flush area with water. Scrub the area with detergent and water. For waste disposal, see section 13 of the MSDS.

## 7. Handling and Storage

<b>Handling</b>	Vapors may form explosive mixtures with air. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in area provided with appropriate exhaust ventilation.
<b>Storage</b>	Contents under pressure. The pressure in sealed containers can increase under the influence of heat. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Keep away from food, drink and animal feedingstuffs. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the MSDS). Level 2 Aerosol.

## 8. Exposure Controls / Personal Protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm

**Personal protective equipment**

<b>Eye / face protection</b>	Chemical goggles are recommended.
<b>Skin protection</b>	Wear suitable protective clothing.
<b>Respiratory protection</b>	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
<b>General hygiene considerations</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical & Chemical Properties**

<b>Appearance</b>	Not available.
<b>Auto-ignition temperature</b>	704.76 °F (373.76 °C) estimated
<b>Boiling point</b>	455.64 °F (235.36 °C) estimated
<b>Color</b>	Not available.
<b>Flammability limits in air, upper, % by volume</b>	8.5 % estimated
<b>Flammability limits in air, lower, % by volume</b>	2.1 % estimated
<b>Flash point</b>	-156.00 °F (-104.44 °C) Propellant estimated
<b>Form</b>	Aerosol.
<b>Odor</b>	Not available.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Physical state</b>	Gas.
<b>Solubility (water)</b>	Not available.
<b>Specific gravity</b>	0.784 estimated
<b>Vapor pressure</b>	65 psig @68F estimated
<b>Other data</b>	
<b>Heat of combustion</b>	20.11 kJ/g estimated

**10. Chemical Stability & Reactivity Information**

<b>Chemical stability</b>	Risk of ignition.
<b>Conditions to avoid</b>	Heat, flames and sparks. Avoid temperatures exceeding the flash point.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.

**11. Toxicological Information****Toxicological data**

<b>Product</b>	<b>Species</b>	<b>Test Results</b>
11 OZ FINAL MIST (CAS Mixture)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	4822.6948 mg/l, 2 Hours, estimated
	Rat	9074.5088 mg/l, 15 Minutes, estimated
		4666.6665 mg/l, 4 Hours, estimated
		2193.3333 mg/l/4h, estimated



Components	Species	Test Results
Butane (CAS 106-97-8)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Mouse	680 mg/l, 2 Hours
	Rat	658 mg/l, 4 Hours
Propane (CAS 74-98-6)		
<b>Acute</b>		
<i>Inhalation</i>		
LC50	Rat	> 1442.847 mg/l, 15 Minutes 658 mg/l/4h

\* Estimates for product may be based on additional component data not shown.

<b>Chronic effects</b>	Hazardous by OSHA criteria. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged exposure may cause chronic effects.
<b>Neurological effects</b>	Hazardous by OSHA criteria.
<b>Further information</b>	Symptoms may be delayed.

## 12. Ecological Information

Ecotoxicological data		
Product	Species	Test Results
11 OZ FINAL MIST (CAS Mixture)		
Fish	LC50	Fish
		14321.5 mg/L, 96 Hours, estimated

\* Estimates for product may be based on additional component data not shown.

<b>Ecotoxicity</b>	Contains a substance which causes risk of hazardous effects to the environment.
<b>Environmental effects</b>	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
<b>Persistence and degradability</b>	Not available.

### Bioaccumulation / Accumulation

#### Bioaccumulative potential

##### Octanol/water partition coefficient log Kow

Butane	2.89
Propane	2.36

#### Partition coefficient

Butane	2.89
Propane	2.36

## 13. Disposal Considerations

<b>Waste codes</b>	D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal instructions</b>	Contents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied.

## 14. Transport Information

### DOT

#### Basic shipping requirements:

**UN number** UN1950  
**Proper shipping name** Aerosols, flammable  
**Hazard class** 2.1  
**Special precautions** Read safety instructions, MSDS and emergency procedures before handling.

#### Additional information:

**Special provisions** N82  
**Packaging exceptions** 306  
**Packaging non bulk** None  
**Packaging bulk** None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2013, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/13 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

### IATA

**UN number** UN1950  
**UN proper shipping name** Aerosols, flammable  
**Transport hazard class(es)** 2.1  
**Labels required** 2.1  
**ERG code** 10L  
**Special precautions for user** Read safety instructions, MSDS and emergency procedures before handling.  
**Packaging Exceptions** LTD QTY

### IMDG

**UN number** UN1950  
**UN proper shipping name** AEROSOLS  
**Transport hazard class(es)** 2.1  
**Labels required** None  
**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.  
**Packaging Exceptions** LTD QTY

### DOT



### IATA; IMDG



## 15. Regulatory Information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.





**This data sheet contains  
changes from the previous  
version in section(s):**

Product and Company Identification: Product Review  
Regulatory Information: Canada

---

Product name: 11 OZ FINAL MIST

Product #: 58106 Version #: 02 Revision date: 11-19-2013 Issue date: 11-19-2013

SDS US

7 / 7