
okumental



Printing date 09/26/2018 Re' ad on 09/26/201

#### 1 Identification

- · Product identifier
- · Trade name: WB 70xx Series; xx= 00, 02, 10, 20, 21, 30, 31, 32, 40, 41,50, 60, 61, 80
- · Article number: 100000001389
- · Relevant identified uses of the substance or mixture and uses advised against

Currently no such applications are identified.

Application of the substance / the mixture dry erase whiteboard ink

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: DOKUMENTAL GmbH & Co KG Woellnerstraße 26 D-67065 Ludwigshafen Phone + 49 (0)621/37702 321 Fax + 49 (0)621/37702 391 www.dokumental.de

· Information department:

Technical Service, Dr. B. Polzin
Tel.: +49-621-37702 322
Mobile +49-1726204412
E-Mail: bernd.polzin@dokumental.de

Emergency telephone number:

24-hour-Emergency- Telephone-Number (GBK Contract ID: 94050): (001) 352 323 3500

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

H225 Highly flammable liquid and vapor. Flam. Liq. 2



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS02

GHS07

- · Signal word Danger

· Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation.

Precautionary statements
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use for extinction: CO2, powder or water spray.
Store in a well-ventilated place. Keep cool.

Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2Fire Reactivity = 0

(Contd. of page 1)

### Safety Data Sheet acc. to OSHA HCS



Trade name: MB 70xx Series; xx= 00, 02, 10, 20, 21, 30, 31, 32, 40, 41,50, 60, 61, 80

· HMIS-ratings (scale 0 - 4)

HEALTH 2 3 REACTIVITY 0

Health = 2Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable. vPvB: Not applicable.

#### 3 Composition/information on ingredients

- Chemical characterization: Mixtures
- Mixture of the following substances, containing non-hazardous substances and colouring agents. **Description**: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components: 64-17-5 ethanol 67-63-0 propan-2-ol 50-100% 10-25%

Additional information: For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. **After swallowing**: If symptoms persist consult doctor.
- · After swallowing:
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed
- No further relevant information available
- Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam

- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

# 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Wear protective clothing.

· Environmental precautions:

Prevent seepage into sewage system, workpits and cellars. Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.
Protective Action Criteria for Chemicals

64-17-5	ethanol	1,800 ppm
67-63-0	propan-2-ol	400 ppm
PAC-2:	The state of the s	
64-17-5	ethanol	3300* ppi
67-63-0	propan-2-ol	2000* pp



Page 3/8 Printing date 09/26/2018 Reviewed on 09/26/2018

Trade name: WB 70xx Series: xx= 00, 02, 10, 20, 21, 30, 31, 32, 40, 41,50, 60, 61, 80

		(Contd. of page :
PAC-3:		
64-17-5	ethanol	15000* ppm
67-63-0	propan-2-o1	12000** ppm

### 7 Handling and storage

- · Handling:
- Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat. Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location. · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

- · Storage class: 3
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.

Cont	roi parameters
Comp	onents with limit values that require monitoring at the workplace:
64-1	7-5 ethanol (50-100%)
PEL	Long-term value: 1900 mg/m³, 1000 ppm
REL	Long-term value: 1900 mg/m³, 1000 ppm
TLV	Short-term value: 1880 mg/m³, 1000 ppm
67-6	3-0 propan-2-ol (10-25%)
PEL	Long-term value: 980 mg/m³, 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm BEI

Ingredients with biological limit values:

67-63-0 propan-2-ol (10-25%)

BEI 40 mg/L

Medium: urine

Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If only a short-term loading of the glove material by splashes is expected, tricoted gloves with wearability for the better acceptance of the users are recommended.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks



Page 4/8 Printing date 09/26/2018 Reviewed on 09/26/2018

Trade name: WB 70xx Series; xx= 00, 02, 10, 20, 21, 30, 31, 32, 40, 41,50, 60, 61, 80

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has

to be observed.

· Eye protection:



Tightly sealed goggles

Information on basic physical and chemical pro- General Information	roperties	
General Information Appearance:		
Appearance: Form:	Fluid	
Color:		
	According to product specification Product specific	
Odor: Odor threshold:	Not determined.	
Important information on protection of health		
environment, and on safety.	-	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	78 °C (172.4 °F)	
Flash point:	13 °C (55.4 °F)	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	425 °C (797 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
Explosion limits:		
Lower:	2 Vol %	
Upper:	15 Vol %	
Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)	
Density at 20 °C (68 °F):	0.8 g/cm³ (6.7 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/water):	Not determined.	
Viscosity:		
Dynamic at 20 °C (68 °F):	10 mPas	

Not determined.

specifications.

The physical and chemical properties given in Section 9.1 are rough data only, which are partially derived from the component's data of the mixture. These data are no binding product

80.6 %

6.7 8

# 10 Stability and reactivity

- · Reactivity No further relevant information available.

Kinematic:

· Other information

Organic solvents:

Solids content:

· Solvent content:

· Chemical stability
· Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.

(Contd. on page 5)



Page 5/8 Printing date 09/26/2018 Reviewed on 09/26/2018

Trade name: MB 70xx Series; xx= 00, 02, 10, 20, 21, 30, 31, 32, 40, 41,50, 60, 61, 80

(Contd. of page 4)

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available. · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- Acute toxicity: Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
   Behavior in environmental systems:
- Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

# 13 Disposal considerations

- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

# 14 Transport information

- UN-Number
- DOT, ADR, IMDG, IATA UN1263
- UN proper shipping name
- Paint · ADR 1263 Paint IMDG, IATA PAINT

(Contd. on page 6)



Trade name: WB 70xx Series; xx= 00, 02, 10, 20, 21, 30, 31, 32, 40, 41,50, 60, 61, 80

(Contd. of page 5) · Transport hazard class(es) 3 Flammable liquids · Class Label ADR 3 (F1) Flammable liquids · Class Label IMDG, IATA · Class 3 Flammable liquids · Label · Packing group · DOT, ADR, IMDG, IATA · Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids · Danger code (Kemler): · EMS Number: F-E, S-E· Stowage Category · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: DOT · Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L · ADR · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · IMDG · Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · UN "Model Regulation": UN 1263 PAINT, 3, II

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

All ingredients are listed.

- Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page



Page 7/8 Printing date 09/26/2018 Reviewed on 09/26/2018

Trade name: NB 70xx Series; xx= 00, 02, 10, 20, 21, 30, 31, 32, 40, 41,50, 60, 61, 80

(Contd. of page 6) · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. Chemicals known to cause developmental toxicity: None of the ingredients is listed. · DSL/NDSL (Canada) All ingredients are listed · Cancerogenity categories EPA (Environmental Protection Agency) None of the ingredients is listed. · TLV (Threshold Limit Value established by ACGIH) 64-17-5 ethanol A3 67-63-0 propan-2-ol A4 MAK (German Maximum Workplace Concentration) 64-17-5 ethanol · NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed. GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms





GHS07

- · Signal word Danger
- Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed. Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Technical instructions (air):

Class	Share	in	용
NK	50-3	00	

- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Date of preparation / last revision 09/26/2018 / 12

- Date of preparation / last revision 09/26/2018 / 12

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

UMMIS: Marardone Materials Identification System (USA)



Page 8/8 Printing date 09/26/2018 Reviewed on 09/26/2018

Trade name: WB 70xx Series; xx= 00, 02, 10, 20, 21, 30, 31, 32, 40, 41,50, 60, 61, 80

vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids - Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A