

9738175 9734354 9738176 9738168

# Safety Data Sheet

Material Name: Elmer's Painter's Solid Colors

V# DZReleO

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

### **Material Name**

Elmer's Painter's Solid Colors

# Synonyms

7326, 7327, 7332, 7333, 7334, 7335, 7336, 7337, 7339, 7341, 7343, 7344, 7345, 7347, 7349, 7368, 7369, 7370, 7371, 7372, 7373, 7374, 7382, 7383, 7384, 7385, 7387, 7390, 7391, 7394, 7395, 7396, 7397, 7398, 7399, 7400, 7401, 7402, 7403, 7404, 7405, 7413, 7414, 7415, 7416, 7417, 7418, 7419, 7421, 7426, 7427, 7429, 7431, 7518, 7519, 7520, 7522, 7527, 7528, 7567, 7694, 7695, 7698, 7698W, 7699, 7700, 7701, 7705, 7720, 7721, 7724, 7726, J7343Q, J7345Q, J7389Q, J7522Q, JA7336, JA7339, JA7347, JA7393, JA7583, M7327, M7580, M7583, W7325, W7365, W7367, W7380, W7513CLS, W7523, W7524, W7571, W7571Q, WA7326, WA7327, WA7332, WA7333, WA7337, WA7341, WA7452, WA7518, WA7519, WA7520, WA7521, WA7567

Product Use paint related products

#### **Manufacturer Information**

Elmer's Products, Inc 460 Polaris Parkway, Suite 500 Westerville, OH 43082 USA Phone:1-888-435-6377 Fax:1-800-741-6046 Email:comments@elmers.com

Emergency Phone Number: Poison Control Center 1-888-516-2502

For additional product information, access our website at www.elmers.com. To place an order, call 1-800-848-9400.

### Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200. Specific Target Organ Toxicity - Single Exposure - Category 3 (respiratory tract, central nervous system)

Page 1 of 10

Issue Date: 2014-12-12 Revision 1.0



SDS ID: SDS-57

# GHS Label Elements

Material Name: Elmer's Painter's Solid Colors

. . . . .



Signal Word Warning

# Hazard Statement(s)

May cause respiratory irritation. May cause drowsiness or dizziness

# **Precautionary Statement(s)**

### Prevention

Use only outdoors or in a well-ventilated area Avoid breathing dust/fume/gas/mist/vapours/spray

#### Response

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor if you feel unwell

#### Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up

#### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

# Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
34590-94-8	Dipropylene glycol monomethyl ether	<=2.3
7732-18-5	Water	>=97.7

# Section 4 - FIRST AID MEASURES

### **Description of Necessary Measures**

Call a POISON CENTER or doctor/physician if you feel unwell.

Page 2 of 10

Issue Date: 2014-12-12 Revision 1.0



SDS ID: SDS-57

### Inhalation

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

#### Skin

If on skin, wash immediately with plenty of soap and water. Get medical attention if irritation develops.

### Eyes

Remove contact lenses, if present and easy to do. IMMEDIATELY wash with large amounts of warm water, occasionally lifting upper and lower lids, until no evidence of chemical remains (at least 15-20 minutes). Get medical attention immediately.

#### Ingestion

Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious or convulsive person. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

### Most Important Symptoms/Effects

Material Name: Elmer's Painter's Solid Colors

Acute

May cause respiratory irritation. May cause drowsiness or dizziness.

#### Delayed

no information on significant adverse effects.

### Note to Physicians

For inhalation, consider oxygen.

Section 5 - FIRE FIGHTING MEASURES

# **Extinguishing Media**

Suitable Extinguishing Media Use carbon dioxide, regular dry chemical, regular foam or water. Unsuitable Extinguishing Media None known.

#### Special Hazards Arising from the Chemical Slight fire hazard.

#### Hazardous Combustion Products Oxides of carbon, oxides of nitrogen

# Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

# **Fire Fighting Measures**

Move container from fire area if it can be done without risk. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

Page 3 of 10

Issue Date: 2014-12-12 Revision 1.0



SDS ID: SDS-57

Material Name: Elmer's Painter's Solid Colors

Section 6 - ACCIDENTAL RELEASE MEASURES

### **Personal Precautions, Protective Equipment and Emergency Procedures** Wear personal protective clothing and equipment, see Section 8.

# Methods and Materials for Containment and Cleaning Up

Stop leak if possible without personal risk. Small spills: Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal.

## **Environmental Precautions**

Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

# **Precautions for Safe Handling**

Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapors/spray.

#### **Conditions for Safe Storage, Including any Incompatibilities** Store in a well-ventilated place. Keep container tightly closed

Store locked up

Store in accordance with all current regulations and standards. Protect from freezing. Keep separated from incompatible substances.

# **Incompatible Materials**

oxidizing materials

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

# **Component Exposure Limits**

Dipropylene glycol monomethyl ether	34590-94-8
ACGIH:	100 ppm TWA
	150 ppm STEL
	Skin - potential significant contribution to overall exposure by the cutaneous route
NIOSH:	100 ppmTWA; 600 mg/m3TWA
	150 ppmSTEL; 900 mg/m3STEL
	Potential for dermal absorption

Page 4 of 10

Issue Date: 2014-12-12 Revision 1.0



SDS ID: SDS-57

#### Material Name: Elmer's Painter's Solid Colors

	600 ppmIDLH	
Europe:	50 ppm TWA; 308 mg/m3 TWA	
	Possibility of significant uptake through the skin	
OSHA (US):	100 ppmTWA; 600 mg/m3TWA	
	prevent or reduce skin absorption	
Mexico:	100 ppmTWA LMPE-PPT; 60 mg/m3TWA LMPE-PPT	
	150 ppmSTEL [LMPE-CT]; 900 mg/m3STEL [LMPE-CT]	
	Skin - potential for cutaneous absorption	

### **Biological limit value**

There are no biological limit values for any of this product's components. Engineering Controls Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits. Individual Protection Measures, such as Personal Protective Equipment Eye/face protection Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area. Skin Protection Wear appropriate work clothing. Respiratory Protection Under conditions of frequent use or heavy exposure, respiratory protection may be needed. Glove Recommendations Wear appropriate gloves. Protective Materials protective skin cream.

# Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Colored liquid	Physical State	liquid
Odor	Slight, ammonia odor	Color	Multiple
Odor Threshold	Not available	рН	8-9
Melting Point	Not available	Boiling Point	100 °C
Freezing point	0 °C	Evaporation Rate	<1 (butyl acetate=1)

Page 5 of 10

Issue Date: 2014-12-12 Revision 1.0



### Safety Data Sheet Material Name: Elmer's Painter's Solid Colors

SDS ID: SDS-57

<b>Boiling Point Range</b>	100 °C	Flammability (solid, gas)	Not available
Autoignition	Not available	Flash Point	Not available
Lower Explosive Limit	Not available	Decomposition	Not available
Upper Explosive Limit	Not available	Vapor Pressure	Not available
Vapor Density (air=1)	>1	Specific Gravity (water=1)	0.9 - 1
Water Solubility	Dilutable with water	Partition coefficient: n- octanol/water	Not available
Viscosity	<35 centistokes	Solubility (Other)	Dilutable
Density	8.85 - 11.33 lb/gal	Physical Form	liquid

# Section 10 - STABILITY AND REACTIVITY

Reactivity No hazard expected.

Chemical Stability Stable at normal temperatures and pressure.

**Possibility of Hazardous Reactions** Will not polymerize.

**Conditions to Avoid** Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

Incompatible Materials oxidizing materials

Hazardous decomposition products

Thermal decomposition products oxides of carbon, oxides of nitrogen

Section 11 - TOXICOLOGICAL INFORMATION

### Information on Likely Routes of Exposure

Inhalation May cause respiratory irritation. May cause drowsiness or dizziness. Skin Contact No information on significant adverse effects.

Page 6 of 10

Issue Date: 2014-12-12 Revision 1.0



#### Material Name: Elmer's Painter's Solid Colors

SDS ID: SDS-57

Eye Contact No information on significant adverse effects. Ingestion No information on significant adverse effects.

### Acute and Chronic Toxicity

#### **Component Analysis - LD50/LC50**

The components of this material have been reviewed in various sources and the following selected endpoints are published: Dipropylene glycol monomethyl ether (34590-94-8) Oral LD50Rat 5230 mg/kg Dermal LD50Rabbit 9500 mg/kg Water (7732-18-5) Oral LD50Rat >90 mL/kg

Immediate Effects May cause respiratory irritation. May cause drowsiness or dizziness.

Delayed Effects No information on significant adverse effects.

Irritation/Corrosivity Data May cause respiratory irritation.

Respiratory Sensitization No information available for the product.

**Dermal Sensitization** No information available for the product.

Component Carcinogenicity None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

Germ Cell Mutagenicity No information available for the product.

**Reproductive Toxicity** No information available for the product.

Specific Target Organ Toxicity - Single Exposure respiratory tract, central nervous system

Specific Target Organ Toxicity - Repeated Exposure No target organs identified

Aspiration hazard No information on significant adverse effects.

Medical Conditions Aggravated by Exposure No data available.

Page 7 of 10

Issue Date: 2014-12-12 Revision 1.0



Material Name: Elmer's Painter's Solid Colors

### Section 12 - ECOLOGICAL INFORMATION

Dipropylene glycol monomethyl ether	34590-94-8
Fish:	LC50 96 h Pimephales promelas >10000 mg/L [static

# Section 13 - DISPOSAL CONSIDERATIONS

LC50 48 h Daphnia magna 1919 mg/L IUCLID

### **Disposal Methods**

Invertebrate:

Dispose of contents/container in accordance with local/regional/national/international regulations.

# Section 14 - TRANSPORT INFORMATION

US DOT Information: UN/NA #: Not Regulated

TDG Information: UN#: Not Regulated

IATA Information: UN#: Not Regulated

# Section 15 - REGULATORY INFORMATION

#### **U.S. Federal Regulations**

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Dipropylene glycol monomethyl ether	34590-94-8
SARA 313:	1 % de minimis concentration (applies to R-(OCH2CH2)n-OR', where $n = 1, 2$ , or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl

Page 8 of 10

Issue Date: 2014-12-12 Revision 1.0



SDS ID: SDS-57

Material Name: Elmer's Painter's Solid Colors

C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or Sulfonate, Chemical Category N230) (related to Glycol ethers)

# SARA Section 311/312 (40 CFR 370 Subparts B and C)

### Acute Health: Yes Chronic Health: No Fire: No Pressure: No Reactivity: No

### **U.S. State Regulations**

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Dipropylene glycol monomethyl ether	34590-94-8	Yes	Yes	Yes	Yes	Yes
Water	7732-18-5	No	No	No	No	Yes

#### Not listed under California Proposition 65

#### Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Dipropylene glycol monomethyl ether	34590-94-8
	1%

# **Component Analysis - Inventory**

Dipropylene glycol monomethyl ether (34590-94-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

### Water (7732-18-5)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

# Section 16 - OTHER INFORMATION

#### **NFPA Ratings**

Health: 2 Fire: 1 Reactivity: 0 Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes New SDS: 12/12/2014

Page 9 of 10

Issue Date: 2014-12-12 Revision 1.0



### Safety Data Sheet Material Name: Elmer's Painter's Solid Colors

#### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

#### **Other Information**

Reasonable care has been taken in the preparation of this information; however, the manufacturer makes no warranty whatsoever including the warranty of merchantability, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental, consequential, or other such damages resulting from its use or misuse.

#### **Disclaimer:**

Supplier gives no warranty whatsoever, including the warranties of merchantability or of fitness for a particular purpose. Any product purchased is sold on the assumption the purchaser shall determine the quality and suitability of the product. Supplier expressly disclaims any and all liability for incidental, consequential or any other damages arising out of the use or misuse of this product. No information provided shall be deemed to be a recommendation to use any product in conflict with any existing patent rights.

Page 10 of 10

Issue Date: 2014-12-12 Revision 1.0