

8407

9724807
9730154
9731953
Page 1/8
9735881**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/12/2016

Reviewed on 04/12/2016

V# 0520211

1 Identification**Product Identifier****Trade name:** Earthenware & Stoneware Casting Slip**Product Number:**

SL-IP1 Castables Slip, OCSSLIP John's Low Fire Slip Cone 06-02, SLE01 Mayco Low Fire White Casting Slip, SLS01 Mayco Stoneware White Casting Slip, AC-306 Clay Mender

Relevant identified uses of the substance or mixture and uses advised against:

Casting slip for use with casting molds in the production of ceramic ware.

Product Description

Casting slip is a suspension of clay and other materials in water, used in the production of low-fire, ceramic ware.

Details of the Supplier of the Safety Data Sheet:**Manufacturer/Supplier:**Coloramics, LLC (D.B.A. Mayco Colors)
4077 Weaver Court South
Hilliard, Ohio 43026
United States of America
(614) 876-1171**Emergency telephone number:** In case of emergency contact your Regional or Local Poison Control Center**2 Hazard(s) Identification****Classification of the substance or mixture:**

The product does not need classification according to OSHA HazCom Standard 29 CFR paragraph (d) of §1910.1200(g) and GHS Rev 03.

Label elements:**GHS label elements:** Non-Regulated Material**Hazard pictograms:** Non-Regulated Material**Signal word:** Non-Regulated Material**Hazard statements:** Non-Regulated Material**Unknown acute toxicity:**

61 % of the mixture consists of component(s) of unknown toxicity.

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 0

Fire = 0

Reactivity = 0

HMIS-ratings (scale 0 - 4)

HEALTH 0 Health = 0

FIRE 0 Fire = 0

REACTIVITY 0 Reactivity = 0

Hazard(s) not otherwise classified (HNOC): None known**3 Composition/Information on Ingredients****Chemical characterization: Mixtures****Description:** Mixture of substances listed below with non-hazardous additions.

(Contd. on page 2)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/12/2016

Reviewed on 04/12/2016

Trade name: Earthenware & Stoneware Casting Slip**Dangerous Components:**

CAS: 1332-58-7	Kaolin	25-50%
CAS: 14807-96-6 RTECS: WW2710000	Talc (Mg ₃ H ₂ (SiO ₃) ₄) not containing asbestos or asbestiform fibres	25-50%
CAS: 471-34-1 RTECS: EV 9580000	Calcium Carbonate Eye Irrit. 2B, H320	5-10%
CAS: 37244-96-5	Nepheline Syenite ⚠ STOT SE 3, H335	5-10%

4 First-Aid Measures**Description of first aid measures:****General information:** No special measures required.**After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:** Generally the product does not irritate the skin.**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** If swallowed and symptoms occur, consult a doctor.**Information for doctor:****Most important symptoms and effects, both acute and delayed:**

Kaolin: Prolonged inhalation of excessive levels of kaolin may cause a benign pneumoconiotic condition, not normally associated with a decrement in lung function. In cases of long-term exposure to extremely high levels of dust, progressive fibrosis may occur with lung function impairment.

Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5 Fire-Fighting Measures**Extinguishing media:****Suitable extinguishing agents:**CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**Special hazards arising from the substance or mixture:** No further relevant information available.**Advice for firefighters:****Protective equipment:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

6 Accidental Release Measures**Personal precautions, protective equipment and emergency procedures:** Not required.**Environmental precautions:** Do not allow to enter sewers/surface or ground water.**Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (i.e. sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the collected material according to regulations.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage**Handling****Precautions for safe handling:** No special measures required.**Information about protection against explosions and fires:** No special measures required.

(Contd. on page 3)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/12/2016

Reviewed on 04/12/2016

Trade name: Earthenware & Stoneware Casting Slip

- **Conditions for safe storage, including any incompatibilities:**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Store in the original container.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s):** No further relevant information available.

8 Exposure Controls/Personal Protection

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters:**

- **Components with occupational exposure limits:**

1332-58-7 Kaolin

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 2* mg/m ³ E; as respirable fraction

14807-96-6 Talc (Mg₃H₂(SiO₃)₄) not containing asbestos or asbestiform fibres

PEL	Long-term value: 20 mppcf ppm (containing <1% Quartz)
REL	Long-term value: 2* mg/m ³ *respirable dust
TLV	Long-term value: 2* mg/m ³ *as respirable fraction; E

471-34-1 Calcium Carbonate

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	TLV withdrawn

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

- **Exposure controls:**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

The usual precautionary measures for handling chemicals should be followed.

- **Breathing equipment:** Not required.

- **Protection of hands:** Not required.

- **Material of gloves:** Not required.

- **Penetration time of glove material:** Not applicable.

- **Eye protection:**



Safety glasses recommended.

(Contd. on page 4)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/12/2016

Reviewed on 04/12/2016

Trade name: Earthenware & Stoneware Casting Slip**9 Physical and Chemical Properties****· Information on basic physical and chemical properties****· General Information****· Appearance:**

Form: Liquid
Color: Light grey
Odor: Earthy
Odor threshold: Not determined.

· pH-value: Acidic

· Change in condition

Melting point/Melting range: Not determined.
Boiling point/Boiling range: 100 °C (212 °F)

· Flash point: None

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

· Auto igniting: Product is not self-igniting.

· Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower: 0.0 Vol %
Upper: 0.0 Vol %

· Vapor pressure @ 20 °C (68 °F): 23 hPa (17 mm Hg)

· Density:

Relative density: Not determined.
Vapor density: Not determined.
Evaporation rate: Not determined.

· Solubility in / Miscibility with:

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined.
Kinematic: Not determined.

· Solvent content:

Organic solvents: 0.0 %

· Other information: No further relevant information available.

10 Stability and Reactivity

· Reactivity: No further relevant information available.

· Chemical stability: Stable under normal conditions.

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions: No dangerous reactions known.

· Conditions to avoid: No further relevant information available.

· Incompatible materials: No further relevant information available.

(Contd. on page 5)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/12/2016

Reviewed on 04/12/2016

Trade name: Earthenware & Stoneware Casting Slip

- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information

- **Information on toxicological effects:**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

471-34-1 Calcium Carbonate

Oral LD50 6450 mg/kg (rat)

- **Primary irritant effect:**

- **On the skin:** No irritating effect.

- **On the eye:** No irritating effect.

- **Additional toxicological information:**

The product is not subject to classification according to internally approved calculation methods for preparations.

When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

- **Carcinogenic categories:**

- **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

- **NTP (National Toxicology Program):**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

12 Ecological Information

- **Toxicity:**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

- **Additional ecological information:**

- **General notes:** Not known to be hazardous to water.

- **Results of PBT and vPvB assessment:**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects:** No further relevant information available.

13 Disposal Considerations

- **Waste treatment methods:**

- **Recommendation:**

Observe all federal, state and local environmental regulations when disposing of this material.
Smaller quantities can be disposed of with household waste.

- **Uncleaned packagings**

- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 6)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/12/2016

Reviewed on 04/12/2016

Trade name: Earthenware & Stoneware Casting Slip**14 Transport Information**

- **UN-Number:**
- **DOT, ADR, ADN, IMDG, IATA** Non-Regulated Material
- **UN proper shipping name:**
- **DOT, ADR, ADN, IMDG, IATA** Non-Regulated Material
- **Transport hazard class(es):**
- **DOT, ADR, ADN, IMDG, IATA**
- **Class:** Non-Regulated Material
- **Packing group:**
- **DOT, ADR, IMDG, IATA** Non-Regulated Material
- **Environmental hazards:** Not applicable.
- **Special precautions for user:** Not applicable.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.
- **UN "Model Regulation":** Non-Regulated Material

15 Regulatory Information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture:**
- **SARA (Superfund Amendments and Reauthorization):**

• **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

• **Section 313 (Specific toxic chemical listings):**

513-77-9 Barium carbonate

• **TSCA (Toxic Substances Control Act):**

1332-58-7 Kaolin

14807-96-6 Talc (Mg₃H₂(SiO₃)₄) not containing asbestos or asbestiform fibres

471-34-1 Calcium Carbonate

497-19-8 Sodium carbonate

9003-04-7 2-Propenoic acid, homopolymer sodium salt

513-77-9 Barium carbonate

1344-09-8 Silicic acid, sodium salt

7732-18-5 Water, distilled water, deionized water

• **California Proposition 65:**• **Chemicals known to cause cancer:**

None of the ingredients are listed.

• **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

• **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

• **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

• **New Jersey Right-to-Know List:**

None of the ingredients are listed.

(Contd. on page 7)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/12/2016

Reviewed on 04/12/2016

Trade name: Earthenware & Stoneware Casting Slip

• New Jersey Special Hazardous Substance List:		
None of the ingredients are listed.		
• Pennsylvania Right-to-Know List:		
None of the ingredients are listed.		
• Pennsylvania Special Hazardous Substance List:		
None of the ingredients are listed.		
• Carcinogenic categories:		
• EPA (Environmental Protection Agency):		
513-77-9 Barium carbonate		D, CBD(inh), NL(oral)
• TLV (Threshold Limit Value established by ACGIH):		
1332-58-7 Kaolin		2 mg/m3
14807-96-6 Talc (Mg3H2(SiO3)4) not containing asbestos or asbestiform fibres		A4
513-77-9 Barium carbonate		A4
• NIOSH-Ca (National Institute for Occupational Safety and Health):		
None of the ingredients are listed.		
• GHS label elements Non-Regulated Material		
• Hazard pictograms: Non-Regulated Material		
• Signal word: Non-Regulated Material		
• Hazard statements: Non-Regulated Material		
• National regulations:		
The product is subject to be classified according with the latest version of the regulations on hazardous substances.		
• Chemical safety assessment: A Chemical Safety Assessment has not been carried out.		

16 Other Information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

• **Date of preparation / last revision:** 04/12/2016 / 3

• **Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit

(Contd. on page 8)

Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 04/12/2016

Reviewed on 04/12/2016

Trade name: Earthenware & Stoneware Casting Slip

BEI: Biological Exposure Limit

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

· *** Data compared to the previous version altered.**

SDS created by MSDS Authoring Services www.msdsauthoring.com +1-877-204-9106