

SAFETY DATA SHEET Asia Pacific GHS Format

Print date: 15-Jan-2013 Revision Number: 10 Revision date: 15-Jan-2013

1. IDENTIFICATION OF THE SUBSTANCE AND COMPANY

Trademark:

SABIC® LDPE

Product Code:

HP4024W-00900

Product Description:

Polyethylene [CASRN 9002-88-4]

Product Type:

Commercial Product

Recommended use:

May be used to produce molded or extruded articles or as a component of other industrial

products.

Company:

SABIC Asia Pacific PTE Ltd. One Temasek Avenue #06-01 Millenia Tower 039192, Singapore

SABIC (Shanghai) Trading Co. Ltd.

Suite 2106, Jin Mao Tower 88 Century Boulevard Pudong New Area Shanghai 200121, China

Manufacturer:

SABIC

P.O. Box 5101

Riyadh 11422 Saudi Arabia

Emergency Telephone Number:

+65 6557 2555 extension 200 (Singapore)

+86-532-83889090 (24h) (China)

Emergency

800 424-9300 (USA)

Transportation/CHEMTREC

+1 703-527-3887 (globally, outside USA)

(24 HOUR):

E-mail:

sappl@sabic.com.sg

Website Address:

www.sabic.com

2. HAZARDS IDENTIFICATION

The additives in this product are bound in a thermoplastic resin matrix. In accordance with GHS for the classification of the product, the hazard potential may be assessed with respect to the physico-chemical form and/or bioavailability of the individual components in the thermoplastic resin.

Where GHS classifications are shown below, these are based on the individual components in the thermoplastic resin matrix. Under the typical use conditions for the resin, these hazardous components are unlikely to contribute to workplace exposure. Please read the entire safety data sheet and/or consult an EHS professional for a complete understanding.

Globally Harmonized System, UN(GHS) - Classification

Product Name: HP4024W-00900

Page 1 of 7



GHS Category

Not hazardous

· Not classified

GHS-Labeling

GHS Labeling not required

Precautionary Statements

No GHS specific Precautionary Statements required - observe all other warnings and handling instructions in this SDS.

Other hazards which do not result in classification:

SABIC Emergency Overview

- · Granules with slight or no odor
- · Spilled material may create slipping hazard
- · Can burn in a fire creating dense, toxic smoke
- · Molten plastic can cause severe thermal burns
- Fumes produced during melt processing may cause eye, skin, and respiratory tract irritation. Severe over-exposure may result in nausea, headache, chills, and fever. See below for additional effects.
- Secondary operations, such as grinding, sanding, or sawing can produce dust which may present an explosion or respiratory hazard.

Other Information:

Cool skin rapidly with cold water after contact with molten material. Heating can release hazardous gases. Hazardous fumes can also occur in post-processing operations.

Processing Issues:

Processing vapors may cause irritation to the eyes, skin, and respiratory tract. In cases of severe exposure, nausea and headache can also occur. Grease-like processing vapor condensates on ventilation ductwork, molds, and other surfaces can cause irritation and injury to skin.

Aggravated Medical Conditions:

MEDICAL RESTRICTIONS: There are no known health effects aggravated by exposure to this product. However, certain sensitive individuals and individuals with respiratory impairments may be affected by exposure to components in the processing vapors.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product consists primarily of high molecular weight polymers which are not expected to be hazardous. The ingredients in this product are present within the polymer matrix and are not expected to be hazardous.

4. FIRST AID MEASURES

If Inhalation:

Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. If symptoms persist, call a physician.

On skin contact:

Immediately cool the skin by rinsing with cold water after contact with hot material. Wash off immediately with soap and plenty of water. Consult a physician.

On contact with eyes:

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If eye imitation persists, consult a specialist.

On ingestion:

No hazards which require special first aid measures.

Product Name: HP4024W-00900

Page 2 of 7



Precautions:

Cool molten product on skin with plenty of water. Do not remove solidified product. Do not peel

polymer from the skin.

5. FIRE-FIGHTING MEASURES

Autoignition Temperature:

>300°C

Suitable Extinguishing Media:

Use dry chemical, CO2, water spray or "alcohol" foam. Water is the best extinguishing medium. Carbon dioxide and dry chemical are not generally recommended because their lack

of cooling capacity may permit re-ignition on larger resin fires (blobs, drools, etc.).

Unsuitable Extinguishing Media for Safety Reasons: Do not use a solid water stream as it may scatter and spread fire.

Hazards from Combustion

Products:

Fire will produce dense black smoke containing hazardous combustion products, carbon

oxides, hydrocarbon fragments.

Specific Hazards:

Take precautionary measures against static discharges. During processing, dust may form explosive mixture in air. Thermal decomposition can lead to release of irritating gases and

vapors.

Special Protective Equipment

for Firefighters:

Exposure hazards:

In the event of fire, wear self-contained breathing apparatus (EU: NEN-EN137).

Do not release chemically contaminated water into drains, soil or surface water. Sufficient

measures must be taken to retain the water used for extinguishing. Dispose of contaminated water and soil according to local regulations.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:

See section 8. If spilled, take caution, as material can cause surfaces to become very slippery.

Environmental Precautions:

Do not flush into surface water or sanitary sewer system. Material should not be released into

the environment.

Clean up:

Sweep up and shovel into suitable containers for disposal. Do not create a powder cloud by using a brush or compressed air.

7. HANDLING AND STORAGE

Handling:

Handle in accordance with good industrial hygiene and safety practices Provide for appropriate exhaust ventilation and dust collection at machinery Minimize dust generation and accumulation. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical

grounding and bonding, or inert atmospheres

Storage:

Store in a dry and cool area. Keep away from heat sources and sources of ignition. Keep away

from direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION


Exposure limits:

No components with information, unless noted below

*SABIC Recommended Exposure Limits have been established for certain chemicals.

Product Name: HP4024W-00900

Page 3 of 7



Engineering Measures to

Reduce Exposure:

In the case of hazardous fumes, wear self-contained breathing apparatus. Wear face-shield and protective suit for abnormal processing problems. Handle in accordance with good

industrial hygiene and safety practice. Provide for appropriate exhaust ventilation at machinery.

Hand Protection:

Protective gloves should be worn, (EU: NEN-EN 374), When handling hot material, wear heat-

resistant protective gloves that are able to withstand the temperature of molton resin

Eye Protection:

Safety glasses with side-shields. (EU: NEN-EN 165-166).

Respiratory Protection:

In the case of hazardous furnes, wear self contained breathing apparatus. In case of

insufficient ventilation wear suitable respiratory equipment. (EU: NEN-EN149).

Body Protection:

Long sleeved clothing (EU: NEN-EN 340-369-465).

Hygiene Measures:

When using, do not eat, drink or smoke.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:

Appearance:

Solid

Granules

Color: Odor:

Same es color code

Characteristic

Melting point/range:

104-120°C

Boiling point/range: Flash Point:

decomposition starting from 300°C Not applicable

Evaporation Rate:

Negligible

Explosive Limits

Not determined

lower:

Not determined

Vapor Pressure:

Negligible 0.91-0.93 g/cm3

Density:

Insoluble

Water Solubility: **Autoignition Temperature:**

upper:

Explosive Properties:

>300°C Dust may form explosive mixture in air

Oxidising Properties: VOC content (%):

Not oxidising Negligible

10. STABILITY AND REACTIVITY

Stability:

Stable under ambient conditions. Hazardous polymerisation does

not occur.

Polymerization:

Hazardous polymerization does not occur.

Conditions to Avoid:

Avoid temperatures above 300°C. Heating can result in the formation of gaseous decomposition products, some of which may be hazardous. Do not exceed melt temperature recommendations in product literature. Purgings of hot material should be collected in small, flat, thin shapes and quenched with water to allow for rapid cooling. Do not allow product to remain in barrel at elevated

temperatures for extended periods of time.

Hazardous Decomposition Products:

Process vapors under recommended processing conditions may

include trace levels of hydrocarbons, carbon oxides.

Product Name: HP4024W-00900

Page 4 of 7



11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information:

LD50/oral/rat: LD50/dermal/rabbit: >5000 mg/kg

>2000 mg/kg

Component Information:

Component Information Text:

No data available

Sensitization

Respiratory Sensitization:

Not classified

Irritation:

Eye Irritation:

no data available

Subchronic Toxicity (28 days)
Repeated Oral Toxicity(28d): Repeated Dermal Toxicity(28d):

No information available No Information available

Subchronic Toxicity:

No information available

Chronic Toxicity

Carcinogenicity:

There are no known carcinogenic chemicals in this product except

specifically mentioned below.

Mutagenic Effects: Reproductive Toxicity: Developmental Toxicity:

No data is available on the product itself

No information available No information available

Neurological effects:

No information available

Specific Target Organ Toxicity(STOT)

Target Organ Effects:

Not established

Aspiration Hazard

Aspiration Hazard Statement:

No data available

Other relevant toxicity information

Remarks:

The toxicological data has been taken from products of similar

composition.

Special Studies:

No Information

12. ECOLOGICAL INFORMATION

Ecotoxicity Effects:

Ecological damages are not known or expected under normal use. Small particles can have an effect on water and soil organisms.

13. DISPOSAL CONSIDERATIONS

Product Name: HP4024W-00900

Page 5 of 7



Revision date: 15-Jan-2013

products:

Waste from residues / unused Where possible recycling is preferred to disposal or incineration. Dispose of in accordance with

Contaminated Packaging:

Empty containers should be transported/delivered using a registered waste carrier for local

recycling or waste disposal.

Waste Disposal:

Recycling is encouraged. Landfill or incinerate in accordance with federal, state and local requirements. Collected processing fume condensates and incinerator ash should be tested to

determine waste classification.

14. TRANSPORT INFORMATION

IMO / IMDG

Not regulated

ICAO

Not regulated

IATA-DGR

Not regulated

DOT

Not regulated

ADR/RID

Not regulated

ADR

Not regulated

ADN

Not regulated

15. REGULATORY INFORMATION

Further regulatory information can be requested via your local sales office.



16. OTHER INFORMATION

SABIC® LDPE is a registered trademark of Saudi Basic Industries Corporation

SDS Scope:

Singapore: Conforms to Singapore workplace Safety and Health (WSH) Act, WSH Regulations, and GHS Standard 586 China: Conforms to Chinese Regulation on the Control over Safety of Hazardous Chemicals (Decree No 591) and GHS standards GB15258,GB13698,GB/T16483 etc.

Japan: Conforms to Industrial Safety and Health Law, Japan (2006) and Industrial GHS Standards JIS Z7250, JIS Z7251

Korea: Conforms to Industrial Safety & Health Act, Ministry of Labor, Korea

Taiwan: Conforms to Taiwan Rules on Hazard Communication and Labeling of Hazardous Substances, (Council of Labor Affairs, Taiwan) and GHS standards Z1051

Thailand: Conforms to Notification of the Ministry of Industry on the System of Classification and Hazard Communication of Hazardous Substances B.E. 2555 (2012)

This document is also applicable in other countries and regions.

Prepared by:

Product Stewardship & Toxicology

DISCLAIMER: The information contained in the Safety Data Sheet is at the date of its issuance to the best of our knowledge correct according to the data available to us. The information is meant as a guideline for safe use, handling, disposal, storage and transport of products and does not imply any warranty (not implied nor explicitly) or specification. The Supplier shall to the extent permitted by law not be liable for any error or incorrectness in the information contained in this Safety Data Sheet. The information relates exclusively to the specified products, which may not be suitable for combination with other materials or use in processes other than those specifically described here.

End of Safety Data Sheet

Product Name: HP4024W-00900 Page 7 of 7 Revision date: 15-Jan-2013