
WA25085 V#084660



(

SAFETY DATA SHEET

Issuing Date No data available

Revision Date 20-Jan-2015

Revision Number 1

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name	TIANQIU Carbon Zinc battery R03/AAA (No lead added)
Other means of identification	
Synonyms	None
Recommended use of the cher	nical and restrictions on use
Recommended Use	Carbon Zinc Battery
Uses advised against	No information available
Details of the supplier of the sa	fety data sheet
Supplier Name	GUANGZHOU TIANQIU ENTERPRISE CO., LTD.
Supplier Address	9/F TianQiu Building No.16-30, He Yi Rd., San Yuan Li Ave., GuangZhou China
	GUANGZHOU
	GUANDONG
	510410
	CN
Supplier Phone Number	Phone:13825131170
	Fax:8620-36323339
	Contact Phone:8620-36322277
	gd@gztiangiu.com
Supplier Email	qu@gztanqu.com



Page 1/20

2. HAZARDS IDENTIFICATION

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4	
Acute toxicity - Inhalation (Gases)	Category 4	
Acute toxicity - Inhalation (Dusts/Mists)	Category 4	
Skin corrosion/irritation	Category 1 Sub-category B	
Serious eye damage/eye irritation	Category 1	
Carcinogenicity	Category 2	
Specific target organ toxicity (repeated exposure)	Category 2	

GHS Label elements, including precautionary statements

		Emergency Ov	verview	
Signal word	Dan	ger		
Hazard Stater	nents			
Harmful if swa	llowed			
Harmful if inha	aled			
Causes sever	e skin burns and eye damage			
Suspected of	causing cancer			
May cause da	mage to organs through prolo	nged or repeated exposur	re	
			afety information is given for expos	
		above hazards		
Appearance	No data available	Physical State	Solid	Odor Odorles



Page 2/20

Revision Date 20-Jan-2015

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area Do not breathe dust/fume/gas/mist/vapors/spray

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a POISON CENTER or doctor/physician

Skin

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell Immediately call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Rinse mouth Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable



Page 3/20

Unknown Toxicity

,

.

17.48% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Very toxic to aquatic life with long lasting effects

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Zinc	7440-66-6	15 - 40	*
Manganese dioxide	1313-13-9	10 - 30	
Graphite	7782-42-5	3 - 7	*
Zinc chloride	7646-85-7	3 - 7	
Iron	7439-89-6	1 - 5	*
Carbon black	1333-86-4	1 - 5	
PVC (Chloroethylene, polymer)	9002-86-2	1-5	

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice	First aid is upon rupture of sealed battery.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention/advice.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Seek immediate medical attention/advice.



Page 4/20

Inhalation	Permove to freeh air. If breathing has stopped, give artificial respiration. Get		
Innalauon	Remove to fresh air. If breathing has stopped, give artificial respiration. Get		
	medical attention immediately. Do not use mouth-to-mouth method if victim		
	ingested or inhaled the substance; give artificial respiration with the aid of a pocket		
	mask equipped with a one-way valve or other proper respiratory medical device. If		
	breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary		
	edema may occur. Get medical attention immediately if symptoms occur.		
Ingestion	Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water.		
	Never give anything by mouth to an unconscious person. Call a physician or		
	poison control center immediately.		
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved, take		
	precautions to protect themselves and prevent spread of contamination. Avoid		
	contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to		
	give mouth-to-mouth resuscitation. Use personal protective equipment as		
	required. Wear personal protective clothing (see section 8).		
Most important symptoms and el	fects, both acute and delayed		
Most Important Symptoms and Effects	Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.		
Indication of any immediate med	ical attention and special treatment needed		
Notes to Physician	Product is a corrosive material. Use of gastric lavage or emesis is		
notes to r nysician	contraindicated. Possible perforation of stomach or esophagus should be		
	investigated. Do not give chemical antidotes. Asphyxia from glottal edema may		
	occur. Marked decrease in blood pressure may occur with moist rales, frothy		
	sputum, and high pulse pressure.		

9

Page 5/20

Revision Date 20-Jan-2015

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

Uniform Fire Code	Corrosive: OtherSolid
	Toxic: Solid
	Oxidizer: Class 1Solid
Hazardous Combustion Products	
Carbon oxides.	
Physical/Chemical Reaction	No data available.
Properties	
Explosion Data	
Sensitivity to Mechanical Impact	No.
Sensitivity to Static Discharge	No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.



Page 6/20

.

.

.

6. ACCIDENTAL RELEASE MEASURES Personal precautions, protective equipment and emergency procedures		
Other Information	Refer to protective measures listed in Sections 7 and 8.	
Environmental Precautions		
Environmental Precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Should not be released into the environment. Do not allow to enter into soil/subsoil. Prevent product from entering drains.	
Methods and material for contain	ment and cleaning up	
Methods for Containment	Prevent further leakage or spillage if safe to do so.	
Methods for cleaning up	Pick up and transfer to properly labeled containers.	

9

Page 7/20

7. HANDLING AND STORAGE				
Precautions for safe handling				
Handling Conditions for safe storage, inc	In case of rupture: Handle in accordance with good industrial hygiene and safety practice Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Use only with adequate ventilation and in closed systems. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Do not breathe dust. Avoid generation of dust.			
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.			
Incompatible Products	Acids, Bases, Oxidizing agent.			

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

4

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Zinc 7440-66-6	STEL: 10 mg/m ³ respirable fraction TWA: 2 mg/m ³ respirable fraction	TWA: 5 mg/m ³ fume TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	IDLH: 500 mg/m ³ Ceiling: 15 mg/m ³ dust TWA: 5 mg/m ³ dust and fume STEL: 10 mg/m ³ fume
Manganese dioxide 1313-13-9	TWA: 0.02 mg/m³ Mn TWA: 0.1 mg/m³ Mn	(vacated) Ceiling: 5 mg/m³ Ceiling: 5 mg/m³ Mn	IDLH: 500 mg/m ³ Mn TWA: 1 mg/m ³ Mn STEL: 3 mg/m ³ Mn

9

Page 8/20

Revision Date 20-Jan-2015

Graphite 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
Zinc chloride 7646-85-7	STEL: 2 mg/m ³ fume TWA: 1 mg/m ³ fume	TWA: 1 mg/m ³ fume (vacated) TWA: 1 mg/m ³ fume (vacated) STEL: 2 mg/m ³ fume	IDLH: 50 mg/m ³ fume TWA: 1 mg/m ³ fume STEL: 2 mg/m ³ fume
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction		IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
PVC (Chloroethylene, polymer) 9002-86-2	TWA: 1 mg/m ³ respirable fraction	-	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d
	962 (11th Cir., 1992) See section 15 for national exposure control parameters
Appropriate engineering controls	
Engineering Measures	Showers
	Eyewash stations
	Ventilation systems
Individual protection measures, s	such as personal protective equipment If there is a risk of contact:. Face protection shield.
Skin and Body Protection	Wear protective gloves and protective clothing. Long sleeved clothing. Chemical resistant apron. Impervious gloves.
Respiratory Protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

9

Page 9/20

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use. Do not breathe dust.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State	Solid		
Appearanca	No data available	Odor	Odorless
Color	No information available	Odor Threshold	No information available
Property	Values	Remarks Method	
рН	No data available	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	Negligible	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing Properties	No data available		



Page 10/20

Revision Date 20-Jan-2015

Other Information

Softening Point VOC Content (%) Particle Size Particle Size Distribution

No data available No data available No data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability Stable under recommended storage conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid Exposure to air or moisture over prolonged periods. Excessive heat.

Incompatible materials Acids. Bases. Oxidizing agent.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:.

(4)

Page 11/20

Inhalation	Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive furnes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal. May cause irritation of respiratory tract. Harmful by inhalation.
Eye Contact	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Corrosive to the eyes and may cause severe damage including blindness. Causes serious eye damage. May cause irreversible damage to eyes.
Skin Contact	Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns.
Ingestion	Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Manganese dioxide 1313-13-9	= 9000 mg/kg (Rat)		•
Graphite 7782-42-5	> 10000 mg/kg (Rat)	·	
Zinc chloride 7646-85-7	= 350 mg/kg (Rat)	-	
Iron 7439-89-6	= 984 mg/kg (Rat)	•	•
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	•

Information on toxicological effects



Page 12/20

```
Symptoms
```

Erythema (skin redness). Burning. May cause blindness. Coughing and/ or wheezing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

No information available.

No information available.

Sensitization

Mutagenic Effects

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Carbon black 1333-86-4	A3	Group 2B		×
PVC (Chloroethylene, polymer)		Group 3		
9002-86-2				

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).
Chronic Toxicity	Chronic exposure to corrosive fumes/gases may cause erosion of the teeth followed by jaw necrosis. Bronchial irritation with chronic cough and frequent attacks of pneumonia are common. Gastrointestinal disturbances may also be seen. Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. Carbon black has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation.

9

Page 13/20

 Target Organ Effects
 Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Blood. Central Nervous System (CNS). Central Vascular System (CVS). Kidney. Lymphatic System. Cardiovascular system. Liver. Lungs. Pancreas.

Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 1,190.00 mg/kg ATEmix (inhalation-gas) 14,873.00 ppm (4 hr) ATEmix (inhalation-dust/mist) 4.96 mg/l ATEmix (inhalation-vapor) 36.36 ATEmix



Page 14/20

12. ECOLOGICAL INFORMATION

This product contains a chemical which, although not listed, meets the IMDG criteria for being a severe marine pollutant

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flee
Zinc 7440-66-6	96h EC50: 0.11 - 0.271 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.09 - 0.125 mg/L (Pseudokirchneriella subcapitata)	 96h LC50: 2.16 - 3.05 mg/L (Pimephales promelas) 96h LC50: 0.211 - 0.269 mg/L (Pimephales promelas) 96h LC50: = 2.66 mg/L (Pimephales promelas) 96h LC50: = 30 mg/L (Cyprinus carpio) 96h LC50: = 0.45 mg/L (Cyprinus carpio) 96h LC50: = 7.8 mg/L (Cyprinus carpio) 96h LC50: = 3.5 mg/L (Lepomis macrochirus) 96h LC50: = 0.24 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.59 mg/L (Oncorhynchus mykiss) 96h LC50: = 0.41 mg/L (Oncorhynchus mykiss) 		48h EC50: 0.139 - 0.908 mg/L
Iron 7439-89-6		96h LC50: = 13.6 mg/L (Morone saxatilis)		
Carbon black 1333-86-4				24h EC50: > 5600 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Manganese dioxide	<0
1313-13-9	

Other adverse effects

No information available.



Page 15/20

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

 Disposal methods
 This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

 Contaminated Packaging
 Dispose of contents/containers in accordance with local regulations.

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Zinc	Ignitable powder Toxic
7440-66-6	
Zinc chloride	Toxic
7646-85-7	Corrosive

14. TRANSPORT INFORMATION

DOT	NOT REGULATED
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
Marine Pollutant	This product contains a chemical which, although not listed, meets the IMDG criteria for
	being a severe marine pollutant
TDG	Not regulated
MEX	Not regulated
ICAO	Not regulated
IATA	Not regulated
Proper Shipping Name	NON REGULATED

(4)

Page 16/20

Revision Date 20-Jan-2015

Hazard Class	N/A
IMDG/IMO	Not regulated
Hazard Class	N/A
Marine Pollutant	Product is a marine pollutant according to the criteria set by IMDG/IMO
RID	Not regulated
ADR	Not regulated
ADN	Not regulated
	15. REGULATORY INFORMATION
International Inventories	
TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Zinc - 7440-66-6	7440-66-6	15 - 40	1.0
Manganese dioxide - 1313-13-9	1313-13-9	10 - 30	1.0
Zinc chloride - 7646-85-7	7646-85-7	3-7	1.0
SARA 311/312 Hazard Categories			
Acute Health Hazard	No		
Chronic Health Hazard	No		
Fire Hazard	No		
Outline of a second second	No		
Sudden release of pressure hazard	No		



Page 17/20

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollulants	CWA - Hazardous Substances
Zinc 7440-66-6		x	x	
Zinc chloride 7646-85-7	1000 lb	x		x

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ	
Zinc 7440-66-6	1000 lb		RQ 454 kg final RQ RQ 1000 lb final RC	
Zinc chloride 7646-85-7	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ	

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65			
Carbon black - 1333-86-4	Carcinogen			

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois	
Zinc	x	x	x	×		
7440-66-6						
Manganese dioxide			х	×	×	
1313-13-9						
Graphite	×	x	×			
7782-42-5						
Zinc chloride	x	x	×	x		
7646-85-7						
Carbon black	x	x	x		x	
1333-86-4		-				



Page 18/20

Revision Date 20-Jan-2015

PVC (Chloroethylene, polymer)	X	
9002-86-2		

International Regulations

Mexico

. .

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits		
Manganese dioxide		Mexico: TWA= 0.2 mg/m ³		
1313-13-9 (10 - 30)				
Graphite		Mexico: TWA= 2 mg/m ³		
7782-42-5 (3 - 7)				
Zinc chloride		Mexico: TWA 1 mg/m ³		
7646-85-7 (3 - 7)		Mexico: STEL 2 mg/m ³		
Carbon black		Mexico: TWA 3.5 mg/m ³		
1333-86-4 (1-5)		Mexico: STEL 7 mg/m ³		

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Non-controlled

		16	OTHER INF	ORM	ATION		
NFPA	Health Hazards	2	Flammability	0	Instability 0		Physical and Chemica Hazards -
HMIS	Health Hazards	0	Flammability	0	Physical Hazard	0	Personal Protection
Prepared By	Prod	uct S	stewardship				
	23 B	ritish	American Blvd.				
	Latha	am, I	NY 12110				
	1-80	0-57	2-6501				
Revision Date	20-Jan-2015						
Revision Note	No in	form	ation available				



Page 19/20

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet



Page 20/20