

SB33552

V# 084660

8718



PAK KO BATTERIES FACTORY LIMITED



Unit 11, 9/F., Block A, Hoi Luen Ind. Ctr., No. 55 Hoi Yuen Rd., Kwun Tong, Kln., H.K.
 Tel.: (852) 2345-5245 Fax.: (852) 2797-9591 E-mail: pakko@pakkobatteries.com
 http://www.pakkobatteries.com

Approval Date:

1 Mar 2016

Page:

1 Of 4

No.: PKSDSL1154C

Safety Data Sheet

Mercury Free Alkaline Manganese Button Cell

Specification : 0% Mercury Content Data

Model No. Pak Ko L1154C / AG 13 / LR44

Weight: 1.95g

Section1 : Information of Manufacturer

Pak Ko Batteries Factory Limited

Rm 911, Blk A, Hoi Luen Ind. Ctr.,

55 Hoi Yuen Rd., Kwun Tong, Kln.

Tel: 852 2345 5245

In case of poisoning, contact Mr. L.W. Poon

Tel: 852 2345 5245

Section 2: Hazard Classification

N.A.



Section 3 : Hazardous Ingredients / Identity Information

Ingredient	CAS NO.	EC No.	Content (wt%)
Manganese Dioxide	1313-13-9	215-202-6	22.20%
Zinc	7440-66-6	231-175-3	8.80%
Graphite	7782-42-5	231-955-3	3.60%
Potassium Hydroxide	1310-58-3	231-119-8	8.60%
Cadmium	7440-43-9	231-152-8	<0.0005%
Mercury	7439-97-6	231-106-7	<0.0001%
Lead	7439-92-1	231-100-4	<0.001%
Iron	7439-89-6	231-096-4	56.80%



PAK KO BATTERIES FACTORY LIMITED

Unit 11, 9/F., Block A, Hoi Luen Ind. Ctr., No. 55 Hoi Yuen Rd., Kwun Tong, Kln., H.K.
Tel.: (852) 2345-5245 Fax.: (852) 2797-9591 E-mail: pakko@pakkobatteries.com
<http://www.pakkobatteries.com>

Approval Date:

1 Mar 2016

Page:

2 Of 4

Section 4: First Aid Measures

First aid Procedures

If electrolyte leakage occurs and makes contact with skin, wash immediately.

If electrolyte comes into contact with eyes, wash with copious amounts of water for fifteen minutes, and contact a physician.

Section 5: Fire and Explosion Hazard Data

Flash point (Method Used) N.A.

Ignition temp. N.A.

Flammable Limits N.A.

LEL N.A.

UEL N.A.

Extinguishing Media N.A.

Special Fire Fighting Procedures N.A.

Unusual Fire and Explosion Hazards

Do not dispose of battery in fire - may explode.

Do not short - circuit battery - may explode.

In case of fire, it is permissible to use any class of extinguishing medium on these batteries or their packing material. Cool exterior of batteries if exposed to fire to prevent rupture.

Fire fighters should wear self-contained breathing apparatus.

Section 6 : Accidental Release or Spillage

Steps to Be Taken in Case Material is Released or Spilled

Batteries that are leaking should be handled with rubber gloves.

Avoid direct contact with electrolyte.



Section 7: Handling and Storage

Safe handling and storage advice

The battery is extremely sensitive to adverse effects of humidity. Be sure to store them in a place that is dry and subject to little temperature change. Do not place near boiler or radiator, nor expose to direct sun light. Do not dispose of the battery in fire. Do not charge the battery. Do not short-circuit the battery. Do not put in backward position. Do not store in disorderly fashion, or allow metal objects to be mixed with stored batteries. Do not disassemble the battery, handling in such manner can cause the battery to explode, leak and injury.



PAK KO BATTERIES FACTORY LIMITED



Unit 11, 9/F., Block A, Hoi Luen Ind. Ctr., No. 55 Hoi Yuen Rd., Kwun Tong, Kln., H.K.
Tel.: (852) 2345-5245 Fax.: (852) 2797-9591 E-mail: pakko@pakkobatteries.com
<http://www.pakkobatteries.com>

Approval Date:

1 Mar 2016

Page:

3 Of 4

Section 8: Exposure Controls / Personal Protection

Occupational Exposure Limits:		LTEP	N.A.	STEP	N.A.
Respiratory Protection (Specify Type)			N.A.		
Ventilation	Local Exhausts		N.A.	Special	N.A.
	Mechanical (general)		N.A.	Other	N.A.
Protection Gloves			N.A.	Eye Protection	N.A.
Other Protective Clothing or Equipment			N.A.		
Work / Hygienic Practices			N.A.		

Section 9 : Physical / Chemical Characteristics

Form :	N.A.	Specific Gravity (H ₂ O=1)	N.A.
Boiling Point	N.A.	Melting Point	
Vapor Pressure (mm Hg)	N.A.	Evaporation Rate(Butyl Acetate=1)	N.A.
Vapor Density (AIR=1)	N.A.	pH	N.A.
Solubility in Water	N.A.	Appearance and Odor	N.A.

Section 10: Reactivity Data

Stability	Unstable ()	Conditions to Avoid
Yes (X)	Stable (X)	



Incompatibility (Materials to Avoid)

Hazardous Decomposition or By products

When heated, battery may emit hazardous vapour of KOH/ NaOH and Hg

Hazardous Reactions	May Occur ()	Conditions to Avoid
Yes (X)	Will Not Occur (X)	

Section 11: Toxicological information

Route(s) of Entry Yes=(X) Inhalation? (N.A.) Skin? (N.A.) Ingestion? (N.A.)

Health Hazard (Acute and Chronic) / Toxicological information

In case of electrolyte leakage, skin will be itchy when contaminated with electrolyte.



PAK KO BATTERIES FACTORY LIMITED

Unit 11, 9/F., Block A, Hoi Luen Ind. Ctr., No. 55 Hoi Yuen Rd., Kwun Tong, Kln., H.K.
Tel.: (852) 2345-5245 Fax.: (852) 2797-9591 E-mail: pakko@pakkobatteries.com
<http://www.pakkobatteries.com>

Approval Date:

1 Mar 2016

Page:

4 Of 4

Section 12: Ecological Information

N.A.

Section 13: Disposal Method

Dispose of batteries according to government regulations

Section 14: Transportation Information

Pak Ko batteries are considered to be "Dry cell" batteries and are unregulated for purposes of transportation by the U.S. Department of Transportation(DOT), International Civil Aviation Administration (ICAO), International Air Transport Association(IATA) and International Maritime Dangerous Goods Regulation (IMDG). The only DOT requirement for shipping these batteries is special provision A123 which states: "Batteries, dry are not subject to the requirement of this subchapter only when they are offered for transportation in a manner that prevents the dangerous evolution of heat (For example, by the effective insulation of exposed terminals). As per 57th edition of IATA (2016) requires that batteries being transported by air must be protected from short-circuiting and protected from movement that could lead to short-circuiting."

Section 15: Regulatory Information

Special requirement be according to the local regulatory.

Section 16: Other Information

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

