

8980.

## MATERIAL SAFETY DATA SHEET

9736076A  
V# 10781000

SECTION 1 - PRODUCT IDENTIFICATION AND USE				
PRODUCT IDENTIFIER : SPECTRUM LEAD FREE UNDERGLAZE 501 UG WHITE			PRODUCT IDENTIFICATION NUMBER 501	
PRODUCT USE : CERAMIC GLAZE				
MANUFACTURER'S NAME SPECTRUM GLAZES INC.		SUPPLIER'S NAME SPECTRUM GLAZES INC.		
STREET ADDRESS: 273 BOWES RD, UNIT A1		STREET ADDRESS: 273 BOWES RD, UNIT A1		
CITY: CONCORD PROVINCE: ONTARIO		CITY: CONCORD PROVINCE: ONTARIO		
POSTAL CODE: L4K1H8 EMERGENCY TEL(905)695-8355		POSTAL CODE: L4K1H8 EMERGENCY TEL(905)695-8355		
SECTION 2 - HAZARDOUS INGREDIENTS				
HAZARDOUS INGREDIENTS	%	CAS NUMBER	LD50 OF INGREDIENTS (SPECIFY SPECIES AND ROUTE)	LC50 OF INGREDIENT (SPECIFY SPECIES)
SiO2	10-15	14808-60-7	ILV 15mg/m3 TLV/TWA	
MgO	.5-1.5	1309-48-4		
CaO	1-2	1305-78-8		
Na2O	.5-1	1313-59-3		
Al2O3	.5-1	1344-28-1		
B2O3	.5-1	1303-86-2		
ZrO2	20-25	1314-23-4		
SECTION 3 - PHYSICAL DATA				
PHYSICAL STATE LIQUID	ODOUR AND APPEARANCE ODOURLESS LIQUID			ODOUR THRESHOLD (PPM) N.A.
VAPOUR PRESSURE (mm Hg) N.A.	VAPOUR DENSITY (AIR=1)	EVAPORATION RATE N.A.	BOILING POINT (C) N.A.	FREEZING POINT (C) N.A.
pH 6.5-7	SPECIFIC GRAVITY 1.6-2.0	COEFF. WATER/OIL DIST. N.A.		
SECTION 4 - FIRE AND EXPLOSION DATA				
FLAMMABILITY YES__ NO X FLAMES UNDER WHICH CONDITIONS : THIS PRODUCT DOES NOT SUPPORT COMBUSTION				
MEANS OF EXTINCTION NO SPECIAL MEANS REQUIRED				
FLASHPOINT AND METHOD NONE	UPPER FLAMMABLE LIMIT (% BY VOLUME) N.A.		LOWER FLAMMABLE LIMIT (% BY VOLUME) N.A.	
AUTOIGNITION TEMP. (C) N.A.	HAZARDOUS COMBUSTION PRODUCTS NONE			
EXPLOSION DATA N.A.	SENSITIVITY IMPACT N.A.	ACTIVITY TO STATIC DISCHARGE N.A.		
SECTION 5 - REACTIVITY DATA				
CHEMICAL STABILITY YES X NO__ IF NO, UNDER WHICH CONDITIONS				
INCOMPATIBILITY WITH OTHER SUBSTANCES YES__ NO X IF SO WHICH ONES REACTIVITY				
REACTIVITY AND UNDER WHAT CONDITIONS: NO REACTIVITY				
HAZARDOUS DECOMPOSITION PRODUCT: MATERIAL IS STABLE, NO POLYMERIZATION BUT TOXIC FUMES MAY BE RELEASED WHEN MATERIAL IS MELTED.				

PRODUCT IDENTIFIER SPECTRUM LEAD FREE UNDERGLAZE 501 UG WHITE			
<b>SECTION 6 - TOXICOLOGICAL PROPERTIES</b>			
ROUTE OF ENTRY SKIN CONTACT      SKIN ABSORPTION X      EYE CONTACT X      INHALATION INGESTION X			
EFFECTS OF ACUTE EXPOSURE TO PRODUCT: SKIN IRRITATION DUE TO ABRASIVENESS. EYE EXPOSURE COULD CAUSE IRRITATION BUT NO TOXIC EFFECTS.			
EFFECTS OF CHRONIC EXPOSURE TO PRODUCT: METAL FUMES IN THE VAPOURS FROM FIRING CERAMIC GLAZES MAY CAUSE LUNG INFLAMATION AND DAMAGE TO KIDNEY AND NERVOUS SYSTEM.			
EXPOSURE LIMITS	IRRITANCY OF PRODUCT	SENSITIZATION TO PRODUCT	CARCINOGENICITY
TERATOGENICITY	REPRODUCTIVE TOXICITY	MUTAGENICITY	SYNERGISTIC PRODUCTS
<b>SECTION 7 - PREVENTIVE MEASURES</b>			
PERSONAL PROTECTIVE EQUIPMENT:			
GLOVES (SPECIFY) WORK GLOVES	RESPIRATOR (SPECIFY) APPROVED DUST MASK	EYE (SPECIFY) SAFETY GLASSES	
FOOTWEAR (SPECIFY)	CLOTHING (SPECIFY)	OTHER (SPECIFY)	
ENGINEERING CONTROLS (SPECIFY, EG. VENTILATION, ENCLOSED PROCESS) VENTILATION SHOULD BE USED WHEN SPRAYING GLAZES.			
LEAK AND SPILL PROCEDURE: SCOOP INTO SUITABLE RECEPTACLE. DO NOT WASH DOWN DRAIN.			
WASTE DISPOSAL: SEND TO APPROVED SITE IN ACCORDANCE WITH REGULATIONS.			
HANDLING PROCEDURES AND EQUIPMENT: NO SPECIAL EQUIPEMENT NEEDED. FOLLOW STANDARD PLANT HYGIENE PROCEDURE.			
STORAGE REQUIREMENTS: STORE IN DRY AREAS.			
SPECIAL SHIPPING INFORMATION: PROTECT AGAINST PHYSICAL DAMAGE. DOT LABEL NON-REGULATED			
<b>SECTION 8 - FIRST AID MEASURES</b>			
SPECIFIC MEASURES: GLAZE CONTAINS THE OXIDES LISTED IN THE CHEMICAL FORMULA IN FORM OF CERAMIC FRIT. SOME OF THESE OXIDES ARE ON THE INGREDIENT DISCLOSURE LIST, ONCE THESE OXIDES ARE FUSED AND CONVERTED INTO FRIT THEY ARE NO LONGER AVAILABLE IN TOXIC FORM EVEN THOUGH TESTING WOULD DETECT THE PRESENCE OF THESE OXIDES. (FRIT IS ESSENTIALLY AN INSOLUBLE SUBSTANCE). THE OXIDES ARE PRESENT IN THE FORM OF A SINTERED CERAMIC STAIN OF LOW SOLUBILITY. THESE INGREDIENTS ARE PRESENT IN A STABLE AQUEOUS SUSPENSION.			
<b>SECTION 9 - PREPARATION DATE OF MSDS</b>			
PREPARED BY (GROUP, DEPARTMENT, ETC.) TECHNICAL DEPT.	PHONE NUMBER: (905) 695-8355	DATE 15 OCTOBER 2015	