

900.

C10897

MATERIAL SAFETY DATA SHEET

W.F. Young

ABSORBINE SUPERSHINE BLACK

08/99

MSDS#: 0037

MANUFACTURER: W.F. YOUNG, INC.

111 LYMAN STREET

SPRINGFIELD, MA 01102

NON-EMERGENCY TELEPHONE: MA (413) 737-0201

SECTION 1: CHEMICAL PRODUCT IDENTIFICATION

PRODUCT NAME: Absorbine Supershrine Black

PRODUCT DESCRIPTION: Black thin liquid

MEDICAL EMERGENCY TELEPHONE (Poison Center): (303) 623-5716

TRANSPORTATION EMERGENCY TELEPHONE (Chemtrec):

1-800-424-9300

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS
(Typical Values)

HAZARDOUS INGREDIENTS/ CAS NO.	WT. %	ACGIH (TLV)	OSHA (PEL)
Acetone	75-85	750 ppm	1000ppm
67-64-1		(8 hr)	(8hr)
Phenolic Novolac Resin	15-25		
Not classified			
Black Dye			

OTHER IMPORTANT INGREDIENTS

SECTION 3: HAZARDS IDENTIFICATION

SIGNS AND SYMPTOMS OF EXPOSURE: Prolonged exposure to excessive concentrations may result in irritation of mucous membranes, headaches, drowsiness, fatigue, and narcosis.

ROUTES OF ENTRY:

INHALATION? Yes

SKIN? Yes

INGESTION? Yes

HEALTH HAZARDS (Acute and Chronic): The Health effects noted below are consistent with requirements under OSHA Hazard Communication Standard (29 CFR 1910.1200).

EYE CONTACT: Liquid is severely irritating to the eyes. High vapor concentrations are also irritating.

SKIN CONTACT: Liquid is mildly irritating to the skin. Prolonged skin contact may result in skin irritation and dermatitis.

INGESTION: May produce CNS depression. Seek medical attention.

CARCINOGENICITY:

NTP? No

IARC MONOGRAPH? No

OSHA MONOGRAPH? No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Pre-existing skin disorders may be aggravated by exposure.

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention, if needed.

SKIN CONTACT: If irritation occurs, flush skin with water. If irritation persists, get medical attention.

INHALATION: Remove victim to fresh air, treat symptomatically. Get medical attention if symptoms persist.

INGESTION: Contact a physician or Poison Control Center.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT (Method Used): 20.3 deg F (TOC)

FLAMMABLE LIMITS: N/E

LEL: N/E

UEL: N/E

EXTINGUISHING MEDIA: Foam, Carbon Dioxide, Dry Chemical and Water Fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Water spray can be used to reduce intensity of flames and to dilute spills to nonflammable mixture.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors from this product may travel or be moved by air currents and be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges or other ignition sources at location distant from handling point. Vapors are heavier than air.

SECTION 6: ACCIDENTAL RELEASE MEASURES & DISPOSAL

SPILL CONTROL METHODS: Eliminate ignition sources. Avoid eye or skin contact. Place leaking containers in well-ventilated area. If fire potential exists, blanket spill with foam or use water spray to disperse vapors. Contain spill to minimize contaminated area and facilitate salvage or disposal. To clean up spill, flush area sparingly with water or use an absorbent. Avoid runoff into storm sewers and ditches which lead to natural waterways. Call the National Response Center (800-424-8802) if spill is equal to or greater than reportable quantity (5000 lb/day) under "Superfund". All clean-up and disposal should be carried out in accordance with Federal, State, and Local Regulations. If required, state and local authorities should be notified.

WASTE DISPOSAL METHODS: This product, when spilled or disposed of, is a hazardous waste as defined in Resource Conservation Recovery Act regulations (40 CFR 261). Preferred method is incineration or biological treatment in federal/state approved facility.

SECTION 7: HANDLING & STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING & STORING: Store away from oxidizing agents; keep away from heat or ignition sources; use adequate ventilation.

OTHER PRECAUTIONS: Keep container closed. Ground containers when empty. Do not store or consume food, drink, or tobacco in area where they may become contaminated with this material.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

RESPIRATOR PROTECTION: Avoid prolonged or repeated breathing of vapors. If exposure may or does exceed occupational exposure limits (Section 2) use a NIOSH-APPROVED respirator to prevent overexposure. In accord with 29 CFR 1910.134 use either an atmosphere-supplying respirator or an air-purifying respirator for organic vapors.

VENTILATION: Local exhaust - Recommend at least 10 changes per hour.

SKIN AND EYE PROTECTION: Avoid contact with eyes. Wear chemical goggles if there is a likelihood of contact with eyes. Avoid prolonged or repeated contact with skin.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash; safety showers; wash after handling

W.F. Young

ABSORBINE SUPERSHINE BLACK

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: Not Established
 MELTING POINT: Not Established
 VAPOR PRESSURE: Not Applicable
 VAPOR DENSITY (AIR = 1): Not Applicable
 EVAPORATION RATE (butyl acetate = 1): Not Applicable
 VOLATILE FRACTION BY WEIGHT: 80
 SOLUBILITY IN WATER (By weight %): Partial
 SPECIFIC GRAVITY (H₂O = 1) @ 25 C: 0.865
 pH:
 APPEARANCE: Black thin liquid
 ODOR: Acetone

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable
 INCOMPATIBILITY (Materials to avoid): Avoid heat, sparks, and flame.
 HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Carbon monoxide, Carbon dioxide, Oxides of Nitrogen
 HAZARDOUS POLYMERIZATION: Will not occur

SECTION 11: TOXICOLOGICAL INFORMATION

ORAL LD50: TBD
 DERMAL LD50: TBD
 INHALATION LC50: Not established
 EYE EFFECTS: Produces ocular damage in the form of erythema, chemosis, iritis, mucoid discharge, and corneal opacity.
 SKIN EFFECTS: Is not a primary skin irritant

SECTION 12: ECOLOGICAL INFORMATION

Avoid runoff into storm sewers and ditches which lead to natural waterways.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Preferred method is incineration or biological treatment in federal/state approved facility.

SECTION 14: TRANSPORTATION INFORMATION

DOT, IMO, ICAO, TRANSPORT CANADA:
 HAZARD CLASS: ORM-D
 PROPER SHIPPING NAME: Consumer Commodity.
 UN NUMBER:
 LABEL:
 PACKING GROUP:
 PLACARD:
 FLASH POINT: 20.3 deg F
 NFPA:
 HEALTH: 1
 FLAMMABILITY: 3
 REACTIVITY: 0
 SPECIAL: None
 4=Extreme 3=High 2=Moderate 1=Slight 0=Insignificant

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATION:
 OSHA: Subpart Z
 TSCA: EPA, Section 313 Table II
 CERCLA HAZARDOUS SUBSTANCE (40 CFR 302): Reportable quantity, sec 302. RECRA Waste No. U002 5000 lbs (2270)
 SARA TITLE III: Threshold planning quantity, sec.302
 SARA HAZARD CATEGORIES: H-1 Immediate health hazard; H-2 Delayed health hazard; P-3 Fire Hazard
 TURA 3B:

CHEMICAL SUBSTANCE/ CONCENTRATION % WT.
 CAS NO.

Acetone 75 - 85
 67-64-1

LISTED UNDER THE FOLLOWING: FEDERAL REGULATIONS; STATE REGULATIONS; INTERNATIONAL REGULATIONS

SECTION 16: OTHER INFORMATION

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of the knowledge of W.F. Young, Inc. The data on this sheet relates only to the specific material designed herein and does not relate to use in combination with any other material or in any process. W.F. Young, Inc. assumes no legal responsibility for use or reliance upon this data. This information herein is provided solely for your consideration, investigation, and verification.

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES: Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representation as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s). A request has been made to the manufacturer to approve the contents of this material safety data sheet. Upon receipt a new MSDS will be made available.

COMPAS Code: 13540181