


SAFETY DATA SHEET





1. Identification

Product identifier 1000, 2200 Series Products

Other means of identification

See page 8

SDS number

1000, 2200 Series (921276)_USA_English

Recommended use

Various end uses e.g. pharmaceutical excipient, personal care/cosmetics, food contact coatings,

additive for wax blends, use in adhesives etc.

Recommended restrictions

None known

Manufacturer/Importer/Supplier/Distributor information

Company Name

The International Group Inc.

Address

50 Salome Dr.

Toronto

ON, M1S2A8, CA

Telephone

001-(416)-293-4151

E-mail

Contact person Emergency phone number

001-(416)-293-4151

001-(800)-561-3509

CHEMTREC (North

Amerca)

001-(800)-424-9300

2. Hazard(s) identification

Physical hazards

Not classified

Health hazards

Not classified.

OSHA defined hazards

Not classified.

This product does not meet the criteria for classification according to OSHA Hazard Communication Standard (OSHA GHS).

Label elements

Hazard symbol

None.

Signal word

None. The product does not meet the criteria for classification.

Precautionary statement

Prevention

Hazard statement

Observe good industrial hygiene practices.

Response

Wash hands after handling.

Storage

Store away from incompatible materials.

Disposal

Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known

3. Composition/information on ingredients

Substances

Chemical name

Common name and synonyms

CAS number

%

Paraffin wax

8002-74-2

100

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

1000, 2200 Series

Version #: 02

Revision date: 20-April-2015

Issue date: 11-March-2015

SDS US 1/8

921276

4. First-aid measures

Inhalation

Solid: No specific first aid measures noted. If fumes from heated product are inhaled: Move to

fresh air. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Solid: No specific first aid measures noted. If burned by contact with hot material, cool molten material adhering to skin as quickly as possible with water, and see a physician for removal of

adhering material and treatment of burn.

sheet to the doctor in attendance.

Eye contact

Solid: No specific first aid measures noted. Exposure to fumes, vapors or smoke of over heated product can result in irritation of eyes. Direct contact of molten material will cause injury and burns. When handling of molten product eye shield must be worn at all times. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Should an accident occur, flush eyes with generous amounts of water for at least 15 minutes. Administer prompt first aid measures. Get medical attention if irritation develops and persists.

Ingestion

media

Solid: No specific first aid measures noted. Not acutely toxic by ingestion. If material is ingested, do not induce vomiting. Contact with hot product may cause severe burns. Get medical attention immediately.

Most important symptoms/effects, acute and delayed Eye and skin contact: When heated, contact with molten product can cause injury and burns.

Indication of immediate medical attention and special treatment needed

General information

If you feel unwell, seek medical advice (show the label where possible). Show this safety data

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Provide general supportive measures and treat symptomatically.

Do not use water on molten material: Explosion hazard could result.

Specific hazards arising from the chemical

By heating and fire, irritating vapors/gases may be formed. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Do not direct water at source of leak or safety devices as icing may occur. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Methods and materials for containment and cleaning up

Keep unnecessary personnel away. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.

Handle as a thermoplastic. With molten spills, allow the material to solidify and cool. Keep material out of sewers and watercourses by diking or impounding. Recover and place into appropriate containers for recycling or disposal, according to prevailing local, state and federal laws.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Allow material to solidify, and scrape up. Following product recovery, flush area with water.

Small Spills: Where possible allow molten material to solidify naturally.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water.

Environmental precautions

1000, 2200 Series

Version #: 02 Revision date: 20-April-2015

Issue date: 11-March-2015

SDS US

921276

7. Handling and storage

Precautions for safe handling

When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers. Do not handle until all safety precautions have been read and understood. Heat only in areas with appropriate exhaust ventilation. Do not breathe fume/mist/vapors. Avoid contact with molten material. When using, do not eat, drink or smoke. Observe good industrial hygiene practices. Do not empty into drains. Avoid release to the environment. Wash contaminated clothing before reuse. The material is a solid at room temperature exhibiting elevated temperature softening characteristics. Above its softening point, the material liquefies and flows more readily as the temperature increases. The material may be used as a hot liquid for application purposes and requires caution in handling.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS). When kept in molten state, inert gas blanketing may be used to avoid material degradation. As a solid, avoid contamination by keeping in closed containers.

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form	
Paraffin wax (CAS 8002-74-2)	TWA	2 mg/m3	Fume.	
US. NIOSH: Pocket Guide to C	hemical Hazards			
Components	Туре	Value	Form	
Paraffin wax (CAS	TWA	2 mg/m3	Eume	

Biological limit values

8002-74-2)

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Eye wash facilities and emergency

shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear approved safety goggles. Wear a face shield when working with molten material.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

Other

The material may be utilized in molten form. Proper protective splash resistant clothing, thermal gloves, splash resistant shoes, and eye shields must be worn to prevent injury. Use molten material in well ventilated areas. When working in confined areas, use of appropriate respiratory

gear is recommended.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Issue date: 11-March-2015

9. Physical and chemical properties

Appearance

Physical state

Form

Slabs, prills, pastilles or granules

Color

White to light gray or tan.

Odor threshold

None to slight petroleum odor.

Odor pH

921276

No data available. Not applicable

1000, 2200 Series

Version #: 02

Revision date: 20-April-2015

SDS US 3/8 Melting point/freezing point

99 - 212°F (37 - 100°C)

Initial boiling point and boiling

> 572 °F (> 300 °C)

range

Flash point

>347°F (> 175°C) ASTM D-92

Evaporation rate

< 0.01 (Butyl acetate = 1)

Flammability (solid, gas)

Will support a flame above flash point.

Upper/lower flammability or explosive limits

Flammability limit - lower

No data available.

(%)

Flammability limit - upper

No data available.

(%)

Explosive limit - lower (%) 0.9 % Explosive limit - upper (%) 7 %

Vapor pressure < 0.01 n

Vapor density

< 0.01 mm Hg (77 °F/25 °C) > 5 (Air = 1)

Relative density

0.9 - 0.93 (77 °F/25 °C)

Solubility(ies)

Solubility (water) < 0.1 % (68 °F/20 °C) ition coefficient No data available.

Partition coefficient (n-octanol/water)

No data available.

Auto-ignition temperature

Decomposition temperature

No data available.

Viscosity

No data available.

Other information

Partition coefficient

< 0.01

(oil/water)

Percent volatile Negligible.

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

No dangerous reaction known under conditions of normal use. Hazardous polymerization does not

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous reactions

occur.

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition products Decomposition of this product can generate carbon dioxide, carbon monoxide and other products

such as aldehyldes and ketones depending on conditions of oxidation.

11. Toxicological information

Information on likely routes of exposure

Inhalation Not rel

Not relevant at normal room temperatures. When heated, irritating vapors may be formed. Wax

fumes have been reported to be irritating to the respiratory tract, especially to sensitized persons.

Skin contact Health injuries are not known or expected under normal use. Molten material will produce thermal burns.

Health injuries are not known or expected under normal use. Molten material will produce thermal

burns

Ingestion

Health injuries are not known or expected under normal use. Contact with hot material can cause thermal burns which may result in permanent damage.

E a sed alia contact Contact with selling

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

Eye and skin contact: Contact with molten material may cause thermal burns.

Information on toxicological effects

Acute toxicity

Not expected to be acutely toxic.

Skin corrosion/irritation

Thermal burn hazard - contact with hot material may cause thermal burns.

1000, 2200 Series

SDS US

921276

Version #: 02

Revision date: 20-April-2015

Issue date: 11-March-2015

4/8

Serious eye damage/eye

irritation

Not classified. Direct contact of molten product to the eyes will cause thermal burns and eye injury.

Respiratory or skin sensitization

Respiratory sensitization

Not classified.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

Not classified.

Carcinogenicity

Not expected to be hazardous by OSHA criteria.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

Not classified.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Solid product: Not likely, due to the form of the product.

Chronic effects

Not expected to be hazardous by OSHA criteria. Exposure to vapors, fumes, or smoke from molten material handled in confined areas can produce irritation of respiratory tracts, and possible physical discomfort to sensitive individuals. In rats, chronic ingestion of paraffins has shown accumulation in target organs (liver, spleen) with associated nonspecific immune response.

Further information

None

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of this product. No data available

Bioaccumulative potential

No data available

Mobility in soil Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

General information

This product is not regulated as dangerous goods for solid and molten product shipped under 212 °F/100 °C. Hot molten product shipped over 212 °F/100 °C requires a class 9 "HOT" with

statement: Elevated temperature material, liquid, N.O.S. 9, UN3257, III (WAX).

1000, 2200 Series

SDS US

921276

Version #: 02

Revision date: 20-April-2015

Issue date: 11-March-2015

5/8

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Paraffin wax (CAS 8002-74-2)

US. New Jersey Worker and Community Right-to-Know Act

Paraffin wax (CAS 8002-74-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Paraffin wax (CAS 8002-74-2)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

Not Listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

1000, 2200 Series

921276

SDS US

Version #: 02

Revision date: 20-April-2015

Issue date: 11-March-2015

6/8

Country(s) or region

Inventory name

On inventory (yes/no)*

United States & Puerto Rico

Toxic Substances Control Act (TSCA) Inventory

Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date

11-March-2015

Revision date

20-April-2015

Version #

02

HMIS® ratings

Health: 0 Flammability: 1

Physical hazard: 0

List of abbreviations

LD50: Lethal Dose, 50%.

LC50: Lethal Concentration, 50%. TWA: Time weighted average. STEL: Short term exposure limit. DOT: Department of Transportation.

IATA: International Air Transport Association.
IMDG: International Maritime Dangerous Goods.
OSHA: Occupational Safety and Health Administration.

CAS: Chemical Abstracts Service.

WHMIS: Workplace Hazardous Materials Information System.

HMIS: Hazardous Materials Identification System.

NFPA: National Fire Protection Association.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices

IARC Monographs. Overall Evaluation of Carcinogenicity

HSDB® - Hazardous Substances Data Bank Registry of Toxic Effects of Chemical Substances (RTECS)

Registry of Toxic Effects of Chemical Substances (RTECS

Disclaimer

References

This material safety data sheet is offered for your information only. We believe the statements, technical information and recommendations contained here in are reliable, but are given without warranty or guarantee of any kind, expressed or implied. THE INTERNATIONAL GROUP, INC. assumes no responsibility for any loss, damage or expense, direct or consequential, arising from the use of our material. It is the responsibility of the user to determine the suitability and completeness of such information for the required use or application. We do not assume any legal responsibility for nor do we give permission, inducement or recommendation to practice any patented invention without a license. Further, it is the user's obligation to utilize this material in full compliance with all health, safety and environmental regulations.

PRODUCT	PRODUCT	PRODUCT
NUMBER	NUMBER	NUMBER
1070A 1070C 1208A 1210A 1212U 1216A 1221A 1226A 1226F 1227A 1230C 1230D 1230E 1230F 1230F 1230G 1230H 1230K 1230H 1231A 1231B 1231U 1235A 1235B 1235C 1236A 1236B 1236C 1236A 1236B 1236C 1236A 1236B 1236C 1236A 1236B 1236C 1236A 1236B 1236C 1236A 1236B 1235C 1236A 1236B 1236C 1236A 1236B 1236C 1236A 1236B 1236C 1236D 1250B 1250D 1250B 1250D 1250B 1250D 1250B 1250D 1250B 1250D 1260E 1260D 1260E 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1260D 1260B 1270A 1274A	1278A 1284A 1286A 1288B 1290A 1290B 1293A 1296A 1297A 1297U 1301A 1302B 1302C 1302F 1302U 1303A 1303F 1303U 1304A 1303A 1303A 1303A 1303A 1313A 1314A 1325A 1325B 1325C 1330A 1339A 1339A 1349A 1349A 1349A 1347B 1377A 1380A 1347B 1377A 1380A 1397U 1398A 1347B 1377A 1380A 1397U 1398A 1397U 1398A 1397U 1398A 1397U 1398A 1397U 1398A 1397U 1398A 1397U 1398A 1430A 1397U 1398A 1430A 1397U 1398A 1430A 1397U 1398A 1430A 1397U 1398A 1430A 1397U 1398A 1430A 1435A 1397U 1398A 1430A 1397U 1398A 1430A 1397U 1398A 1430A 1435A 1397U 1398A 1430A 1435A 1397U 1398A 1430A 1435A 1397U 1398A 1430A 1430A 1435A 1397U 1398A 1430A 1435A 1397U 1398A 1430A 1435A 1397U 1398A 1430A 1430A 1435A 1397U 1398A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A 1430A	2237A 2243A 2251B 2251C 2251U 2252A 2281A 2281A 2285A 2289A 2289B 2289B 2289B 2289G 2289N 2289U R-6032A R-6192A R-6262A R-6283A R-6427A R-6448A