



Product Name: ALL-WEATHER ® Plastic Ear Tag Marker-Black Revision Date: August 8, 2011

Page 1 of 7

SAFETY DATA SHEET

Section 1: Product and Company Identification

Product Name: ALL-WEATHER ® Plastic Ear Tag Marker - Medium Tip Black, Fine Tip Black

Product Code: Medium Tip Black (96623, 96734)

Fine Tip Black (96723, 96733)

Product Use: Weather-resistant marker for polyurethane tags

Supplier: LA-CO Industries, Inc. 1201 Pratt Boulevard Elk Grove Village, IL.

60007-5746

E-mail Contact: customer_service@laco.com

Phone: (847) 956-7600 Fax: (847) 956-9885

24-hour Emergency: CHEMTREC: (800) 424-9300

Section 2: Hazards Identification

Protective Clothing	NFPA Rating (USA)	EC Classification	WHMIS (Canada)	Transportation
Not Required for Normal Use		Not Classified as Dangerous	Not Controlled	Excepted Quantity [Class 3 Flammable liquid]

Emergency Overview:

The ink inside the marker contains components which are considered hazardous by inhalation of vapors and skin contact. Exposure to hazardous or dangerous substances is not expected when handling this product for its intended use.

Appearance, Color and Odor: Marker containing less than 10 mL of black ink. Organic solvent odor.

USA: This product is not a hazardous material as defined by 29 CFR1910.1200, OSHA Hazard Communication Evaluation. This product meets the definition of an "article".

Canada: This is not a controlled product under WHMIS. This product meets the definition of a "manufactured article" and is not subject to the regulations of the Hazardous Products Act.

European Communities (EC): This product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Potential Health Effects: ACUTE (short term):

Relevant Route(s) of Exposure: Skin contact.

Inhalation: Exposure to hazardous substances by inhalation is not expected with normal use of the marker.

Ingestion: Not an expected route of occupational exposure. Acute oral toxicity of the component substances

is low.

Skin: Normal use of marker will not result in harmful effects. The ink may cause irritation when in

contact with the skin. Some components of the ink may be absorbed through the skin.

Eye: Not an expected route of occupational exposure. Liquid and concentrated vapors can irritate the

eyes.





Section 2: Hazards Identification, continued

CHRONIC (long term): see Section 11 for additional toxicological data

Long-term health effects are not expected with normal use of the marker. Prolonged or repeated contact with of the ink to skin may result in defatting and

drying of skin and may result in dermatitis.

Medical Conditions Aggravated by Exposure: Preexisting skin disorders may be aggravated by repeated exposure to the liquid in

the marker.

Interactions With Other Chemicals: Not available

Potential Environmental Effects: Not available

Section 3: Composition / Information on Ingredients

Chemical Name	CAS No.	Wt.%	EC#	Symbol	Risk Phrases
Methyl Isobutyl ketone (MIBK)	108-10-1	10 – 37	203-550-1	F; Xn; Xi	R11; R20; R36/37; R66
Xylene	1330-20-7	10 - 30	215-535-7	Xn	R10; R20/21; R38
2-phenoxyethanol	122-99-6	10 – 15	204-589-7	Xn; Xi	R22; R36
n-Butyl Alcohol	71-36-3	0 - 15	200-751-6	Xn	R10; R22; R37/38; R41; R67
Vinyl acetate Vinyl chloride copolymer	9003-22-9	3-7	Polymer	Not applicable	Not applicable
Ethylbenzene	100-41-4	3 - 7	202-849-4	F; Xn	R11; R20
Amines, C12_14-tert-alkyl, compds. with 1-[[5-(1,1-dimethylpropyl)-2-hydroxy-3-nitrophenyl]azo]-2-naphyhalenol 1-[[2-hydroxy-4(or 5)-nitrophenyl]azo]-2-naphthenol chromium complexes	117527-94-3	3-7	403-720-7	N	R51/53
Carbon Black	1333-86-4	1 - 3	215-609-9	Not applicable	Not applicable
2-Amino-2-methyl-1-propanol	124-68-5	0.5 - 1.5	204-709-8	Xi	R36/38; R52/53

See Section 16 for the full text of the R-phrases above.

Section 4:	Eiret Aid	Measures
Section 4:	FIRST AIG	weasures

Inhalation: If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice.

Eye Contact: No effects expected. If irritation occurs, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes.

If irritation persists, obtain medical advice.

Skin Contact: No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. If

irritation persists, obtain medical advice.

Ingestion: If irritation or discomfort occurs, obtain medical advice immediately.





Section 5: Fire Fighting Measures

Flammable Properties: Ink contained within the markers is flammable.

Suitable extinguishing Media: For small fires, use water spray, dry chemical, carbon dioxide, or alcohol-resistant

foam. For large fires, use carbon dioxide, dry chemical powder, alcohol-resistant foam or polymer foam. Firefighting foams are the extinguishing agent of choice for most flammable liquid fires. Use water spray to cool fire-exposed containers.

Unsuitable extinguishing Media: Not available

Explosion Data:

Sensitivity to Mechanical Impact: Not applicable

Sensitivity to Static Discharge: Not applicable

Specific Hazards arising from the Chemical: If involved in a fire, combustion may produce toxic and irritating fumes and gases.

Protective Equipment and precautions for

firefighters:

Self-contained breathing apparatus and protective clothing should be worn.

Remove all unprotected personnel.

NFPA

Health: 0
Flammability: 1
Instability: 0

Section 6: Accidental Release Measures

Personal Precautions: If large volumes of liquid ink are released, wear protective gloves, goggles and

clothing. Ventilate the area. Monitor the workplace air for harmful concentrations of vapors and take appropriate precautions if concentrations in air exceed

workplace exposure limits.

Environmental Precautions: Prevent the product from entering sewers or waterways.

Methods for Containment: If large volumes of liquid ink are released, stop the leak if it is safe to do so.

Contain spilled ink with earth, sand, or absorbent material which does not react

with spilled material.

Methods for Clean-up: Clean up spills immediately. Shut off or extinguish all sources of Ignition.

Immediately soak spilled material with water. Soak up spill with absorbent material which does not react with spilled chemical. Put material in suitable, covered, labeled containers. Contaminated absorbent material may pose the same hazards

as the spilled product. Dispose of any contaminated, unusable product as

described in Section 13 of this SDS.

Section 7: Handling and Storage

Handling: Avoid breathing vapors. Do not use near sources of extreme heat. Keep out of

reach of children.

Storage: Store in a cool, dry area, out of direct sunlight and away from heat, flames and

ignition sources. Keep markers closed when not in use.



Section 8: Exposure Controls/Personal Protection

Exposure Guidelines

Measurable airborne concentrations of the component substances, listed in Section 3, are not expected when the markers are used for their intended purpose. Consult local authorities for acceptable exposure limits.

Exposure Controls

Engineering Controls:

Not required for normal use.

Personal Protection:

Eye/Face Protection: Not required for normal use. In case of accidental release of large quantities of ink, wear goggles.

Skin Protection: Not required for normal use. In case of accidental release of large quantities of ink, wear gloves.

Respiratory Protection: Not required for normal use.

General Hygiene Measures: Avoid breathing vapors. Do not ingest. Avoid contact of the ink to skin and eyes. Keep out of reach

of children.

Section 9: Physical and Chemical Properties

Physical State:	Solid, containing liquid ink.	Flash Point & method:	16°C (61°F) CC ASTM D56 for MIBK
Appearance, Color and Odor:	Cylindrical marker; black odor of organic solvent.	Autoignition Temperature:	Not available
Odor Threshold:	Not available	Flammability Limits in Air:	Not available
pH:	Not applicable	Vapor Pressure:	Not applicable
Specific Gravity:	< 1.0	Vapor Density:	Not applicable
Partition coefficient:	Not available	Evaporation Rate:	Not applicable
Solubility:	Not applicable	Boiling Point/Range:	138.3°C (281°F)
Viscosity:	Not applicable	Melting Point:	Not available
Decomposition Temperature:	Not available	VOC Content:	85% (w/w) for liquid ink

Section 10: Stability and Reactivity

Chemical Stability: Stable at normal room temperature.

Conditions to Avoid: Do not use in conditions of extreme heat or near open flames.

Incompatible Materials: Incompatible with strong oxidizing agents.

Hazardous Decomposition

Products:

Reactions:

Not applicable

Possibility of Hazardous

9

Not applicable





Section 11: Toxicological Information

Acute Toxicity Data Acute toxicity data is not available for the liquid ink preparations inside the markers. The ink contains

substances which are considered toxic and harmful by inhalation and in contact with skin however, exposure to toxic and harmful substances by the user is not expected when the marker is used for its

intended purpose.

Other Toxicity Data

Carcinogenicity: The component Ethylbenzene is listed by IARC (International Agency for Research on Cancer) in

Group 2B, possibly carcinogenic to humans, and by ACGIH (American Conference of Governmental Industrial Hygienists) as A3, confirmed animal carcinogen with unknown relevance to humans. Normal use of the markers is not expected to pose the risk of exposure to carcinogenic substances.

Irritation: Normal use of marker will not result in harmful effects. High concentrations of vapors may cause

irritation to the eyes. Ink may cause irritation in contact with skin.

Corrosivity: Not applicable
Sensitization: Not applicable

Neurological Effects: Not applicable with normal use of the marker.

Genetic Effects: Not applicable with normal use of the marker.

Reproductive Effects: Not applicable with normal use of the marker.

Developmental Effects: Not applicable with normal use of the marker.

Target Organ Effects: Not applicable with normal use of the marker.

Section 12: Ecological Information

Ecotoxicity: Not available

Persistence/Degradability: Not available

Bioaccumulation/Accumulation: Not available

Mobility: Not available

Section 13: Disposal Considerations

Waste Disposal Method: Do NOT dump into any sewers, on the ground or into any body of water. Store material for

disposal as indicated in Section 7 Handling and Storage.

The conditions of use, storage and disposal of this product are beyond our control and may be beyond our knowledge. For this and other reasons, LA-CO Industries, Inc. does not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any

way connected with the handling, storage, use or disposal of this product.

USA: Dispose of in accordance with local, state and federal laws and regulations.

Canada: Dispose of in accordance with local, provincial and federal laws and regulations.

EC: Waste must be disposed of in accordance with relevant EC Directives and national, regional and

local environmental control regulations. For disposal within the EC, the appropriate code

according to the European Waste Catalogue (EWC) should be used.





Section 14: Transport Information:

U.S. Hazardous Materials Regulation (DOT 49CFR): This product conforms to 49 CFR 173.4 for domestic highway or rail

transport only.

Conforms to 49 CFR 173.4a Excepted quantity of Class 3 Flammable

liquid.

Canadian Transportation of Dangerous Goods (TDG): Dangerous goods in excepted quantity.

ADR/RID: Dangerous goods in excepted quantity.

IMDG: Dangerous goods in excepted quantity.

ICAO/IATA: Dangerous goods in excepted quantity.

Section 15: Regulatory Information

USA

TSCA Status: All component substances are listed on the TSCA inventory.

SARA Title III

Sec. 302/304: None Sec: 311/312: Flammable

Sec. 313: Xylenes, Ethylbenzene, Methyl Isobutyl Ketone, n-Butyl Alcohol, Chromium compound CERCLA RQ: Xylenes 100 lb, Ethylbenzene 1 000 lb, Methyl Isobutyl Ketone 5 000 lb, n-Butyl Alcohol 5

000 lb

California Prop 65: This product contains the following chemicals known to the State of California to cause

cancer: Ethylbenzene, and Carbon Black*.

*As sold, this product does not contain Carbon Black as airborne, or unbound particles of

respirable size.

State Right-to-Know Lists: Xylene, Ethylbenzene, Carbon black and Methyl isobutyl ketone, can be found on the

following state right to know lists: California, New Jersey, Pennsylvania, Minnesota,

Massachusetts.

2-Phenoxyethanol can be found on the following state right to know lists: Pennsylvania.

Canada This product has been classified in accordance with the hazard criteria of the Controlled

Products Regulations and the MSDS contains all the information required by the Controlled

Products Regulations.

WHMIS Classification: Not controlled. Product meets the definition of a "manufactured article" and is not subject

(for workplace exposures) to the regulations of the Hazardous Products Act.

New Substance Notification All component substances are listed on Canada's Domestic Substances List (DSL).

Regulations:

NPRI Substances: Xylene (mixed isomers), Ethylbenzene, Methyl Isobutyl Ketone, n-Butyl Alcohol, Chromium

compound.

EC Classification for the Substance/Preparation

European Inventories: All component substances are listed in EINECS.

Symbol: This product is not classified as dangerous according to Directive 1999/45/EC and its

amendments.



Page 7 of 7



Section 16: Other Information

Full Text of R-phrases appearing in Section 2:

LA-CO Markal

R10: Flammable. R11: Highly flammable.

R20/21: Harmful by inhalation and in contact with skin.

R22: Harmful if swallowed.

R36/37/38: Irritating to eyes, respiratory system and skin.

R41: Risk of serious damage to eyes.

R51/53: Toxic to aquatic organisms, may cause long term adverse effects in the

aquatic environment.

R52/53: Harmful to aquatic organisms, may cause long term adverse effects in the

aquatic environment.

R66: Repeated exposure may cause skin dryness or cracking.R67: Vapors may

cause drowsiness and dizziness.

Preparation Information:

Revision Date:

August 8, 2011

Revision Summary:

December 9, 2005: Preparation Date

October 19, 2007: Updated Exposure Limits (Section 8).

November 17, 2008; SDS template update. August 8, 2011; Revised formulation.

Manufacturer Disclaimer:

The information contained herein is based on data available to us and is accurate and reliable to the best of our knowledge and belief. However, LA-CO Industries, Inc. makes no representations as to its completeness or accuracy. Information is supplied on condition that persons receiving such information will make their own determination as to its suitability for their purposes prior to use. In no event will LA-CO Industries, Inc. be responsible for damages of any nature whatsoever resulting from the use of or reliance upon the information contained herein.

Prepared by: LEHDER Enviro

LEHDER Environmental Services Limited (519) 336-4101

www.lehder.com

Disclaimer:

While LEHDER Environmental Services Limited believes that the data set forth herein is accurate, as of the date hereof, LEHDER makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data is offered solely for your consideration, investigation and verification.