

SAFETY DATA SHEET

1/23/2026

SECTION I - IDENTIFICATION

Material Name

NASCO GLUE (MFG FOR NASCO INT'L)

Company Information

Handy Art, Inc.
 365 Sunnyside Drive
 Milton, WI 53563
 Phone: 1-608-868-6873
 Fax: 1-608-868-6233
 Email: handyart@handyart.com

For transportation emergencies only call: 608-868-6873

For health emergencies call the Poison Control Center: 1-800-222-1222

SECTION II - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

There are no GHS label elements.

SECTION III - COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

<u>Hazardous Ingredients</u>	<u>CAS/EC #</u>	<u>PEL/TLV (MG/M#)</u>	<u>Max % Weight</u>	<u>NTP</u>	<u>IARC</u>
None					

SECTION IV - FIRST AID MEASURES

FIRST AID MEASURES: NONE REQUIRED. NO ACUTE HEALTH EFFECTS EXPECTED.

SECTION V - FIRE FIGHTING MEASURES

FLASH POINT (METHOD): N/A
 EXPLOSION LIMITS IN AIR (% BY VOLUME): NOT EXPLOSIVE
 EXTINGUISHING MEDIA: NO SPECIAL MEDIA REQUIRED
 FIRE FIGHTING PROCEDURES: NO SPECIAL FIRE FIGHTING PROCEDURES REQUIRED
 UNUSUAL FIRE & EXPLOSION HAZARDS: NOT COMBUSTIBLE

AUTOIGNITION TEMPERATURE: N/A

SECTION VI - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE A MATERIAL IS SPILLED: Clean up in accordance with all applicable regulations. Absorb spillage with non-combustible, absorbent material. For waste disposal, see Section XIII

SECTION VII - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN DURING STORAGE AND HANDLING: Good industrial hygiene practice requires that exposure be maintained below the TLV. This is preferably achieved through the provision of adequate ventilation. When exposure cannot be adequately controlled in this way, personal respiratory protection should be employed.

SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION AND SPECIAL VENTILATION REQUIREMENTS: NONE REQUIRED
 OTHER PROTECTIVE EQUIPMENT (GLOVES, GOGGLES, ETC): NONE REQUIRED
 WORK/HYGIENE PRACTICES: NONE REQUIRED
 ENGINEERING CONTROLS: NONE REQUIRED

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: N/A
VAPOR PRESSURE: N/A
SPECIFIC VAPOR DENSITY (AIR=1): N/A
SOLUBILITY IN WATER: N/A

MELTING POINT: N/A
FLASH POINT (METHOD): N/A
SPECIFIC GRAVITY: N/A
REACTIVITY IN WATER: NON-REACTIVE

SECTION X - STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION PRODUCTS: N/A
STABILITY; STABLE CONDITIONS TO AVOID: N/A
INCOMPATIBILITY (MATERIALS TO AVOID): N/A
HAZARDOUS DECOMPOSITION PRODUCTS: N/A

SECTION XI - TOXICOLOGICAL INFORMATION

ACUTE EFFECTS ASSOCIATED WITH USE OF THIS MATERIAL: NONE EXPECTED
The summated LD50 is 13510 mg/kg.
The summated LC50 is 5957.6 mg/cubic meter.
This product is not considered to be a known or suspected human carcinogen by NTP, IARC or OSHA (see section III)

SECTION XII - ECOLOGICAL INFORMATION

HARMFUL EFFECTS KNOWN OTHER THAN THOSE ASSOCIATED WITH SUSPENDED INERT SOLIDS IN WATER.

SECTION XIII - DISPOSAL CONSIDERATIONS

RCRA HAZARD CLASS (40 CFR 261): THIS PRODUCT IS NOT CLASSIFIED AS A HAZARDOUS WASTE.
WASTE DISPOSAL METHOD: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

SECTION XIV - TRANSPORTATION INFORMATION

U.S. DOT (49 CFR 172.101): THIS IS NOT A HAZARDOUS MATERIAL AS CLASSIFIED BY CFR 172.101.

SECTION XV - REGULATORY INFORMATION

CONTENTS OF THIS SDS COMPLY WITH OSHA HAZARD COMMUNICATION STANDARD 29 CFR 1910.1200

EPA SARA TITLE III CHEMICAL LISTINGS:
SECTION 302.4 EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355):
NONE

SECTION 313 TOXIC CHEMICALS (40 CFR 372):
NONE

INTERNATIONAL REGULATIONS

CANADIAN WHMIS: THIS PRODUCT IS A CONTROLLED PRODUCT UNDER CANADA'S WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM. IT CONTAINS THE FOLLOWING TOXIC OR HIGHLY TOXIC MATERIALS:
FERRIC OXIDE
MICA
MICA/IRON OXIDE
MICA/TITANIUM DIOXIDE/IRON OXIDE
PIGMENT RED 2 DISPERSION
PROPYLENE GLYCOL
SODIUM TRIPOLYPHOSPHATE ANHYDR
TITANIUM DIOXIDE

Under CPSC's consumer product regulations (16CFR1500.3 and 150014), this product has the following required acute and chronic hazard labeling:

NONE

SECTION XVI - OTHER INFORMATION

AP (Approved Product) Seal



Conforms to
ASTM D 4236

Definition of the AP Seal:

The AP (Approved Product) Seal identifies art materials that are safe and that are certified in a toxicological evaluation by a board-certified toxicologist (medical expert) to contain no materials in sufficient quantities to be toxic or injurious to humans, including children, or to cause acute or chronic health problems. These products are certified by ACMI to be labeled in accordance with the chronic hazard labeling Standard, ASTM D 4236, and the U.S. Labeling of Hazardous Art Materials Act (LHAMA).

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

LAST REVISION DATE: 01/23/2026

Prepared by Duke OEM Toxicology